

M101P-ME, 10.1-inch Rugged Tablet PC

A Tablet Computer for Healthcare Professionals that Saves Time and Improves Efficiency

M101P-ME is a healthcare Windows-based tablet computer with a housing enhanced with antimicrobial properties, weighting at just 1200 grams (2.65 pounds). This mobile and portable device is flexible enough to function as a standalone device and competent enough to be used for all sorts of data collection, patient care, information management and wireless communication in Healthcare environments.

With rugged features, a crystal clear 1920 x 1200 resolution display, projected capacitive touch screen, barcode scanner and superior processing power coming from Intel's Apollo Lake processor, this tablet can be used in hospital halls, waiting rooms or nurse stations for communicating and documenting patient information, allowing paramedics and nurses to instantly access and keep patient records.



Highlights

- 10.1" 1920 x 1200 IPS LED Panel with direct optical bonding
- Intel® Apollo Lake Pentium N4200 processor
- Housing enhanced with antimicrobial properties
- Long battery life
- USB 3.0 (Type C) connector
- Optional 1D/2D barcode scanner to scan medications or wrist bands
- Lightweight, rugged, IP65 waterproof and dustproof
- IEC 60601-1, 60601-1-2 Healthcarely Certified

*Please consult your reseller or Winmate representative before purchasing.

*Accessories and Integrated Options may vary depending on your configuration. Visit Winmate website for more accessories and details.

Winmate



M101P-ME 10.1-inch Rugged Tablet PC

A Tablet Computer for Healthcare Professionals that Saves Time and Improves Efficiency

Display Specificatio	n	
Size	10.1-inch IPS display with LED Backlight	
Resolution Panel Brightness Touch Contrast Ratio Viewing Angle Technology System Specificatio	1920 x 1200 WUXGA 600 nit With direct optical bonding for sunlight readable Multi-touch projected capacitive 800:1 85/85/85/85 • Anti-glare technology • Ambient light sensor, e-compass, gyro, acceleratio sensors • Automatic screen rotation • Intel HD Graphics (built-in CPU) video controller	
Processor	Intel Pentium N4200 Processor 1.10 GHz, up to 2.50 GHz with turbo boost technolog 4GB SODIMM DDR3L-1600 (up to 8GB) ¹ 128GB solid state drive (SSD) Optional up to 512GB, up to 128GB additional storage with microSDXC card slot Windows 10 IoT Enterprise (64 bit)	
System Memory Storage Operating System		
Wireless Communio	ation	
WLAN Bluetooth GNSS WWAN	802.11 a/b/g/n/ac Bluetooth 5.0 GPS, GLONASS Optional 4G LTE	
Interface		
Docking Connector HDMI USB Power Input Micro SD Audio Connector Expansion Port	1 x 19-pin docking connector 1 x Micro HDMI 1 x USB3.0 (Type A), 1 x USB3.0 (Type C) ² 1 x Power Jack 1 x Micro SD Slot 1 x Audio Combo connector (Mic in or Line Out) 1 x Expansion Connector for USB 2.0 / Full RS232 (Optional)	
Keyboard and Input	:	
Touch Button LED Indicators	 10-point multi touch, support Rain, Glove, Stylus On-screen QWERTY keyboard Button 1 x power, 1 x Home, 2 x volume key, 2 x function key (Programmable function key configured by Hottab Utility) Power, Battery, HDD, RF 	
Audio		
Microphone Speaker	Built-in dual Digital Mic with Noise Cancellation 2 x 1 watt speaker	
Cameras		
Web Camera Rear Camera	2MP webcam 8MP rear camera with autofocus and LED light	
Data Capture		
Barcode HF RFID	Optional 1D/2D Barcode Reader Optional HF RFID reader 13.56 MHz	
Security Function		
Security	Password security for user and hard disk lock Trusted Platform Module (TPM) 2.0 Kensington Lock OTL Me increased	
Mobile Device Mgmt.	SOTI Mobicontrol compatible ³	
Regulatory Approv	als	
Certificate	 CE, FCC, IC IEC 60601-1, IEC 60601-1-2, EN 60601-1, ANSI/AAMI ES 60601-1 	

Mechanical and Environment

Dimension (W x L x H) Weight	1.2 kg (2.65 lbs) with standard battery,1.4 kg (3.1 lbs) with optional high capacity batteryRugged housing enhanced with antimicrobial propertie			
Housing Operating Temperature				
Storage Temperature	-30°C to 70°C			
Humidity IP Proof		% RH, non-condensing		
Shock	IP65 certified, Dustproof and waterproof MIL-STD-810G Method 516.6 Procedure I			
Vibration		IOG Method 514.6 Procedure I		
Drop	MIL-STD-81	IOG Method 516.6, 4 ft to concrete ⁵		
Power Management				
Power Input Battery	12-19V DC 7.4V, typ. 5140 mAh Li-Polymer Battery (2S1P) 7.4V, typ. 10280 mAh Li-Polymer Battery (2S2P, optional			
Battery Operating Time				
High Capacity Battery:				
Adapter	100-240V, 5	50-60Hz / 19V DC		
Accessories				
Standard Accessorie				
Adapter and Power Corc		922D072W19V0		
Capacitive Stylus		9B0000000415 98K000A00095		
Standard Battery	· Cortified			
Optional Healthcarely Certified Accessories 7 Healthcare Grade Tablet Dock 98DT00A00012				
Optional non-Healthcarely Certified Accessories 7				
Desk Dock	arely Cert	98DT00A0000F		
Vehicle Dock (without VGA output)		98K000A0003L		
Battery Charger		98KT00A0000F		
Smart Card Reader		98K000A0003U		
Hand Strap		98K000A0003J		
UHF RFID Reader		98K000A0004J		
VESA Mount Kit		98KT00A0001H		
Shoulder Strap		98K000A0003Q		
Carry Bag Micro HDMI Cable		9B00000003J 9491191190K1		
Vehicle Charger		9226065W19V0		
USB-C to Ethernet Adapter		9AN00000000		
USB-C to RS232 Adapter		9AN0000000L		
USB-C to USB-A Hub		9AN0000000J		
Drawing ⁸				
271.8	30			
	••••			
Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near				



Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example)

Caution hot or cold environments

- Total usable memory will be less depending upon actual system configuration.
 The USB Type-C connector follows USB 3.0 standard, which does not support Alternate Mode (ALT) or USB Power Delivery (USB-PD).
- 3. SOTI is available upon request.
- 4. Length measurements do not include protrusions. Weight varies with options and active pen.
- The drop test with high-capacity battery must come with hand strap.
 Measured at dimming LCD brightness. Varies depending on the usage conditions, or
- when an external device is attached." 7. Accessories and Integrated Options may vary depending on your configuration.
- 8. This is a simplified drawing and some components are not marked in detail.

Winmate

Release Date: 14-Jan-2020 V2.2



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660