

NDiS M335

Embedded Computer Power by Intel® Celeron® N3150
OPS Digital Signage Platform, Support Remote Management



Main Features

- Intel® Celeron® Processor N3150
- Integrated Intel® HD graphics
- Support 4K2K video out
- Dual SO-DIMM slots for up to 8GB of DDR3L 1600 memory
- WWAN/WLAN/TV Tuner support
- 2.5" HDD/SSD and NGFF dual storage
- Remote management (DASH)

Product Overview

NDiS M335 OPS player, which follows the electrical and mechanical specifications of the Open Pluggable Specification, is based on Intel® Celeron® Processor N3150 (formerly codenamed "Braswell"). NDiS M335 can be plugged into any OPS-complaint display devices to render rich multimedia contents. Thanks to the modular and cable-less, NDiS M335 OPS player satisfies the need for quick deployment and hassle-free maintenance of large digital signage network dispersed in different geographical locations.

Powered by future generation Intel® processor, the NDiS M335 OPS player with integrated new Intel® graphic engine can support 4K2K and Microsoft DirectX 11.1. Taking advantage of the latest Intel® technology, NDiS M335 can accelerate 3D rendering, image processing and video decoding to provide targeted audience highly personalized information base on the result of audience measurement to deliver accurate marketing messages.

Specifications

CPU Support

- Intel® Celeron® Processor N3150 Quad Core 1.6GHz SoC processor

Graphic

- Integrated Intel® HD graphics

Main Memory

- 2 x 204 pin SO-DIMM socket, support DDR3L 1600MHz with un-buffered and non-ECC SDRAM up to 8GB

I/O Interface-Front

- 1 x Power button
- 1 x Reset button
- 1 x HDD LED
- 2 x USB3.0
- 2 x USB2.0
- 2 x HDMI (HDMI2 support 4K2K output)
- 1 x Mic-in
- 1 x Line-out
- 1 x 2.5" HDD/SSD slot
- 1 x RJ45 with LEDs for Gigabit LAN
- 2 x antenna hole

I/O Interface-Rear

- 1 x TMDS

- 1 x Audio out L/R
- 2 x USB2.0
- 1 x USB3.0
- DC input +12V~+19V
- Control signals (PWR_STATUS, PS_ON#, PB_DET, CEC, SYS_FAN)

Storage Device

- 1 x 2.5" SATA storage bay for HDD/SSD
- 1 x NGFF(M2) B key slot, support 2242 SSD, SATA interface

Expansion

- 1 x mini-PCIe for optional WWAN/WLAN/TV tuner module
- 1 x SIM slot

Dimensions

- 200mm (W) x 119mm (D) x 30mm (H) (7.8" x 4.7" x 1.1")


Power Power Supply

- 1 x DC power input +12v ~ +19V

Environment

- Operating temperature:
Ambient with air flow from 0°C ~ 45°C
- Storage temperature: -20°C ~ 80°C
- Humidity: 10 to 90% (non-condensing)

www.nexcom.com



Certification

- CE approval
- FCC Class A

Operating System

- Win 7/WES7/Win8.1(64bit)/Win10/WE8S/Linux

Ordering Information

- **NDiS M335 (P/N: 10W00M33500X0)**
Intel® Celeron® N3150 processor SoC OPS

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660