




EMX-BYT2

Intel® Celeron® J1900 Processor Thin Mini ITX Motherboard

- > Intel® Celeron® J1900 Processor (2M Cache, Up to 2.42 GHz)
- > 2 x 204-pin DDR3L 1333 MHz SO-DIMM supports up to 8GB
- > VGA, HDMI, Dual channel 18/24-bits LVDS
- > 2 x Intel® i211AT Gigabit Ethernet
- > Realtek ALC662 Audio Codec
- > 1 x Mini PCI-e Supported mSATA, 1 x Mini PCI-e, 1 x PCI-e
- > 2 x SATA II, 2 x SATA Power, 2 x USB 2.0, 4 x USB 3.0
- > 5 x RS232, 1 x RS232/422/485, 8-bit GPIO
- > Mic-in, Line-out, 1 S/PDIF, Optional Infineon SLB9665 TPM 2.0
- > Onboard eMMC (Optional 32GB)
- > DC in +12V

+ Spec

System	
Processor	Intel® Celeron® J1900 Processor (2M Cache, Up to 2.42 GHz)
System Memory	2 x 204-pin DDR3L 1333 MHz SO-DIMM supports up to 8GB
I/O Chip	EC ITE IT8528E
BIOS	AMI 64Mbit SPI BIOS
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
Expansion	
Expansion	1 x PCI-e 1 x Mini PCI-e Supports mSATA (Switch Through Jumper) 1 x Mini PCI-e 1 x SD card slot supports SD/ SDHC Card 1 x SIM card slot
I/O	
USB	2 x USB 2.0 4 x USB 3.0
SATA	2 x SATA Power 2 x SATA II
COM Port	5 x RS232 1 x RS232/422/485
DIO	1 x 8-bit GPIO
Other	1 x S/PDIF
Display	
Chipset	Intel® Celeron® SoC integrated Graphics
Resolution	VGA: 2560 x 1600 @ 60Hz HDMI: 1920 x 1200 @ 60Hz LVDS 1920 x 1080 @ 60Hz
LVDS	Dual channel 18/24-bits LVDS 1920 x 1080 Chrontel. CH7511B eDP to LVDS Converter
Multiple Display	Dual Display
Audio	
Chipset	Realtek ALC662 supports 2-CH
Audio Interface	Mic-in, Line-out
Audio Amplifier	2 x Stereo Class-D 3W Audio Amplifier
Ethernet	
Chipset	2 x Intel i211AT Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ45
Mechanical & Environmental	
Power Requirement	+12V
Power Type	AT/ATX
Operating Temperature	0 ~ 60°C (32 ~ 140°F)
Storage Temperature	-40 ~ 75°C (-40 ~ 167°F)
Operating Humidity	0 ~ 90% Relative Humidity, Non-condensing
Dimension (L x W)	6.69" x 6.69" (170mm x 170mm)
Weight	0.88lbs (0.4Kgs)

+ Ordering

EMX-BYT2-A2R
Intel® Celeron® J1900 Processor Thin Mini ITX Motherboard

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660