

ADAM-4541 ADAM-4542+ ADAM-4561/4562

**Multi-mode Fiber Optic to RS-232/422/485
Converter**

**Single-mode Fiber Optic to RS-232/422/485
Converter**

**1-port Isolated USB to RS-232/422/485
Converter**



ADAM-4541



ADAM-4542+



ADAM-4561/4562



Specifications

General

- Power Input** Unregulated 10 ~ 30 V_{DC}
- Connectors** 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-232/422/485)
2 x ST fiber connector
- Power Consumption** 1.5 W @ 24 V_{DC}

Serial Communications

- Communication Mode** Asynchronous
- Speed Modes (bps)** 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k and RS-232/422 mode (switchable)
- Transmission Mode** Full/half duplex, bidirectional

Fiber Optic Communications

- Optical Power Budget (Attenuation)** 12.5 dB (measured with 62.5/125 μm)
- Transmission Distance** 2.5 km
- Transmission Mode** Multi mode (Send and Receive)
- Wavelength** 820 nm

Specifications

General

- Power Input** Unregulated 12 ~ 24 V_{DC}
- Connectors** 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-232/422/485)
1 x SC fiber connector
- Power Consumption** 3 W @ 24 V_{DC}
- Operation Modes** Support Point-to-Point, Redundant* and Ring (half-duplex)
1 μs
- Redundant Transfer Time** 1 μs

Serial Communications

- Communication Mode** Asynchronous
- Speed Modes (bps)*** 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k, 230.4 k, 460.8 k, 921.6 k and RS-232/422/485 mode (switchable)
- Transmission Modes** Full/half duplex, bidirectional

Fiber Optic Communications

- Optical Power Budget (Attenuation)** 15 dB
- Transmission Distance** 15 km
- Transmission Mode** Single mode (Send and Receive)
- Wavelength** 1310 nm

Specifications

General

- Connectors** Network: USB-type A connector (type A to type B cable provided)
Serial:
ADAM-4561 1 x plug-in terminal (#14 ~ 22 AWG) (3-wire RS-232/422/485)
ADAM-4562 1 x DB-9 serial connectors (9-wire RS-232)

Isolation Voltage

- ADAM-4561: 3,000 V_{DC}
- ADAM-4562: 2,500 V_{DC}

Power Consumption

- ADAM-4561: 1.5 W @ 5 V
- ADAM-4562: 1.1 W @ 5 V

Driver Support

- ADAM-4561: Windows 2000/XP/Vista/7/8 (32&64-bit)
- ADAM-4562: Windows 2000/XP/Vista/7/8 (32&64-bit)

USB Specification Compliance

- ADAM-4561: USB 2.0
- ADAM-4562: USB 2.0

Serial Communications

- Speed Modes (bps)** 75 bps to 115.2 kbps
- Transmission Modes** Full/half duplex, bidirectional

Common Specifications

Environment

- Operating Humidity** 5 ~ 95% RH
- Operating Temperature** ADAM-4541/4542+: -10 ~ 70°C (14 ~ 158°F)
ADAM-4561/4562: 0 ~ 70°C (32 ~ 158°F)
- Storage Temperature** -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- ADAM-4541** Multi-mode Fiber to RS-232/422/485 Converter
- ADAM-4542+** Single-mode Fiber to RS-232/422/485 Converter
- ADAM-4561** 1-port Isolated USB to RS-232/422/485 Converter
- ADAM-4562** 1-port Isolated USB to RS-232 Converter

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advantech:](#)

[ADAM-4541-BE](#) [ADAM-4542+-BE](#)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660