



## EPC-EHL

### Intel® Elkhart Lake Fanless Compact System

- > Intel® Elkhart Lake Processor x6413E
- > Intel® UHD Graphics, Max. Up to 32EU
- > 1-Memory Socket, Max. Up to 32GB DDR4 3200
- > Rich I/O, 4-USB, 1-HDMI, 1-DP, 2-LAN, 4-RS232, 1-Mic-in, 1-Line-out
- > 2-M.2, Key-E/B for Wi-Fi, LTE, SSD, I/O module
- > Fanless Operating Temp, -40 ~ 70°C
- > Wide Range DC Power Input, +9V~36V
- > Default dTPM 2.0, Wall Mount Kit

#### + Spec

System Information	
<b>Processor</b>	Intel Atom® x6413E Processor (1.5M Cache, up to 3.00 GHz, 9W)
<b>System Memory</b>	1 x 260-Pin SO-DIMM Socket, Max. Up to 32GB DDR4 3200MT/s
<b>BIOS Information</b>	AMI uEFI BIOS, 128Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec.
<b>H/W Status Monitor</b>	Monitoring System Temperature and Voltage with Auto Throttling Control
<b>TPM</b>	TPM 2.0
-Expansion-	
<b>M.2</b>	1 x M.2 (Key-B, 2242/3042, PCIe2, or ( PCIe1+USB3.1 GEN1), or (SATAIII + USB 3.1 GEN2), USB2.0, SIM Slot for LTE Cards) *Default is PCIe1/SATAIII+USB3.1 GEN1, others through BIOS Modification. 1 x M.2 (Key-E, 2230, PCIe1, USB2.0)
-Storage-	
<b>M.2</b>	1 x M.2 (Key-B, 2242)
<b>2.5" Drive Bay</b>	1 x 2.5" Drive Bay (7mm)
-Front I/O-	
<b>Power Button</b>	1 x Power Button
<b>LED Indicator</b>	1 x Storage Access LED
-Rear I/O-	
<b>USB Port</b>	2 x USB 3.1 Gen2 (10Gbps) 2 x USB2.0
<b>COM Port</b>	4 x RS232
<b>HDMI</b>	1 x HDMI 2.0b
<b>DP</b>	1 x DP 1.4a
<b>Audio</b>	1 x Mic-in 1 x Line-out
<b>RJ-45</b>	2 x RJ45
<b>LED Indicator</b>	1 x Power on/off LED 1 x Storage Access LED
<b>Antenna</b>	2 x Antenna Mounting with Dust Protection Cover
-Right I/O-	
<b>Antenna</b>	2 x Antenna Mounting with Dust Protection Cover
-Display-	
<b>Graphic Chipset</b>	Intel® UHD Graphics for 10th Gen Intel® Processors
<b>Resolution</b>	1 x HDMI 2.0b Max resolution 4096x2160@60Hz 1 x DP 1.4a Max resolution 4096x2160@60Hz
-Audio-	
<b>Audio Codec</b>	Realtek ALC888S
-Ethernet-	
<b>LAN Chipset</b>	2 x Intel® I226IT
<b>Specification</b>	2x 10/100/1000/2.5G Base-Tx GbE compatible
-Power Requirement-	
<b>DC Input Voltage</b>	Typical +9~36Vdc
<b>DC Input Connector</b>	1 x Lockable DC Jack
<b>Adapter</b>	Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 12V/5A AC-DC 60W Adapter
-Software Support-	
<b>OS Information</b>	Win10, Win11, Linux
-Certification-	



<b>Certification Information</b>	CE, FCC Class B
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	-40°C ~ 60°C (-40°F ~ 140°F) with 0.2m/s air flow -40°C ~ 70°C (-40°F ~ 158°F) with 0.5m/s air flow
<b>Storage Temperature</b>	-20°C ~ 60°C (-4°F ~ 140°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	177 x 123 x 65mm
<b>Vibration Test</b>	With SSD: 5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis
<b>Shock Test</b>	With SDD : 55G, IEC 60068-2-27, Half Sine, 11ms, 3Axis, 6 Face
<b>Drop Test</b>	ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces
<b>Mounting Kit</b>	Wall Mount Kit (Default)
<b>Construction</b>	Aluminum + Metal
<b>Ordering Information</b>	
<b>Ordering Information</b>	EPC-EHL-X13-B1-1R Intel® ATOM® Processor x6413E Fanless Compact System  E1702031831R Australia Power Cord  E1702031833R USA Power Cord  E170P060380R UK Power Cord  E1702031000R EU Power Cord

[www.avalue.com.tw](http://www.avalue.com.tw)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660