

AIR6NO-C-MB NX

YUAN

Business Card Size AI Edge Motherboard

Features

- · Powered by NVIDIA® Jetson Orin™ NX Super up to 157 / 117 TOPS
- · Business Card Size
- · 2×M.2 Gen 4×2 M Key / Gen 4×1 E Key
- · 1×USB3.2 Gen2
- · 1×Mini DisplayPort



Specifications

System	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano			
SOM	16GB Super	8GB Super	8GB Super	4GB Super			
CPU	8-Core Arm® Cortex®-A78AE v8.2	6-Core Arm® Cortex®-A78AE v8.2	6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3				
	64-Bit CPU 2MB L2 + 4MB L3	64-Bit CPU 1.5MB L2 + 4MB L3					
GPU	1024-Core NVIDIA Ampere Architecture GPU with 32 Tensor Cores		1024-core NVIDIA Ampere	512-core NVIDIA Ampere			
			Architecture GPU with 32 Tensor Cores	Architecture GPU with 16 Tensor Cores			
Al Performance	157 TOPS	117 TOPS	67 TOPS	34 TOPS			
	16GB 128-bit LPDDR5	8GB 128-bit LPDDR5	8GB 128-bit LPDDR5	4GB 64-bit LPDDR5			
System Memory	102.4GB/s	102.4GB/s	102 GB/s	51 GB/s			
Interface							
Storage	Supports External NVMe						
Display Interface	1×Mini DP1.4						
Ethernet	1×RJ45 for 10/100/1000Mbps Ethernet (DHCP Client)						
Expansion Slot	1×M.2 2230 M Key PCle Gen4×2 Slot (Nano: Gen3×2)						
Expansion siot	1×M.2 2230 E Key PCle Gen4×1 Slot (Nano: Gen3×1)						
USB	1×USB3.2 Gen2 (Type-C)						
MIPI	8 MIPI CSI-2 Lanes (D-PHY 2.1, Support MIPI Camera, Capture Card) Custom Connector						
Peripheral Communication	2×USB3.2 Gen2 1xPCle Gen4×4 4×GPIO 2×UART (UARTO(*), UART1) 3×12C 1×CAN Bus 10 Pin Header 1×USB2.0 4×GPIO 1×12C 6 Pin Wafer 1×UART (*) 4 Pin Header						
	5V/3A						
	* Please select either Custom Connector UART or 6 Pin Wafer UART to use						
Misc. Features	Firmware Upgradable	Firmware Upgradable					
Development Environment							
JetPack	6.2 or Higher						
Environment							
Power Supply	DC input: 12~36V						
Power Consumption	TBA						
Operating Temperature	0~60 C with Airflow						
Storage Temperature	-20~80 °C						
Certification	CE, FCC						



SDK / Software

Video Feature					
SOM	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano	
30101	16GB Super	8GB Super	8GB Super	4GB Super	
Video Encode	AV1 (UHP)				
	1×4K60 3×4K30 6×1080p60 12×1080p30		1080p30 supported by 1-2 CPU cores		
	H.265 (UHP)				
	1×4K60 3×4K30 6×1080p60 12×1080p30				
	H.264 (UHP)				
	1×4K60 2×4K30 5×1080p60	11×1080p30			
	AV1 (Main Profile)		AV1 (Main Profile)		
	1×8K30 2×4K60 4×4K30 10×1080p60 20×1080p30		1×4K60 2×4K30 5×1080p60	10×1080p30	
	H.265 (Main, Main10)		H.265 (Main, Main10)		
Video Decode	1×8K30 2×4K60 4×4K30 9×1080p60 18×1080p30		1×4K60 2×4K30 5×1080p60 11×1080p30		
	H.264 (Baseline, Main, High)		H.264 (Baseline, Main, High)		
	1×4K60 2×4K30 5×1080p60 11×1080p30		1×4K30 3×1080p60 7×1080p30		
	VP9 (Profile 0, Profile 2)		VP9 (Profile 0, Profile 2)		
	1×4K60 3×4K30 7×1080p60 15×1080p30				
SDK					
	Capture				
	High Performance Renderer				
	Image Snapshot				
	De-interlace, Alpha Blending Engine				
	Auto Signal Detection 2D/3D Video, Audio and VANC Streams Capture				
	Record				
	Encrypt / Sync / Clone / Recording				
	Time-Shifting / Rewind / Pre-Event / Recording				
QCAP	Multi-Streams (3D) Recording				
	Animation Transition Effect				
	Video Cropping, Scaling and Alpha Blending Engine				
	Stream				
	2D/3D Universal Stream Client				
	2D/3D Multi-Streams Stream Server				
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)				
	Animation Transition Effect				
	Video Cropping, Scaling and Alpha Blending Engine				
	*Separate License Required				
	AI SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications				
	Face Recognition				
	Objects Detection				
QDEEP	Objects Segment Optical Character Recognition				
	License Plate Recognition				
	Customizable Video Al Functions Upon Request				
Software (Optional)	Custoffizubie Video Al i difetions	орон нечиезе			
Software (Optional)	W.I. B I II I I f				
	Web Based User Interface		Management Manag	Signal Si	
Xtreamer	Encode / Decode				
	AV1, H.26X				
	Color Format Adjust 444 / 422 / 420, 10Bit / 8Bit Select				
	Record MP4, TS				
	Marie Mari				
	Stream / Network				
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*) *Separate License Required				
	separate dicense nequined				

Mechanical

· Dimension: $90\text{mm} \times 55\text{mm}$

 \cdot Weight: 130g (With SOM and Fan)

Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.

 $^{^{}st}$ All registered trademarks are the property of their owners. The photo is for reference only.

^{*} Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660