

PPC

PPC-1207F

**Industrial 7" Widescreen
MIPS-Based Panel PC
with the RMI AU1250
500MHz processor**

Features and Benefits:

- Low Power MIPS based HMI
- Fanless Design for Rugged Environment and Quiet Application
- Greater viewing 16:9 Screen Ratio
- Supports 2GB SD Slot for extra storage
- Front Panel IP65 Certificate
- OS supports for Microsoft Windows CE 5.0



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714-996-7200 FAX: +1-714-996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.

OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001




www.protech.com.tw


PPC-1207F

Industrial 7" Widescreen MIPS-Based Panel PC
with the RMI AU1250 500MHz processor

Front View



Rear View



Side View



Unit: mm

Specification

Systems	
CPU Type	RMI Alchemy™ Au1250™ 500MHz
Flash ROM	64MB Nor Flash ROM for O.S / 64MB NAND Flash ROM for Storage
Memory	128MB DDRII (533MHz)
Front Panel Protection	IP65 Compliant
Power Requirement	DC in (14~30V) only
Power Consumption	8.5W
Construction	Aluminum front bezel/ Rugged Metal Housing
Mounting	Wall, Stand, Vstand, and ARM (VESA 75 x 75)
O.S. Support	Windows CE 5.0
Dimension (W x H x D)	235 x 150 x 41.5 mm (9.25" x 5.9" x 1.6")
System Weight	1.9kg

I/O Ports

LAN	1 x 10/100Mbps LAN
USB	2 x USB 2.0
Serial Port	2 x COM ports, (COM 1 for RS-232, COM 2 for RS232/RS422/RS485 selectable, All COM ports support +5V/+12V selectable)
Audio	1 x Line out
Speaker	1 x 1.5W internal speakers (option)
Digital I/O	4 in/ 4 out (reserved on board)
Expansion Slots	1 x SD slot

Display

LCD	7"
Brightness (cd/m²)	320 cd/m²
Backlight MTBF	30,000 hrs
Touchscreen	Resistive Type 4-wire
Backlight	LED

Environment

Operating Temp.	-10° ~ 45°C (32°~110°F)
Storage Temp.	-20° ~ 60°C (-4°~140°F)
Humidity	20% ~ 90%

Ordering Information

PPC7527-AB01A	HSF, 7" Panel PC, w/ 800*480 LCD / 4-Wire Touch/ RMI 500MHz
52-002-09065001	65W, 19V DC Output Power Adaptor

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd.
All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Mar. 2010.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660