

## Digital Signage Displays

### EA32C-1D

**VESTEL**




## Key Features



### Auto Launch

We have made it easy to give any HTML5-based application link to the display within the SoC software. Upon this, the display will start with the given link. The application can either be an offline or an online application, allowing the customers to execute their own application.



### Pixel Shifting

Pixel Shifting is designed to be activated inside the SoC in order to prevent for potential risk of image sticking, caused by constant content. With this feature turned on, pixels on the screen will move in an interval while causing no interference of visual experience.



### Scheduler

Digital Signage Monitor Software allows many important features such as Scheduler. Scheduler sets your display turn on/off time easily and lets you not to worry about the status of your displays in any time.



### Source Switching

It is made available to set any Source on startup of the display. It can also be switched on any other signal source using scheduler and failover scenarios. This lets the users to freely control the process of their requirements allowing best user experience.



### Signal Failover

Our SoC Software has a protection for "No Signal" scenario. If the USB is unplugged after your content is set to be displayed with USB, the display will either show your customized banner or search for any other signal from other sources (HDMI, Display Port, etc.). This failover protection is constructed for higher user experience.



### **Display Control**

Digital Signage Display SoC enables the users to control our displays using RS232 commands in a Local Area Network. Together with the full RS232 command list you can change/set volume, turn on/off the monitor, set a schedule for content display, set a webpage link to be displayed and give a wide range of commands in real-time.

### Panel

Screen Size	32"	Panel Technology	FSA (VA)
Backlight Type	Direct-Type LED	Brightness (typical)	350 cd/m <sup>2</sup>
Native Resolution	1920 x 1080 (16:9) - FHD	Contrast Ratio (typical)	3000:1
Dynamic Contrast Ratio	35000:1	Response Time (typical)	8.5 ms
Active Area (H x V)	698.40 x 392.85 mm	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	16.7M (8bits)	Screen Treatment	3H
Haze Level	0,03	Refresh Rate	60 Hz
Orientation	Landscape	Operation Hours	16/7
Area of Usage	Indoor		

### Built-in System

Mainboard Model	17MB130VS	Operating System	Linux (HTML5 based app support)
Wired	10/100 Mbps	WiFi	WiFi 4 (802.11 a/b/g/n)
Bluetooth	NA		

### Monitor Connectivity

RGB Input	N/A	RGB Output	N/A
Video Input	1xHDMI2.0, 2xUSB2.0, DP1.2a	Video Output	DP1.2a
Audio Input	N/A	Audio Output	Headphone
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

### Mechanical

Product Dimensions (WxDxH)	734 x 78 x 435 mm	Package Dimensions (WxDxH)	795 x 128 x 530 mm
Product Weight	TBD	Package Weight	TBD
Vesa Mounting	75 x 75 mm M4	Bezel Width	B:21   T/ L/R:14 mm

### Environmental Conditions

Operating Temperature	0-40°C	Operating Humidity	10-90%
-----------------------	--------	--------------------	--------

### Power

Power Supply	170 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

### Power Consumption

Typical	42 W	Maximum	65 W
Deep Standby	≤0.5 W		

### Features

Mechanical Features	Joystick, IR Extender or Embedded IR Support Options, Rocker Switch, Detachable power cable(Class 2), Logo on bezel only horizontal	Speaker	2 x 6 W
---------------------	---	---------	---------

### Certification

Safety	YES	EMC	YES
CE	YES		

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660