


OPS500-501 NEW

Open Pluggable Specification (OPS) Digital Signage Player with 6th/7th Gen Intel® Core™ i7/i5/i3 & Celeron® Processor, Intel® Q170 and AMT 11.0

Features

- Intel® Open Pluggable Specification (OPS compliance)
- 6th/7th gen Intel® Core™ i7/i5/i3 & Celeron® processors (Skylake/Kaby Lake)
- DDR4-2133 SO-DIMM, up to 16GB
- 1 PCI Express Mini Card slot
- Easy installation and maintenance
- HDMI for 2nd ultra HD display with 4K@60 Hz resolution
- Intel® AMT (Active Management Technology) 11.0



- | | | |
|---------------------|---------------------|-----------------------|
| 1. JAE TX-25A | 6. Power switch | 11. USB 2.0 x 1 |
| 2. Optional antenna | 7. Reset | 12. USB 3.0 x 2 |
| 3. RS-232 | 8. HDD indicator | 13. Optional antenna |
| 4. Ethernet | 9. Audio (Line-out) | 14. 2.5" SATA HDD |
| 5. HDMI output | 10. Audio (Mic-in) | 15. 12VDC power input |



15. JAE TX-25A
1. 12VDC power input



Specifications

Main System	CPU	LGA1151 socket 6th/7th gen Intel® Core™ i7/i5/i3 & Celeron® processor
	Chipset	Intel® Q170
	System Memory	1 x 260 pin DDR4-2133 SO-DIMM, up to 16GB
	Storage	1 x 2.5" SATA HDD tray 1 x mSATA (option)
	Watchdog Timer	255 levels, 1-255 sec.
I/O	2 x USB 3.0	
	1 x USB 2.0	
	1 x 10/100/1000 Mbps Ethernet (Intel® i219LM)	
	1 x HDMI with 4K resolution	
	1 x RS-232 (COM 2)	
	1 x Power on/off button	
	1 x Reset button	
	1 x Audio (Line-out)	
	1 x Audio (Mic-in)	
	1 x DisplayPort (4K@60 Hz via OPS JAE interconnector)	
	1 x HDMI 2.0 (4K@60 Hz via OPS JAE interconnector)	
	2 x USB 2.0 (via OPS JAE interconnector)	
	1 x USB 3.0 (via OPS JAE interconnector)	
	1 x Audio (Line out, via OPS JAE interconnector)	
1 x UART (TX/RX, via OPS JAE interconnector) (COM1)		
1 x 12 VDC power input by adapter option		
Indicator	1 x LED for system power on	
	1 x LED for HDD active	
WiFi	802.11 b/g/n (optional)	
Expansion Slot	1 x full-size PCIe Mini Card (USB + PCI Express + SATA signal)	
Dimensions	200 mm (7.87") (W) x 119 mm (4.68") x 30 mm (1.18")	
Packing Dimension	270 mm (10.63") (W) x 197 mm (7.76") x 70mm (2.76")	
Weight (net/gross)	1 kg (2.21lb)/1.5 kg (3.3 lb)	
Environmental	0°C ~ +45°C (+32°F ~ +113°F) (with airflow 1.2m/s)	

Packing

- 1 x Driver CD
- 1 x Thermal grease
- 2 x M2 x 5 screw
- 2 x M4 x 6 screw

* All specifications and photos are subject to change without notice.

Optional OS Installation

Windows® 8.1, Windows® 10

Ordering Information

Standard


OPS500-501	OPS digital signage player with LGA1151 socket Intel® Core™ i7/i5/i3 & Celeron® processors and iAMT 11.0
------------	--

Optional

AX93167	OPS docking board with 4K resolution
AX93190	OPS docking board with 4K/60 Hz resolution+WLAN kit

* Specifications and certifications may vary contingent on options.

Dimensions



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660