

LNP-1002G-10G-SFP-24

10-Port Industrial Gigabit PoE+ Unmanaged Ethernet Switch, with 8*10/100/1000Tx (30W/Port) and 2*10G SFP+ Slots; 12~55VDC Power Input



Features


- ▶ Supports 8*10/100/1000Tx IEEE 802.3af/at
- ▶ Compliant with 30W/Port and 2*10G SFP+ Slots
- ▶ Store-and-Forward Switching Architecture
- ▶ 56Gbps Back-Plane (Switching Fabric)
- ▶ 16K MAC Address Table
- ▶ 9.6Kbytes Jumbo Frame Support
- ▶ Redundant Power Input Design: 12~55VDC
- ▶ Built-in 1 Relay Output for Power Failure Warning
- ▶ IP30 Rugged Metal Case Design
- ▶ DIN-Rail and Wall Mount Support Included
- ▶ Operating Temperature Range: -40°~65°C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' LNP-1002G-10G-SFP-24 are industrial gigabit PoE+ unmanaged Ethernet switches featuring 8*10/100/1000Tx Gigabit Ethernet ports that support IEEE802.3at for a maximum of 30W/port. The LNP-1002G-10G-SFP-24 is designed with 2*10G SFP+ slots which provide options for long-distance fiber connections. The Ethernet switches are designed with high EFT and ESD protection and support standard operating temperature from -40° to 65°C.

The LNP-1002G-10G-SFP-24 are IP30 rated and DIN-rail mountable. These Ethernet switches are designed to be powered with low voltage input (12~55VDC) while still providing the higher voltages required by the PoE standards. Additionally, these industrial PoE Ethernet switches provide connectivity for outdoor or harsh industrial automation application environments, such as security surveillance, ITS-traffic monitoring systems, oil/gas and mining, facility management for power/utility, water wastewater treatment plants, and lastly, automated production lines in factory automation.

DIMENSIONS



SPECIFICATIONS

Technology		Mechanical Characteristics	
Standards	IEEE 802.3 10Tx Ethernet	Housing	Metal, IP30 protection
	IEEE 802.3u 100Tx Fast Ethernet	Dimension	54 x 142 x 99 mm
	IEEE 802.3ab 1000Tx Gigabit Ethernet	Weight	Unit: 2.5 lbs.; Shipping: 3.12 lbs.
	IEEE 802.3ae 10 Gigabit Ethernet	Mounting	DIN-Rail mounting, Wall mounting
	IEEE 802.3af/at Power over Ethernet	Power Requirement	
Processing Type	Store and Forward	Input Voltage	12~55VDC Redundant Input
Protocol	CSMA/CD	Power Connection	1 removable 6-contact terminal block
Flow Control	IEEE 802.3x back pressure flow control	Relay Contact	24 VDC, 1A resistive
Switch Properties		Overload Current Protection	Present
Switch Architecture	Back-Plane (Switching Fabric): 56.0Gbps	Power Reverse Polarity Protection	Present
Transfer Rate	14,880pps for 10Base-T Ethernet	System Power Consumption	10.2W
	148,800pps for 100Base-T Fast Ethernet	Max PoE Power Budget	90W @12VDC, 180W @24VDC, 240W @36~55VDC
	1,488,000pps for 1000Base-T Gigabit Ethernet	PoE Power Output	30W max. per PoE port
Packet Buffer	8Mbits	Environmental Limits	
Jumbo Frame	9.6Kbytes	Operating Temperature	-40°C to 65°C
MAC Table Size	16K	Storage Temperature	-40°C ~ 85°C
Port Interface		Ambient Relative Humidity	5 to 95%, (non-condensing)
Ethernet Port	8*10/100/1000Tx (PSE: 30W/Port) Auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	Regulatory Approvals	
SFP Port	2*10G SFP+ slots	EMI	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
PoE Pin Out	V+, V+, V-, V-, for pin 1, 2, 3, 6 (End-span, Mode A)	EMS	CE EN55035/EN61000-6-2 Class A, IEC61000-4-2,3,4,5,6,8
LED Indicators	System: Power 1, Power 2, Fault	Free Fall	IEC60068-2-32
	Ethernet Ports: On-Link/Flash-data transmitting	Shock	IEC60068-2-27
Network Cable	PoE: On-connected to PD devices	Vibration	IEC60068-2-6
	SFP: Link/Active	Green	RoHS Compliant
	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m)	Certifications	FCC, CE, UL 61010-1, 61010-2-201
	100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)	Warranty	5 Years
1000BaseTX: 4-pair UTP/STP Cat.5/5E cable EIA/TIA-568 100-ohm (100m)			

ORDERING INFO

LNP-1002G-10G-SFP-24	10-Port Industrial Gigabit PoE+ Unmanaged Ethernet Switch, with 8*10/100/1000Tx (30W/Port) and 2*10G SFP+ Slots; 12~55VDC Power Input
-----------------------------	---

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660