


# IMB-1244-WV

Mini-ITX Motherboard



## KEY FEATURES

- Intel® 14th/13th/12th Gen (Raptor Lake-S Refresh/Raptor Lake-S/Alder Lake-S) Core™ Processors with Q670 chipset
- 2 x 262-pin SO-DIMM DDR5 4800/5600 MHz, up to 96GB (48GB per DIMM)
- 1 x Right Angle PCIe x16 (Gen4)
- 4 x USB 3.2 Gen2, 2 x USB 3.2 Gen1, 4 x USB 2.0, 1 x M.2 Key B, 1 x M.2 Key E, 2 x M.2 Key M, 3 x COM, 2 x SATA3
- 1 x Intel 2.5 Gigabit LAN, 1 x Intel 1 Gigabit LAN
- Supports Quad display, 2 x HDMI 2.0b, 1 x DP 1.4a, 1 x LVDS, 1 x eDP 1.4b
- Supports Intel® vPro, VMD RAID 0/1
- TPM 2.0 onboard IC
- 12~28V DC-In

## SPECIFICATIONS

### Form Factor

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| Dimensions (LxWxH) | Mini-ITX (6.7-in x 6.7-in x 1.0-in, 17.0 cm x 17.0 cm x 2.6 cm) |
|--------------------|-----------------------------------------------------------------|

### Processor System

|         |                                                                                                          |
|---------|----------------------------------------------------------------------------------------------------------|
| CPU     | Intel® 14th/13th/12th Gen (Raptor Lake-S Refresh/Raptor Lake-S/Alder Lake-S) Core™ Processors, up to 65W |
| Chipset | Intel® Q670                                                                                              |
| Socket  | LGA1700                                                                                                  |
| BIOS    | AMI SPI 256 Mbit                                                                                         |

### Memory

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technology | Dual Channel DDR5 4800/5600 MHz*<br>*Actual memory frequency depends on the CPU types and DRAM modules, for more information refer to <a href="https://www.asrockind.com/en-gb/index.php?route=newsblog/faq&amp;faq_id=90">https://www.asrockind.com/en-gb/index.php?route=newsblog/faq&amp;faq_id=90</a> technical FAQ<br>*If motherboard ambient temp. is over 55°C, the memory thermal solution should be added to avoid thermal issue. |
| Capacity   | 96GB (48GB per DIMM)                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Socket     | 2 x 262-pin SO-DIMM                                                                                                                                                                                                                                                                                                                                                                                                                        |

### Graphics

|              |                                                               |
|--------------|---------------------------------------------------------------|
| Controller   | Intel® UHD Graphics                                           |
| HDMI         | HDMI 2.0b<br>Max resolution up to 4096x2160@60Hz              |
| DisplayPort  | DisplayPort 1.4a, DP++<br>Max resolution up to 4096x2160@60Hz |
| LVDS         | Dual channel 24 bit up to 1920x1200@60Hz                      |
| eDP          | eDP 1.4b<br>Max resolution up to 4096x2160@60Hz               |
| MultiDisplay | Quad display                                                  |

### Expansion Slot

|            |                                                                                                                                                       |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| PCIe       | 1 x Right Angle PCIe x16 (Gen4, Support riser card x8/x8)                                                                                             |
| M.2        | 1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless<br>1 x M.2 (Key B, 3042/3052) with PCIe x1, USB 3.2 Gen1, USB 2.0 and SIM for 4G/5G |
| SIM Socket | 1 x SIM socket connected to M.2 key B                                                                                                                 |

### Audio

|           |                                                          |
|-----------|----------------------------------------------------------|
| Interface | Realtek ALC897, High Definition Audio. Line-out, Line-in |
|-----------|----------------------------------------------------------|

### Ethernet

|                   |                                                                                                           |
|-------------------|-----------------------------------------------------------------------------------------------------------|
| Controller/ Speed | LAN1: Intel® I226V with 10/100/1000/2500 Mbps<br>LAN2: Intel® I219LM with 10/100/1000 Mbps, supports vPro |
| Connector         | 2 x RJ-45                                                                                                 |

### Rear I/O

|             |                                                      |
|-------------|------------------------------------------------------|
| HDMI        | 2 x HDMI 2.0b                                        |
| DisplayPort | 1 x DP 1.4a++                                        |
| Ethernet    | 1 x 2.5 Gigabit LAN<br>1 x 1 Gigabit LAN             |
| USB         | 4 x USB 3.2 Gen2                                     |
| Audio       | 2 (Line-in, Line-out or Mic-in, Line-out (optional)) |

### Internal Connector

|                 |                                                                              |
|-----------------|------------------------------------------------------------------------------|
| USB             | 2 x USB 3.2 Gen1 (1 x USB 3.2 header)<br>4 x USB 2.0 (2 x 2.54 pitch header) |
| COM             | COM1, COM3 (RS-232/422/485)<br>COM4 (RS-232)                                 |
| GPIO            | 4 x GPI, 4 x GPO                                                             |
| LVDS            | 1                                                                            |
| eDP             | 1                                                                            |
| SATA PWR Output | 1                                                                            |
| Speaker Header  | 1                                                                            |

### Storage

|      |                                                                                                                                                                                                                      |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| M.2  | 1 x M.2 (Key M, 2242/2280) with PCIe Gen4 x4 for SSD<br>1 x M.2 (Key M, 2242) with PCIe Gen4 x4 and SATA3 for SSD*<br>*Recommend using M2x4-SATA-4P module to support extra 4 SATA ports (supported by special BIOS) |
| SATA | 2 x SATA3 (6Gb/s)                                                                                                                                                                                                    |
| RAID | Intel® VMD RAID 0/1<br>**supported by identical interface (PCIe or SATA)<br>PCIe interface: M.2 Key B + M.2 Key M1/2 or 2 x M.2 Key M<br>SATA interface: SATA port                                                   |

### Security

|     |                    |
|-----|--------------------|
| TPM | TPM 2.0 onboard IC |
|-----|--------------------|

### Watchdog Timer

|          |                                  |
|----------|----------------------------------|
| Output   | From Super I/O to drag RESETCON# |
| Interval | 256 Segments, 0, 1, 2, ...255sec |

### Power Requirements

|           |                                                                                                                           |
|-----------|---------------------------------------------------------------------------------------------------------------------------|
| Input PWR | 12~28V DC-In with 4-pin wafer PWR cable                                                                                   |
| Power On  | AT/ATX Supported<br>- AT : Directly PWR on as power input ready<br>- ATX : Press button to PWR on after power input ready |

### Environment

|                    |                |
|--------------------|----------------|
| Operating Temp     | -20°C ~ 70°C   |
| Storage Temp       | -40° C ~ 85° C |
| Operating Humidity | 5% ~ 90%       |
| Storage Humidity   | 5% ~ 90%       |

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660