

# Hisense

86" Advanced Interactive Display



## **86WR60AE** 86" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Digital Display's deliver unrivalled performance and value. They combine the power of a digital display, tablet, electronic whiteboard and video conference device to deliver the ultimate all-in-one display solution. Interactive Digital Boards (65"/75"/86") have been designed to facilitate market leading knowledge sharing in both business and educational environments. They are touch enabled and have multiple users them at once to present, illustrate and share information.



#### Highlights



#### Smooth Touch

The built-in whiteboard app allows users to smoothly write, draw and erase information on-screen through touch, either by hand or with a stylus pen.



#### **Collaborative interaction**

The touchscreen recognises up to 20 touches at once which is ideal for simultaneous use by meeting participants.



#### Smooth and speedy processing

The open Android 8.0 platform not only guarantees smooth processing, but also supports the installation of Android-based application.



#### Comfortable viewing

Each of our Interactive Digital Boards has a filter to effectively reduce blue light so your eyes remain comfortable even when using the screen for longer periods of time.

Tempered Glass Hisense's WR series have heat treated tempered glass preventing any damage to the touch panels.







Specification subject to change | October 2021





#### Accurate as analog

The IR software precisely recognizes touch points as little as 2 mm making it as accurate as the experience of writing with pen and paper.



#### Intuitive controls

With your fingers you will, among other things, be able to switch between tasks, annotate content from any source, make handwritten notes, zoom in / out and undo changes.

#### **Powerful Architecture**

Expect unstoppable performance by an octa-core processor and 3+32GB large memory.



#### Immersive Sound

Thanks to embedded dual-channel Dolby sound the Hisense WR series will give their users and audiences a cinematic audio-visual experience.

Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



## Hisense

### Specifications

86" Advanced Interactive Display


| Interactive Display Panel                       |                                                                                                                                  |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| LCD Size                                        | 86"                                                                                                                              |
| Backlight Type                                  | D-LED                                                                                                                            |
| Resolution                                      | 3840x2160(pixels)                                                                                                                |
| Brightness                                      | 360cd/m²(typ.)                                                                                                                   |
| Contrast Ratio                                  | 1200:1(typ.)                                                                                                                     |
| Response Time                                   | 8ms (typ.)                                                                                                                       |
| Refreshing Frequency                            | 60Hz                                                                                                                             |
| Viewing Angle                                   | 178°(H) / 178°(V)                                                                                                                |
| Life Time                                       | 30,000 hrs (min.)                                                                                                                |
| Color Gamut(X% NTSC)                            | 85%                                                                                                                              |
| Display Colors                                  | 1.07B(10bit)                                                                                                                     |
| System                                          |                                                                                                                                  |
| 05                                              | Android 8.0                                                                                                                      |
| Language                                        | Chinese/English/German/French/Italian<br>/Spanish/Thai/Indonesian                                                                |
| Speaker                                         |                                                                                                                                  |
| Audio Output Power                              | 2x15W/8Ω                                                                                                                         |
| Connectivity                                    |                                                                                                                                  |
| Input                                           | HDMI IN x 2<br>DP IN x 1<br>VGA IN x 1<br>DPS(optional) x1<br>LAN x 1<br>USB x 4<br>Touch x 1<br>PC-Audio IN x 1<br>RS232 IN x 1 |
| Output                                          | HDMI OUT x 1<br>S/PDIF OUT x 1                                                                                                   |
| Power                                           |                                                                                                                                  |
| Power Requirements                              | AC 100 V ~ 240 V, 50/60 Hz                                                                                                       |
| Power Consumption Without OPS                   | 460W                                                                                                                             |
| Touch                                           |                                                                                                                                  |
| Sensing Type                                    | Infrared Touch Frame                                                                                                             |
| Surface Protection                              | 4mm Anti-Glare Glass                                                                                                             |
| Infrared Touch                                  | ≤20 points                                                                                                                       |
| Touch Accuracy                                  | 90%(±1mm)                                                                                                                        |
| Response Time                                   | ≤8ms                                                                                                                             |
| Minimum Touch Object                            | ≥2mm                                                                                                                             |
| Certification                                   |                                                                                                                                  |
| Standard CertificationCB,CE,ICASAEAN69731729401 | $CB CE ERP \triangle$                                                                                                            |

| Physical                   |                                                                      |
|----------------------------|----------------------------------------------------------------------|
| Thysical                   |                                                                      |
| Housing Color              | Black                                                                |
| Product Size (W x H x D)   | 1972 × 1192 × 116mm                                                  |
| Package Size (W x H x D)   | 2171 × 1382 × 341mm                                                  |
| Net Weight                 | 74.2kg                                                               |
| Packed Weight              | 102kg                                                                |
| VESA                       | 1000x400mm, 4-M8 screw                                               |
| Optional                   |                                                                      |
|                            |                                                                      |
|                            | Mobile Cart                                                          |
| Basic                      | Mobile Cart                                                          |
| Basic                      | Mobile Cart<br>OPS                                                   |
| Basic<br>What's in the box |                                                                      |
|                            |                                                                      |
|                            | OPS                                                                  |
|                            | OPS<br>User manual                                                   |
|                            | OPS<br>User manual<br>Pen × 2                                        |
| What's in the box          | OPS<br>User manual<br>Pen × 2<br>Remote Control                      |
| What's in the box          | OPS<br>User manual<br>Pen × 2<br>Remote Control<br>Hanging Wheel × 4 |

Battery × 2

Wall Mount Bracket

#### Dimensions



8 2

**HISENSE B2B EUROPE** 

Beechavenue 139, I 119 RB Schiphol-Rijk,

sales@hisense-b2b.co

www.hisense-b2b.com +44 (0)115 8248811



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660