

# MPC152-845

15" XGA TFT Fanless Medical Grade Touch Panel Computer with Intel® Celeron® Processor N3060

## **Features**

- 15" XGA TFT LCD display with LED backlight
- Fanless design with Intel® Celeron® processor N3060
- 2 GbE LANs, 4 USB and 2 COM
- Plastic and IP65-rated front bezel
- Supports RFID (optional)
- External AT/ATX mode selection switch
- Easy access storage design
- Supports panel mount, wall mount, VESA arm and desktop stand
- Adjustable RS-232/422/485 setting via BIOS
- 4th EN 60601-1 (ESD contact 8KV, air 15KV), CE and FCC



A Side view



#### Introduction

The MPC152-845 is a 15" fanless medical touch panel computer. In response to market demand, this medical panel computer is a cost effective solution. It adopts a modern, super sleek and fanless design and is equipped with a 15" TFT LCD as well as Intel® Celeron® processor N3060 dual core up to 2.48 GHz. For wireless network connection, the MPC152-845 offers 2 PCI Express Mini Card slots. By just plugging in the mini card WLAN card, customers can have instant access to wireless LAN/GPRS/GSM/4G environments. Besides, it provides two types of power input: DC power with terminal block connector and AC power adapter with screw type connector.

#### Super Slim & Ultra Lightweight Design

With a thickness of 54.6 mm and weight of  $3.2~{\rm kg}$  the MPC152-845 is designed for use in space-constrained environments.


#### Certifications

This 15-inch medical panel platform complies with 4th version of EN 60601-1 and CE, FCC Class B certifications to ensure medical operation safety.

#### Aluminum Back Chassis with Excellent Thermal Solution

With Axiomtek's patent for plastic plus aluminum mechanism design, the MPC152-845 can dissipate the heat easily and keep the system operation stable.





1. Power switch (ATX) 2. Power input connector (Phoenix) 3. Power input connector (Screw) 4. 2 x USB 2.0 5. Audio (Line-out) 6. 1 x RS-232/422/485 7. 1 x RS-232 8. 2 x USB 3.0 9. 2 x LAN 10. 8 x DIO (programmable, DB9) 11. AT/ATX selectable switch 12. Touch LED indicator 13. Touch on/off button 14. HDD & Power LED indicator

#### **Specifications**

| Front Bezel | IP65, NEMA 4 rugged protection, plastic front bezel |   |
|-------------|---|---|
| LCD Panel   | Display Type  | 15" XGA TFT LCD with LED backlight                          |
|             | Brightness (cd/m <sup>2</sup> )                     | 420 nits (XGA)  |
|             | Resolution  | 1024 x 768 (XGA)  |
|             | Viewing Angel (H/V)                                 | 160°/160°   |
| Main System | CPU   | Intel® Celeron® processor N3060<br>2 cores (up to 2.48 GHz) |
|             | System Memory                                       | 1 x 204-pin DDR3L-1600 SO-DIMM,<br>up to 8GB                |
|             | BIOS  | AMI UEFI BIOS   |
|             | Storage   | 1 x 2.5" SATA HDD (9.5 mm height)<br>1 x mSATA              |
|             | Watchdog Timer                                      | 255 levels, 0 to 255 sec.                                   |
|             | Onboard Graphics                                    | Integrated in Intel® GFX                                    |



### **Specifications**

| I/O Connector         | 1 x RS-232   |  |
|-----------------------|--|--|
|                       | 1 x RS-232/422/485   |  |
|                       | 2 x 10/100/1000 Mbps Ethernet                                  |  |
|                       | 2 x USB 2.0  |  |
|                       | 2 x USB 3.0  |  |
|                       | 1 x Audio (Line-out)   |  |
|                       | 1 x Switch for power on/off                                    |  |
|                       | 1 x AT/ATX selectable switch                                   |  |
|                       | 1 x 8-bit DIO (programmable, DB9)                              |  |
| Expansion Interface   | 1 x Full-size PCI Express Mini Card slot with mSATA            |  |
|                       | 1 x Full-size PCI Express Mini Card slot with SIM              |  |
| Touchscreen           | Resistive type   |  |
| Power Supply          | AC version: 100 to 240 V AC-DC, 65W power adapter or           |  |
|                       | DC version: 9 to 36 VDC with over current protection fuse      |  |
| Power Consumption     | 32 W   |  |
| Dimension             | 387.9 mm (15.27") (W) x 54.6 mm (2.14") (D) x 307.7 mm         |  |
|                       | (12.11") (H)   |  |
| Packing Dimensions    | 510 mm (20.08") (W) x 105 mm (4.13") (D) x 385 mm (15.16") (H) |  |
| Weight (net/gross)    | 3.2 kg (7.05 lb)/5.1 kg (11.24 lb)                             |  |
| Operating Temperature | 0°C to +40°C (+32°F to +122°F)                                 |  |
| Relative Humidity     | 20% to 90% @ +40°C; non-condensing                             |  |
| Operation Vibration   | 2G, 5 - 500Hz, random for SSD                                  |  |
| Certifications        | 4th EN 60601-1 (ESD contact 8KV, air 15KV), CE and FCC         |  |

### **Packing List**

- 1 x MPC152-845 1 x Driver CD 1 x Adapter (MPC152-845-J) 1 x Power cord (MPC152-845-J) 1 x Phoenix connector (MPC152-845 DC)

### **Ordering Information**

| Standard      | itandard  |  |
|---------------|---|--|
| MPC152-845-J  | 15" XGA fanless medical touch panel computer with Intel®<br>Celeron® processor N3060, 5-wire resistive touch screen,<br>AC-DC 65W power adapter (screw type connector) and EMI<br>class B |  |
| MPC152-845-DC | 15" XGA fanless medical touch panel computer with Intel®<br>Celeron® processor N3060, 5-wire resistive touch screen<br>and DC power input (terminal block connector)                      |  |

#### **Optional Accessories**

| Wi-Fi + Bluetooth kit |                              |  |
|-----------------------|------------------------------|--|
|                       | 881251520A0E                 | Panel mount kit                                  |
|                       | 881251521A0E                 | Wall mount kit                                   |
|                       | E226171119                   | Stand kit  |
|                       | 881251203A0E                 | RFID kit   |
|                       | *Specifications and certific | ations may vary based on different requirements. |

### **Optional EOS Installation**


| WES 7         |  |
|---------------|--|
| WE8S (64-bit) |  |
|               |  |


## **Optional OS Installation**

| Windows® 7            |  |
|-----------------------|--|
| Windows® 8.1 (64-bit) |  |
| Windows® 10           |  |



### Dimensions





336



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660