

NUC BOX-8365UE

Fanned Embedded BOX PC



IoT Solutions
Alliance

ASRock
— Industrial —



KEY FEATURES

- Intel® 8th Gen (Whiskey lake-U) Core™ Processors
- 2 x 260-pin SO-DIMM up to 32GB DDR4 2400 MHz (16GB per DIMM)
- 3 x USB 3.2 Gen2, 2 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E, 1 x SATA3
- 1 x Intel 1 Gigabit LAN, 1 x Realtek 1 Gigabit LAN
- Supports triple display, 1 x HDMI 1.4, 2 x DP 1.2a
- TPM 2.0 onboard IC
- 12V DC-In
- 110.0 x 118.5 x 67.3 mm, Fanned Barebone

SPECIFICATIONS

Processor System

CPU	Intel® 8th Gen (Whiskey lake-U) Core™ Processors NUC BOX-8145UE (I3-8145UE DC, 2.2GHz, 15 W) NUC BOX-8365UE (I5-8365UE QC, 1.6GHz, 15 W) NUC BOX-8665UE (I7-8665UE QC, 1.8GHz, 15 W)
Chipset	MCP
Socket	N/A
BIOS	AMI SPI 128 Mbit

Memory

Technology	Dual Channel DDR4 2400 MHz
Capacity	32 GB (16 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	Intel® Gen9 Graphics DX 12
HDMI	HDMI 1.4b Max resolution up to 4096x2160@24Hz
DisplayPort	DisplayPort 1.2a Max resolution up to 4096x2160@60Hz
VGA	N/A
LVDS	N/A
eDP	N/A
DVI	N/A
MultiDisplay	Triple Display

Expansion Slot

mini-PCIe/ mSATA	N/A
mini-PCIe	N/A
M.2	1 x Key E (2230) with PCIe x1 and USB 2.0 for Wireless
SIM Socket	N/A

Audio

Interface	Realtek ALC233, High Definition Audio. Line-out, Mic-in
-----------	---

Ethernet

Controller/ Speed	NUC BOX-8365UE / NUC BOX-8665UE: LAN1: Intel® I219LM with 10/100/1000 Mbps, supports AMT/vPro LAN2: Realtek RTL8111H with 10/100/1000 Mbps NUC BOX-8145UE: LAN1: Intel® I219V with 10/100/1000 Mbps LAN2: Realtek RTL8111H with 10/100/1000 Mbps
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (Key M, 2242/2260) with PCIe x4 and SATA3 for SSD *Not support M.2 Key M 2280
mSATA	N/A
SATA	1 x SATA3 (6Gb/s)
eMMC	N/A

Front I/O

HDMI	N/A
DisplayPort	N/A
USB	1 x USB 3.2 (Gen2) + 2 x USB 2.0
Audio	1 (Mic-in or Line-out)

Rear I/O

HDMI	1 x HDMI 1.4
DisplayPort	2 x DP 1.2a
VGA	N/A
DVI	N/A
Ethernet	2 x 1 Gigabit LAN
USB	2 x USB 3.2 (Gen2)
Audio	N/A
COM	N/A
PS2	N/A

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	1 x 12V/96W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Mechanical

Construction	Plastic
Mounting	VESA mounting
Dimensions (W x H x D)	110.0 x 118.5 x 67.3 mm
Weight	Net Weight: 0.7kg

Others

OS Support	Windows 10
TPM	N/A
Certifications	CE, FCC Class A
Packing List	1 x 12V/96W Power Adapter 1 x Screw Package 1 x Product DVD 1 x VESA mounting bracket 1 x Heatsink for M.2 Key M

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660