



APC-2138

21.5" 11th Gen Intel® Core™ Processor i5/i3
Expandable Ultra light Multi-Touch Fanless Panel PC

- > 21.5" PCAP Multi Touch
- > Onboard 11th Gen. Intel® Core™ SoC i5/i3 & Celeron® BGA Processor
- > 2 x 260-pin DDR4 3200 MHz SO-DIMM supports up to 64GB
- > 2 x GLAN, 2 x DP++, 4 x USB
- > 2 x 2W Speakers
- > Front IP65, Fanless System & VESA Compliance
- > 1 x 2.5" SSD w/Service Window
- > Optional WiFi 802.11 ac/a/b/g/n

Spec

-System Information-	
Processor	Intel® Core™ i5-1135G7 (up to 4.2GHz, quad-core, 8M Cache, TDP: 15W) Intel® Core™ i3-1115G4 (up to 3.0GHz, dual-core, 6M Cache, TDP: 15W)
Platform Controller Hub	Intel® Tiger Lake SoC integrated
System Memory	2 x 260-pin DDR4 3200 MHz SO-DIMM supports up to 64GB (non ECC only)
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
TPM	Onboard NuvoTon NPCT754AADYX support TPM 2.0
SBC	EMX-TGLC
Expansion	
Expansion	1 x M.2 Type B 3042/3052/2242/2260/2280 support WWAN+GNSS or NVMe SSD 1 x M.2 Key E 2230 support WiFi module and CNVi (1 x PCIe x1 & USB 2.0 Signal)
Storage	
Storage	1 x 2.5" Drive Bay 1 x M.2 slot
Panel	
LCD Size	21.5"
Display Type	Full HD
Resolution	1920x1080
Pixel pitch	248.25um (H) x248.25um (V)
Luminance	250cd/m²
Contrast ratio	3000
Viewing angle	89 (U), 89 (D), 89 (L), 89 (R)
Response time	18ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	89 %
I/O	
USB Port	4 x USB 3.0
Display Port	2 x DP ++
Display	
Graphic Chipset	Intel® 11th Generation CPU integrated
Spec. & Resolution	DP1+DP2 (DP1.4): Max: 7680 x 4329@60 Hz DP3+DP4 (DP1.4): Max: 7680 x 4329@60 Hz Single DP port (2021/2 Lab test): 5120 x 2160 @60 Hz, DVT check Max: 7680 x 4329@60 Hz Note: This resolution is actual test result. Intel resolution as below: 2 x DP++ : 1920 x 1080@60 Hz 2 x DP: 4096 x 2304@60 Hz LVDS: 1920 x 1080 Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS) eDP 4096 x 2304@60 Hz *2 x DP++, LVDS, eDP Default (Thin Mini ITX), Optional: DP3 and DP4 for full height (Maximum: 6 for quadruple independent displays)
Audio	
Audio Codec	Realtek ALC897 co-lay ALC888S & Tempo 92HD73
Speaker Output	2 x 2W
Certifications	
Certification Information	CE FCC Class B
Ethernet	

www.avalue.com.tw



LAN Chipset	1 x Intel® I225IT 2.5 Gigabit Ethernet 1 x Intel® I219LM Gigabit Ethernet PHY
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Power Requirement	
DC Input	+12V~24V
DC Input Connector	4-pin din
Adapter	Input:100 ~ 240Vac/ 50 ~ 60Hz Output:90W Adapter (24V @ 3.75A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 60°C (14°F ~ 140°F)
Operating Humidity	0% @ 90% Relative Humidity, Non-condensing
Weight	6.3 Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
IP Rating	Front IP65
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm
Power Mode	AT/ATX
System Fan	Fanless
Construction - Front	Plastic- Black
Construction - Rear	Plastic- Black
Dimension	539.6 * 342.6 * 45.2 mm
Fanless	Yes
Software Support	
OS Information	Win10 64bit, Win11 64bit
Ordering Information	
Ordering Information	APC-2138-C15-A1R 21.5" 1920x1080 Projected Capacitive Touch Panel PC (Plastics, Black), Intel Core i3-1115G4/4GB Memory/4USB3.0/2LAN/2DP/SPK/90W Power adapter APC-2138-C35-A1R 21.5" 1920x1080 Projected Capacitive Touch Panel PC (Plastics, Black), Intel Core i5-1135G7/4GB Memory/4USB3.0/2LAN/2DP/SPK/90W Power adapter

www.avalu.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660