




IMB-1239-WV

Mini-ITX Motherboard

KEY FEATURES

- Intel® 14th/13th/12th Gen (Raptor Lake-S Refresh/Raptor Lake-S/Alder Lake-S) Core™ Processors with H610 chipset
- 2 x 262-pin SO-DIMM DDR5 4800/5600 MHz, up to 96GB (48GB per DIMM)
- 1 x PCIe x16 (Gen5), 2 x USB 3.2 Gen2, 1 x USB 3.2 Gen1, 5 x USB 2.0, 1 x M.2 Key B, 1 x M.2 Key E, 1 x M.2 Key M, 2 x COM, 2 x SATA3
- 1 x Intel 2.5 Gigabit LAN, 1 x Intel 1 Gigabit LAN
- Supports Triple display, 2 x HDMI 2.0b, 1 x DP 1.4a, 1 x LVDS, 1 x eDP 1.4b
- TPM 2.0 onboard IC
- 12~28V DC-In (Lockable DC Jack)

SPECIFICATIONS

Form Factor

Dimensions	Mini-ITX (6.7-in x 6.7-in x 1.5-in, 17.0 cm x 17.0 cm x 2.5 cm)
------------	---

Processor System

CPU	Intel® 14th/13th/12th Gen (Raptor Lake-S Refresh/Raptor Lake-S/Alder Lake-S) Core™ Processors, up to 65W
Chipset	Intel® H610
Socket	LGA1700
BIOS	AMI SPI 256 Mbit

Memory

Technology	Dual Channel DDR5 4800/5600 MHz* *Actual memory frequency depends on the CPU types and DRAM modules, for more information refer to https://www.asrockind.com/en-gb/index.php?route=newsblog/faq&faq_id=90 technical FAQ *If motherboard ambient temp. is over 55°C, the memory thermal solution should be added to avoid thermal issue
Capacity	96 GB (48 GB per DIMM)
Socket	2 x 262-pin SO-DIMM

Graphics

Controller	Intel® UHD Graphics
HDMI	HDMI 2.0b Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4a, DP++ Max resolution up to 4096x2160@60Hz
LVDS	Dual channel 24 bit up to 1920x1200@60Hz
eDP	eDP 1.4b Max resolution up to 4096x2160@60Hz
MultiDisplay	Triple Display

Expansion Slot

PCIe	1 x PCIe x16 (Gen5)
M.2	1 x M.2 (Key E, 2230) with PCIe x1, USB 2.0 and CNVi for Wireless 1 x M.2 (Key B, 3042/3052) with PCIe x1, USB 3.2 Gen1, USB 2.0 and SIM for 4G/5G
SIM Socket	1 x Socket connected to M.2 Key B

Audio

Interface	Realtek ALC897, High Definition Audio. Line-out, Mic-in
-----------	---

Ethernet

Controller/ Speed	LAN1: Intel® I226V with 10/100/1000/2500 Mbps LAN2: Intel® I219V with 10/100/1000 Mbps
Connector	2 x RJ-45

Rear I/O

HDMI	2 x HDMI 2.0b
DisplayPort	1 x DP 1.4a++
Ethernet	1 x 2.5 Gigabit LAN 1 x 1 Gigabit LAN
USB	2 x USB 3.2 Gen2 2 x USB 2.0
Audio	2 (Mic-in, Line-out)

Internal Connector

USB	1 x USB 3.2 Gen1 (1 x USB 3.2 header) 3 x USB 2.0 (1 x 2.54 pitch header)
COM	COM1, COM3 (RS-232/422/485)
GPIO	4 x GPI, 4 x GPO
LVDS	1
eDP	1
SATA PWR Output	1
Speaker Header	1

Storage

M.2	1 x M.2 (Key M, 2242/2280) with PCIe Gen3 x4 for SSD
SATA	2 x SATA3 (6Gb/s)

Security

TPM	TPM 2.0 onboard IC
-----	--------------------

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	12~28V DC-In with 4-pin wafer PWR cable or DC Jack (Screw type)
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready


Environment

Operating Temp	-20°C ~ 70°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

IMB-1239-WV

Mini-ITX Motherboard

BLOCK DIAGRAM



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660