



rBOX101-6COM(ATEX)

ATEX Anti-Explosive Certified Robust Din-rail
Fanless Embedded System



▲ Front view



Din-rail kit ▲ Rear view

Features

- ATEX Anti-Explosive Type "nA" Zone 2 Group II Certification
- Fanless and cableless design
- Supports Intel® Atom™ processor Z510PT 1.1 GHz or Z520PT 1.33 GHz
- Wide temperature operation of -40°C ~ +70°C
- 6 isolated COM ports, 1 isolation DIO (4-IN/4-OUT)
- 2 isolated Ethernet
- 2 watchdog timer
- LED indicators
- SNMP V1/V2c
- Supports one CompactFlash™, one SD card (optional)
- 2 power paths with terminal block and 12-48VDC
- Supports AXView monitoring software package

Introduction

rBOX101-6COM(ATEX) din-rail fanless embedded field controller supports extra low power Intel® Atom™ processors Z510PT and Z520PT with extended temperature range of -40°C to 70°C for use in extreme operating environments.

To prevent ESD and over-voltage, this super compact-size rBOX101-6COM(ATEX) is equipped with six isolated RS-232/422/485, one isolated 10/100/1000Mbps Ethernet & one isolated 10/100Mbps Ethernet and one isolated DIO port for offering magnetic isolation protection. Two power paths input minimize the risk of data loss in the event of a single power failure. Powered by IP30 housing, wide operating temperature range and Safety/EMI/EMS compliance, rBOX101-6COM(ATEX) is ideal for intelligent computing and communication solutions in critical environments such as power utility, transportation and more.


The ready-to-run rBOX101-6COM(ATEX) equipped with AXView monitoring software is a total solution for power plant automation, facility monitoring systems, intelligent transportation systems, and more.

Specifications


Standard Color	Sliver-Black
Construction	Extruded aluminum and heavy-duty steel, IP30
CPU	Intel® Atom™ processor Z510PT 1.1 GHz or Z520PT 1.33 GHz
System Memory	1 x 200-pin DDR2 SO-DIMM max. up to 2 GB
System I/O Outlet	Serial Port 6 x Isolated RS-232/422/485 (COM 1-6) Interface select by software or BIOS Supports Auto Flow Control in RS-485 mode ESD protection 15 KV Magnetic isolation protection 2KV COM 1 & COM 2 speed up to 115.2kbps COM 3 ~ COM 6 serial port speed up to 921.6kbps
	LAN 1 x 10/100/1000Mbps Ethernet 1 x 10/100Mbps Ethernet Magnetic isolation protection 1.5 KV
	USB 2 x USB 2.0 USB power distribution control by software

System I/O Outlet	DIO	1 x DIO (4-IN/4-OUT) DI : Input channels : 4, source type Input voltage : 0 to 30VDC Digital input levels for dry contacts : -Logic level 0: close to GND -Logic level 1: open Digital input levels for wet contacts : -Logic level 0: +10V to +24V (DI to COM-) -Logic level 1: +3V max. DO : Output channels : 4, sink type Output current: Max. 200 mA per channel On-state voltage : 24VDC nominal, open collector to 30V Optical isolation protection 3 KV
	VGA	1 x DB15 connector
	Power Input	2 x DC power input with terminal block
	Alarm Contact	One relay output with current 0.5A @30VDC
Watchdog Timer	2 WDT	WDT 1: one step is 1 sec, 255 levels WDT 2: one step is 250ms, 255 levels
LEDs	System	Power, Alarm, Ready/Active, COM (TXD,RXD)
	Alarm	DC PWR1 or PWR2 is lost (default) User define event

Specifications

Storage	Supports 1 x CompactFlash™ Supports 1 x SD card up to 32 GB (optional)
Installation	Din-rail, wall mount
Power Supply	2 power paths
	Power Input Range 12-48VDC
	Power Input Rating 12-48VDC, 1.5-0.4A
	Power Protection DC Version: OVP (over voltage protection) UVP (under voltage protection) Reverse protection
Operating Temperature	-40°C ~ +70°C (-40°F ~ +158°F)
Storage Temperature	-45°C ~ +85°C (-49°F ~ +185°F)
Humidity	5% ~ 95%
Weight (net/gross)	1.9 kg (4.18 lb) / 2.24 kg (4.93 lb)
Dimensions	100.6 mm (3.96") (W) x 110 mm (4.33") (D) x 135 mm (5.31") (H)
EOS Support	XPE, WinCE, Linux support package, Windows® 7 Embedded
ISO	Manufactured in an ISO9001 facility
Anti-Explosive 	ATEX Anti-Explosive Type "nA" Zone 2 Group II Certification Ex Marking: Certificate No.: TUV 14 ATEX 7480 X
Safety Compliance	UL508, UL60950-1 Heavy Industrial CE, including: EN60950-1, IEC60950-1
EMI Compliance	FCC Part 18 Heavy Industrial CE, including: EN61000-6-4, EN61000-3-2, EN61000-3-3
EMS Compliance	EN50121-4 (Railway application) Heavy Industrial CE, including: EN61000-6-2 EN61000-4-2 (ESD standards) * Contact: +/- 6 KV; criteria B * Air: +/- 8 KV; criteria B EN61000-4-3 (radiated RFI standards) * 10V/m, 80 to 1000 MHz; 80% AM criteria A EN61000-4-4 (burst standards) * Signal ports: +/- 2 KV; criteria B * DC power ports: +/- 2 KV; criteria B EN61000-4-5 (surge standards) * Signal ports: +/- 1 KV; line-to-line; criteria B * DC power ports: +/- 0.5 KV; line-to-earth; criteria B

Dimensions



	EN61000-4-6 (induced RFI standards) * Signal ports: 10 Vrms @ 0.15 ~ 80 MHz; 80% AM criteria A * DC power ports: 10 Vrms @ 0.15 ~ 80 MHz; 80% AM criteria A EN61000-4-8 (magnetic field standards) * 30 A/m @ 50, 60 Hz; criteria A
Environmental Test	IEC60068-2-6 Fc (vibration resistance) 5 g @ 10 ~ 150 Hz, amplitude 0.35 mm (operation/storage/transport) IEC60068-2-27 Ea (shock) 25 g @ 11 ms (half-sine shock pulse; operation); 50 g @ 11 ms (half-sine shock pulse; storage/transport) IEC60068-2-32 Ed (free fall) 1 M (3.281ft)

Ordering Information

Standard	
rBOX101-6COM (ATEX)-FL1.1G	ATEX anti-explosive certified robust din-rail fanless embedded system with Intel® Atom™ processor Z510PT 1.1 GHz, ATEX and 6 isolated COM ports (-40°C ~ +70°C)
rBOX101-6COM (ATEX)-FL1.33G	ATEX anti-explosive certified robust din-rail fanless embedded system with Intel® Atom™ processor Z520PT 1.33 GHz and 6 isolated COM ports (-40°C ~ +70°C)
Optional	
DDR2 SODIMM	1 GB ~ 2 GB (with W.T. memory)
DDR2 SODIMM	1 GB ~ 2 GB (with 0°C ~ +85°C memory; operating temperature: 0°C ~ +70°C)
CompactFlash	2 GB or above (with W.T. CF)
Wall mount kit	

*Specifications and certifications are based on options and may vary.

Overview

Embedded Systems

Embedded Systems for Transportation

3

Embedded Field Controllers

Industrial Firewall

Embedded MicroBoxes

Industrial Barebone Systems

Industrial Chassis

Backplanes

Power Supplies

Peripherals & Accessories



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660