

DS SERIES

DS49ILT6


49" High Brightness 5500 Nits Digital Signage Display




**SUNLIGHT
VIEWABLE IMAGE**



**SUSTAINED
HIGH BRIGHTNESS**



**BUILT-IN
MEDIA PLAYER**



**24 / 7
OPERATION**



**TRUECOLOR™
CALIBRATED**

FOR MORE INFORMATION

For more information about DynaScan, visit our site at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan


V100

SPECIFICATION


MODEL	DS491LT6
LCD Panel Size	48.5 inches LCD
Native Resolution	1920 x 1080
Backlight	LED
Default Color Temperature	D65 (6500 K)
Brightness	5500 nits
Color Depth	10 bits
Contrast Ratio	3000 : 1
Response Time (Typ.)	8 ms
Viewing Angle	178° / 178°
Light Lifetime (Typ.)	100,000 hrs
Blackening Defect Free	Up to 110°C (230°F)
Polarized Sunglasses Support	Yes
Panel Surface	AR, 2H
Power Supply	Internal
Rated Voltage	100-240V ~ 50/60Hz
Power On Mode (Typ./ Max.)	185 W / 340 W
Power Saving Mode	< 1 W
AC out	< 100 W
Bezel Width (T/B/L/R)	8.7 / 8.7 / 8.5 / 8.5 mm
Cabinet Color	Black
Monitor Dimension (LxHxD)	1096.7 x 627.2 x 82.3 mm
Monitor Weight	20.9 kg
Orientation	Portrait / Landscape
VESA Mounting (LxH)	400 x 400 mm
Carrying Handles	Yes
Language	English
Built-in Video Wall Support	Up to 15x15
Support SNMP (Up to V3.0)	Yes
Dimming Control	Yes
Image Retention Protection	Yes
Auto Orientation Sensor	Yes
Ambient Light Sensor	Yes
Power On/Off Scheduling	Yes
Internal Temperature Sensor	Yes
OSD Menu Rotation	Yes
HDMI	x1 (1080p)
DVI-D	x1
DisplayPort	x1
USB	x1 (For Internal Player)
SD Slot	x1 (For Internal Player)
DVI-D	x1
Audio	x1
RS-232	In x1, Out x1
RJ-45	x1 (LAN)
Processor	ARM Quad-Core Cortex-A9
Clock speed	1.6 GHz
Main memory interface	DDR3L-1066, 1GB
Graphics	Mali400MP4, support OpenGL ES1.1/2.0, Open VG1.1
Storage	Internal: Nand flash 8GB(multi sources) External: Support SD , Up to 32GB
Multimedia	Multi-format 1080P video decoders (H.264,VC-1, MPEG-1/2/4, H.263, H.264 MVC, AVS, VP8/6, RV)
Wi-Fi Specification	802.11 b/g/n 2412.0MHz - 2462.0MHz
Operating System	Android 4.4.2
Operating Temperature	0° C ~ 45° C
Storage Temperature	-20° C ~ 60° C
Humidity	10% ~ 80% RH Non-condensing
CERTIFICATION	CE / FCC / RoHS

DIMENSIONS

Unit: mm [inch]



INTERFACE



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave

Ste 1200

Sheridan

WY 82801

USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park

Stone Business Park

Stone

ST15 0YJ

United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660