

FM10, 10.4-inch Vehicle Mounted Computer

A Rugged Vehicle Mounted Computer for Data Collection in Warehouse and Logistics Applications

FM10 is a rugged vehicle mounted computer delivers flexibility and mobility in a vehicle-mount form factor, designed to easily be removed from the dock with a one-click top latch. Since the dock remains attached to the vehicle, this device can easily be moved or switched from one vehicle to another vehicle. FM10 designed to fit seamlessly into forklifts and other warehouse vehicles, will help minimize errors, streamline ordering and inventory management, and improve operational efficiencies.

The processing power comes from Intel's quad core atom E3845 processor. The computer features a brilliant anti-scratch resistive touch screen, and offers 1024 x 768 pixel resolution.



Highlights

- Intel Quad Core Atom E3845 Processor
- 10.4" 1024 x 768 Panel
with anti-scratch resistive touch screen
- Field replaceable front panel to reduce service costs
- Magnesium alloy housing
- Built-in Wi-Fi and Bluetooth 4.0
- IP65 waterproof and dustproof
- Wide range operating temperature

| Order Information | | | |
|-------------------|----------|----------|---------|
| | 3G | 4G | Heater |
| FM10 | Optional | Optional | N/A |
| FM10-HT | Optional | Optional | Default |

FM10, 10.4-inch Vehicle Mounted Computer

A Rugged Vehicle Mounted Computer for Data Collection in Warehouse and Logistics Applications

Display Specification

| | |
|----------------|---|
| Size | 10.4-inch display (4:3) |
| Resolution | 1024 x 768 |
| Brightness | 400 nit |
| Touch | Anti-scratch resistive touch |
| Contrast Ratio | 1200:1 |
| Viewing Angle | 88/88/88/88 |
| Technology | • Light sensor • Intel HD Graphics (built-in CPU) video controller |

System Specification

| | |
|------------------|---|
| Processor | Intel Quad-Core Atom E3845 Processor , 1.91 GHZ |
| System Memory | 4GB SODIMM DDR3L-1600 (up to 8GB) ¹ |
| Storage | 64GB M.2 solid state drive SSD Optional up to 256 GB Additional storage with SD card slot |
| Operating System | Windows 10 IoT Enterprise Windows Embedded 8.1 Industry Pro Windows 7 Professional for Embedded System Windows Embedded Standard 7 |

Wireless Communication

| | |
|-----------|---|
| WLAN | 802.11 a/b/g/n/ac |
| Bluetooth | Bluetooth 4.0 |
| GPS | u-Blox Neo-6Q located on the Vehicle Dock |
| WWAN | Optional 4G/ LTE or 3G. |

Interface

| | |
|----------|--|
| Computer | 1 x SIM Card Slot 1 x SD Card Slot 1 x USB 3.0 |
| Docking | 1 x 12V DC in power input jack 1 x COM 1, 1 x COM 2 1 x USB 2.0 port (support two USB 2.0) 1 x CANBus / Audio 1 x 400Mbps LAN port Optional PoE as a Power sourcing equipment (PSE) support 802.3at Type 2 1 x Power connector SMA Connector(female) for external antenna (WiFi, GPS (optional), WWAN (optional)) |

Keyboard and Input

| | |
|----------------|---|
| Touch | • Resistive, support stylus |
| Button | • On-screen QWERTY keyboard 1 x power, 6 x function key (Programmable function key configured by Hottab Utility) |
| LED Indicators | Wi-Fi, Bluetooth, UPS battery, HDD, Blanking, Heater |

Audio

| | |
|---------|---|
| Speaker | High power speaker (3W * 2), located on the docking |
|---------|---|

Cameras

| | |
|------------|---|
| Web Camera | 2MP webcam, only available for Windows 7/ 8.1/ 10 IoT |
|------------|---|

Security Function

| | |
|--------------------------|--|
| Mobile Device Management | SOTI Mobicontrol compatible ² |
|--------------------------|--|

Mechanical and Environment

| | |
|-----------------------|---|
| Dimension (W x L x H) | Computer: 268 x 214 x 35 mm (10.6 x 8.42 x 1.37 inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches) ³ |
| Weight | Computer 1.7 kg (3.75 lbs) Docking 1.6 kg (3.53 lbs) |
| Housing | Magnesium alloy housing |
| Cooling System | Fanless design |
| Operating Temperature | With optional heater: -30°C to 50°C (-22°F to 122°F) AC mode: -20°C to 50°C (-4°F to 122°F) Batter mode: -10°C to 50°C (14°F to 122°F) |
| Storage Temperature | -30°C to 60°C (-22° to 140°F) |
| Humidity | 5% to 90% RH, non-condensing |
| IP Proof | IP65 certified, dustproof and waterproof |
| Impact | Support EN62262 IK70 rating |
| Shock | MIL-STD-810G Method 516.6 Procedure I |
| Vibration | MIL-STD-810G Method 514.6 Procedure I |
| ESD | Compliant with EN 61000-4-2, enhanced ESD to ±12kV direct & ±15kV air CE, FCC, UL60950-1, EN60950-1, PTCRB, FCC (Electromagnetic Emissions), IC (ICES-003) |
| Certifications | |

Power Management

| | |
|----------------------------|---|
| Power Input | 10V-60V, with isolation power and ignition control |
| UPS Battery | 7.6V typ Battery (2S1P) |
| UPS Battery Operating Time | Minimum 30 minutes ⁴ |

Accessories

Standard Accessories

| | |
|---------------------------------|---|
| Power Cable with Fuse | 98K000A0006O |
| Adapter | 922D084W12V1 |
| Power Converter Cable | 94J602G030K2 |
| USB Cable | 9483098080K0 |
| Wi-Fi Antenna (1 pcs) | 39700000000G |
| External Antenna Fixing Bracket | 88111T201203 |
| Driver CD | 91711111103H (Win 7 Professional) 91711111103A (Win 8.1 Industry) 91711111103B (Win 10 IoT) 91521111100S |

Quick Start Guide Optional Accessories ⁵

| | |
|--|--------------|
| Quick Start Guide | 91521111100S |
| DC Power Jack Cable | 94J0086020K0 |
| Adapter | 90PO12120005 |
| RS232 Cable | 94G3094090K2 |
| Audio Cable | 94E215R060K0 |
| CAN Bus Cable | 94E2150090K0 |
| LAN Cable | 94I0080080KF |
| Key for Vehicle Dock | 9B000000007N |
| WWAN Antenna (1 pcs) | 39700000000H |
| Fuse Kit | 94JL01L01000 |
| Device Mounting Kit 1 (No Drill) | 98K000A0005Y |
| Device Mounting Kit 2 (Drill) | 98K000A0006P |
| Mounting Kit 3 (Keyboard Mounting) | 98K000A0005X |
| UHF Fixed Reader | 9B000000006P |
| Magnetic Multi-Band Combo Antenna- VM10S | 397SM0000006 |
| LTE MIMO/GNSS- VM240 | 39700000000M |
| GPS & LTE MIMO Combo Antenna- VM9C | 397SM0000008 |
| Stylus Kit + Screw | 98K000A0005T |
| Drawing ⁶ | |



Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example)
Do not expose bare skin to this product when handling this unit in extreme hot or cold environments

1. Total usable memory will be less depending upon actual system configuration.
2. SOTI is available upon request.

3. Length measurements do not include protrusions. Weight varies with options.

4. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.

5. Accessories may vary depending on your configuration.

6. This is a simplified drawing and some components are not marked in detail.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660