

R19IE3S-SPM1-B

19" Intel® Celeron® N6211 IP65 Stainless B Series Panel PC



KEY FEATURES

- Intel® Celeron® Elkhart Lake N6211 processor
- Fanless cooling system
- SUS 316 / AISI 316 stainless steel for food and chemical industries
- Full IP65 waterproof enclosure
- A true flat, easy-to-clean front surface with edge-to-edge design
- Supports VESA mount
- Rotary switch adjust different touch mode for Hand / Rain / Glove application
- Emergency and Flat buttons for automation device control
- Optical bonding (optional)



OVERVIEW



Waterproof All-Around

The Panel PC complies with IP65 water and dust resistance for regular cleanup processes and strict hygiene standards in the Food, Beverage, and Pharmaceutical industries



Stainless B Series with Push Buttons

Push-buttons bring precise control directly to the work area, eliminating wasted movement and increasing productivity. Also, the physical buttons are especially useful for critical situations like emergency shutdowns.



Emergency Stop

When an emergency occurs, we don't want to waste time navigating through HMI screens; hence a button offers a quick and simple way to shut down the process.



Ultimate Touch Experience

The highly-sensitive touch screen and PCAP multi-touch support make it easy for users to key in data, rotate images, drag and drop files, and zoom in with two or more fingers. The rotary switch gives a simple, intuitive way to switch hand, rain, and glove modes.

SPECIFICATIONS

ח	ien	lav

Resolution 1280x1024 19.0 inches Contrast Ratio 1000:1 **Panel Brightness** 250 0 nits 85,85,80,80 376.32x301.06 mm View Angles Active Area Touch / Glass Projected Capacitive Multi Touch Screen

System Specification

WLAN Support (Optional) BT Support (Optional)

Intel® Celeron® N6211 (up to 2.6GHz) 1 x SO-DIMM, DDR4 3200 MHz, 4GB Processor Memory Intel® Celeron® N6210 (up to 3.0GHz)

8GB (Optional) 16GB (Optional)

WINMATE

www.winmate.com

(Optional)



Storage Temperature -20°C to 60°C Certification CE, FCC IO Ports I x M12 water Serial Port 1 x M12 water		Mounting Cooling System Operating Temperature IP rating USB Port Expansion Port Indicator	Windows 11 IoT Enterprise SAC (64 bit) (Optional) Windows 11 IPro 64 bit (Optional) Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 22.04 (Optional) VESA Mount Fanless design 0°C to 45°C IP65 1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control 1 x LED Indicator for power
Dimension 516 x 395 x 68 Enclosure Stainless Hou Environment Operating Humidity 10% to 90% R Storage Temperature -20°C to 60°C Certification Certification CE, FCC IO Ports Power Input 1 x M12 water, Serial Port 1 x M12 water, LAN 1 x waterproof Control Button Rear side: 1 x Power Butt 1 x Reset Butte	H, Non-Condensing proof connector for 12V DC proof connector for RS232	Operating Temperature IP rating USB Port Expansion Port	Panless design 0°C to 45°C IP65 1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Enclosure Stainless Hou Environment Operating Humidity 10% to 90% R Storage Temperature -20°C to 60°C Certification Certification CE, FCC IO Ports Power Input 1 x M12 water, Serial Port 1 x M12 water, LAN 1 x waterproof Control Button Rear side: 1 x Power Butt 1 x Reset Butt	H, Non-Condensing proof connector for 12V DC proof connector for RS232	Operating Temperature IP rating USB Port Expansion Port	Panless design 0°C to 45°C IP65 1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Environment Operating Humidity 10% to 90% R Storage Temperature -20°C to 60°C Certification Certification CE, FCC IO Ports Power Input 1 x M12 water Serial Port 1 x M12 water LAN 1 x waterproof Control Button Rear side: 1 x Power Butt 1 x Reset Butte	H, Non-Condensing proof connector for 12V DC proof connector for RS232	Operating Temperature IP rating USB Port Expansion Port	0°C to 45°C IP65 1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Operating Humidity 10% to 90% R Storage Temperature -20°C to 60°C Certification CE, FCC IO Ports 1 x M12 water Power Input 1 x M12 water LAN 1 x waterproof Control Rear side:	proof connector for 12V DC	IP rating USB Port Expansion Port	1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Storage Temperature	proof connector for 12V DC	IP rating USB Port Expansion Port	1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Certification Certification CE, FCC IO Ports Power Input 1 x M12 water Serial Port 1 x M12 water LAN 1 x waterproof Control Button Rear side: 1 x Power Butt 1 x Reset Butt	proof connector for RS232	USB Port Expansion Port	1 x M12 waterproof connector for 2 x USB2.0 1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Certification CE, FCC IO Ports IO Power Input 1 x M12 water Serial Port 1 x M12 water LAN 1 x waterproof Control Rear side: 1 x Power Butt 1 x Reset Butt	proof connector for RS232	Expansion Port	1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
IO Ports	proof connector for RS232	Expansion Port	1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Power Input	proof connector for RS232	Expansion Port	1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
Power Input	proof connector for RS232	Expansion Port	1 x Front waterproof connector for USB2.0 type-A CN1 and CN2 for front button control
LAN 1 x waterproof Control Rear side: 1 x Power Butt 1 x Reset Button		•	
Control Button Rear side: 1 x Power Butt 1 x Reset Butt	Giga LAN RJ45 connector	Indicator	1 v I ED Indicator for nower
Button Rear side: 1 x Power Butt 1 x Reset Butt			1 x LED Indicator for storage
1 x Power Butt 1 x Reset Butto			
1 x Emergency connector 1 x Rotary Swi	Button & 3 x Flat Button for CN1 & CN2 M12 ich for touch mode		
Accessory			
Power Cord External USB External COM External LAN o External cable Waterproof ca	to DC Adapter with waterproof connector cable with waterproof connector cable with waterproof connector cable with waterproof connector s for CN1 & CN2 with waterproof connector os emale converter	Optional Accessory	1 x Open wire cable for M12 connector
Power			
Power Rating M12 Type: 12V 9~36V DC (Op			

- This is a simplified drawing and some components are not marked in detail.
 Please contact our sales representative if you need further product information.
 All specifications are subject to change without prior notice.
 The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.

0

0

1 USB Type-A

3 CN1 For Emergency Stop & Blue Button
4 CN2 For Green Button & Red Button

ОМ

6 LAN

6 Power Input

OSD Control Panel Wi-Fi Antenna Cover (Optional)



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660