

# W22IB3S-65A3

### 21.5" Intel® Celeron® N2930 IP65 Stainless Resistive Chassis Panel PC



#### **KEY FEATURES**

- Intel® Celeron® Bay Trail-M N2930 1.83GHz Processor
- Fanless Design
- Full IP65 dust/water resistant
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Optical Bonding with Anti-moisture Treatment (Optional)
- 5 Wire Resistive Touch/ Anti-Reflection Protection Glass (Optional)



#### **OVERVIEW**



#### Waterproof All-Around

The Panel PC complies with water and dust resistance for regular cleanup processes and strict hygiene standards in the Food, Beverage, and Pharmaceutical industries.



#### Comprehensive I/O Ports

Combining ruggedness with a range of I/O ports makes this device highly usable for multiple industrial applications. Plus, the waterproof connectors come with screw-on caps for added protection.

### SPECIFICATIONS

SPECIFICATIONS			
Display			
Resolution	1920x1080	Size	21.5 inches
Contrast Ratio	3000:1	Panel Brightness	250.0 nits
View Angles	89,89,89,89	Active Area	476.64x268.11 mm
Touch / Glass	Resistive Touch Screen (Optional) Protection Glass Without Touch Function (Optional)		
System Specification	ı		
Processor	Intel Celeron N2930 1.83GHz (up to 2.16GHz)	Memory	1 x SO-DIMM, DDR3L 1600 MHz, 4GB 8GB (Optional)
Storage	1 x mSATA SSD 128GB. mSATA SSD up to 512GB. (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Operating System	Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 20.04 (Optional)	WLAN	Support (Optional)
ВТ	Support (Optional)		
Mechanical			
Dimension	550 x 340 x 58.6 mm	Weight	10.3Kg
Mounting	VESA Mount Yoke Mount	Enclosure	Stainless Housing
Cooling System	Fanless design		
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C	IP rating	IP65
Certification			
Certification	CE, FCC		

**W**inmate

IO Ports

V.231101.240722 www.winmate.com



Accessory  Control  Cocessory  Co			USB Port	
1 x LED Indicator for storage  control  1 x Power Button 1 x Reset Button	Serial Port	1 x M12 waterproof connector for RS232	LAN	1 x waterproof Giga LAN RJ45 connector
utton 1 x Power Button 1 x Reset Button  1 x Reset Button  1 x Reset Button  1 x Reset Button  1 x Reset Button  1 x Reset Button  1 00-240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External LAN cable with waterproof connector Westerproof caps  VEAs sorews  1 2V DC (M12 type)  IMENSIONS  UNIT:MM  UNIT:MM  UNIT:MM  USS Type-A  O SDC control Panel	ndicator			
1 x Reset Button  Accessory  100-240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External LOM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps  VESA screws  VOWER  TOWER	Control			
100-240V AC to DC Adapter with waterproof connector Power Cord External USB cable with waterproof connector External CND cable with waterproof connector External CND cable with waterproof connector Waterproof caps VESA screws  VESA screws  12V DC (M12 type)  IMENSIONS  UNIT:MM  UNIT:MM  USB Type-A  Power Input  OSD Control Planel	Button			
Power Cord External USB able with waterproof connector External CAM cable with waterproof connector External LAM cable with waterproof connector Waterproof caps VESA screws  Tower Rating 12V DC (M12 type)  IMENSIONS UNIT:MM	Accessory			
OWER RATING  12V DC (M12 type)  IMENSIONS  UNIT:MM   OUSB Type-A  O LAN  OUSB Type-A  O Down Input O OUSB Control Panel	Accessory	Power Cord External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps		
IMENSIONS UNIT:MM  Solve Input  O SD Control Panel	Power			
IMENSIONS UNIT:MM  So SD Control Panel		12\/ DC (M12 time)		
USB Type-A Power Input  AN OSD Control Panel				
		550	58.6	200 M4 VESA
		550	58.6	USB Type-A  A Power Input  LAN  S OSD Control Panel

## NOTE

- 1. This is a simplified drawing and some components are not marked in detail.
  2. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
  3. All specifications are subject to change without prior notice.



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660