

## AEx-121P

#### 21.5" ATEX Certified Stainless Steel Display

Total IP66 Grade with M12 Waterproof Connector Wide range DC 9~36V Power Input Support Panel Mount & VESA Mount Support Projected Capacitive Touch Full Flat Bezel and Fanless Design Stainless Steel OSD Function Key ATEX Zone2, IECEx and C1D2 Certified

> IECEx Certification: Ex nA ic IIC T4 Gc ATEX Certification: (Ex) II 3 G

Industrial Panel PC HMI Controller

**Display Monitor** 



### Features / SUS 316 Stainless Steel





















| External I/O    |   |
|-----------------|---|
| USB             | 1 x M12 8-pin for 2 x USB 2.0 for Touch Control with waterproof cover and chain |
| Graph           | 1 x M12 12-pin for VGA with waterproof cover and chain                          |
| Function Keypad | 1 x M12 8-pin for OSD Cable & External OSD BOX with waterproof cover and chain  |
| Power           | 1xM12 3-pin for DC power connector with waterproof cover and chain              |
|                 |   |

C1D2 Certification: Class I, Division 2, Groups A, B, C, D T4

| Dispalay           |                |  |
|--------------------|----------------|--|
| Display Type       | 21.5" TFT-LCD  |  |
| Max. Resolution    | 1920 x 1080    |  |
| Max. Color         | 16.7M          |  |
| Luminance (cd/m²)  | 300            |  |
| View Angle         | 178(H) /178(V) |  |
| Contrast           | 5000:1         |  |
| Backlight Lifetime | 50,000 hrs     |  |
|                    |                |  |

| Touch Screen          |                            |
|-----------------------|----------------------------|
| Туре                  | Projected Capacitive Touch |
| Interface             | USB                        |
| Light Transmission(%) | 90%                        |

| Power Input           | DC 9~36V                                   |
|-----------------------|--|
| Power Consumption     | AEx-121P: 24W                              |
| Mechanical            |  |
| Construction          | 316 stainless steel chassis                |
| Mounting              | VESA mount 100 x 100, Panel mount (option) |
| IP Rating             | Total IP66                                 |
| Dimensions            | 571 x 362 x 75.1 mm                        |
| Net Weight            | 12.3 kg                                    |
| Environmental         |  |
| Operating Temperature | -20~60°C                                   |
| Storage Temperature   | -30~70°C                                   |
| Storage Humidity      | 10 to 05% @ 40°C non condensing            |

| Environmental         |   |
|-----------------------|---|
| Operating Temperature | -20~60°C  |
| Storage Temperature   | -30~70°C  |
| Storage Humidity      | 10 to 95% @ 40°C, non-condensing  |
| Safety                | CSA C22.2 No.61010  |
| Certificate           | CE / FCC Class A, ATEX Zone2 Ex nA ic IIC T4 Gc Class I, Division2, Group ABCD T4 ANSI/SA 12.12.01-2013 CSA Std. C22.2 No213-1987 |
|                       |   |

. ....

21.5" FHD IP66, 316 Stainless display, VGA input, external OSD box, Projected capacitive touch, 9~36V DC Power input, VESA Mount, AEX-121P Accessary: 1 x M12 for USB touch cable, 1 x VGA Cable, 1 x 3pin power input cable (w/o Adapter)

Industrial Display

Industrial Display

All specifications and photos are subject to change without notice

V 1.4



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660