



Industrial Solutions Partner!

## SSF4488-I / SSH4488-I V1

### 44.8" Resizing LCD, 1600 nits LED backlight, 1920 x 538 ultra-wide aspect ratio 16:4.4

The SSF/SSH4488-I is a 44.8 inch color TFT-LCD display with special aspect ratio 16:4.4 and wide resolution 1920 x 538. It is Litemax's Spanpixel series product which designed for high brightness 1600 nits with power efficiency LED backlight. It provides LCD panel with specific aspect ratios and sunlight readable for digital signage, public transportation, exhibition hall, department store, and vending machine.

#### Key Features

- Resizing LCD
- Ultra-Wide Screen (16 : 4.4)
- High Brightness 1600 nits
- LED Backlight
- Low Power Consumption
- Slim Bezel
- BL MTBF: 100,000 hours



#### Specifications

| Model Name               | SSF4488-I / SSH4488-I V1                                     |
|--------------------------|--------------------------------------------------------------|
| Description              | 44.8" Resizing LCD, 1600 nits LED backlight, 1920x538        |
| Screen Size              | 44.8"                                                        |
| Display Area (mm)        | 1095.84(H) x 307.0(V)                                        |
| Brightness               | 1600 cd/m <sup>2</sup>                                       |
| Resolution               | 1920x538                                                     |
| Aspect Ratio             | 16 : 4.4                                                     |
| Contrast Ratio           | 7000 : 1                                                     |
| Pixel Pitch (mm)         | 0.5708(H) x 0.5708(V)                                        |
| Pixel Per Inch (PPI)     | 44                                                           |
| Viewing Angle            | 176(H), 176°(V)                                              |
| Color Saturation (NTSC)  | 78%                                                          |
| Display Colors           | 16.7M                                                        |
| Response Time (Typical)  | 9.5ms                                                        |
| Panel Interface          | LVDS                                                         |
| AD Board Input Interface | VGA, DVI, HDMI , DP                                          |
| AD Board Input Power     | DC12V (DC24V optional)                                       |
| Power Consumption        | 110W (115W with AD Board)                                    |
| OSD Key                  | 4 Keys (Power Switch, Menu, +, -)                            |
| OSD Control              | Brightness, Color, Contrast, Auto Turing, H/V Position...etc |
| Dimensions (mm)          | 1121.7x 338.9 x 21.6                                         |
| Bezel Size(U/B/L/R)      | 13.3/13.3/10.9/10.9 mm                                       |
| Weight (Net)             | 6.8 kg                                                       |
| Operating Temperature    | 0 °C ~ 50 °C                                                 |
| Storage Temperature      | -20 °C ~ 60 °C                                               |

SSF= Panel+ LED Driving Board

SSH= Panel+ LED Driving Board + AD Control Board

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.




Industrial Solutions Partner!

## Mechanical Drawing

Outline Dimensions

Unit: mm





*Industrial Solutions Partner!*

### Ordering Information

| Part Number            | Description                                                  |
|------------------------|--------------------------------------------------------------|
| <b>SSF4488-INN-A01</b> | 44.8",1600nits,1920*538.LID44A,3in1,V1                       |
| <b>SSH4488-INN-J01</b> | 44.8",1600nits,1920*538,LID44A.AD5827GDHP,AC100~240V,3in1,V1 |
|                        |                                                              |

### Optional Accessories

| Part Number         | Description                          |
|---------------------|--------------------------------------|
| <b>810618301010</b> | CABLE.POWER.AC.1830mm USA type       |
| <b>810618301090</b> | CABLE,POWER,AC,1830mm Europe type    |
| <b>810618301050</b> | CABLE.POWER.AC.1830mm UK type        |
| <b>810618301170</b> | CABLE.POWER,AC,1830mm Australia type |
| <b>810618301031</b> | CABLE.POWER.AC.1830mm Japan type     |
|                     |                                      |

### By Customer Request

|              |                                 |
|--------------|---------------------------------|
| <b>Glass</b> | Tempered glass, AR coating..... |
|--------------|---------------------------------|

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660