

VMS-RPPS

**Intel® 12/13th Rugged Fanless Vehicle
Telematics System**



Product Features

- Intel® 12/13th Gen PS-series Core i7/i5/i3/Celeron® Processor
- 2-262 Pin SODIMM Socket Max. Up to 64GB DDR5 4800MHz
- 3-Storage, 1-M.2 Key-M, 2-2.5" External Drive Bay
- 9~60Vdc Input, with Ignition Control & Vehicle Power Management
- CE, FCC A, E-Mark, ISO7637-2 Certified
- Intel® Iris® Xe/UHD Graphics
- 3-Expansion, 1-Full Size Mini PCIe, 1-M.2 Key-E, 1-M.2 Key-B w/ SIM slot
- Onboard GPS module, Support RAID 0/1, TPM 2.0, iAMT
- -40C~70C Operating Temperature

Specification

System Information

Processor	Intel® 13th Raptor Lake/12th Alder Lake PS-series Core i7/i5/i3/Celeron® Processor
System Memory	2 x 262-Pin SODIMM Socket Max. Up to 64GB DDR5 4800MHz (non ECC only)
BIOS Information	AMI UEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	CPU & System Temperature monitoring Voltage monitoring
RAID	Support RAID 0/1
TPM	TPM 2.0
iAMT	Depends on sku

Expansion

M.2	1 x M.2 Key-E 2230 (1 x PCIe1 + USB2.0) supports Wi-Fi & BT Module 1 x M.2 Key-B 3042/3052 (1 x PCIe1 + USB3.2) w/ SIM slot2(external)
-----	---

mPCIe	1 x Full Size Mini PCIe (1 x PCIe1 + USB2.0) w/ SIM slot2(external)
-------	---

Storage

M.2	1 x M.2 Key-M 2280 (1 x PCIe4) NVMe
-----	-------------------------------------

2.5 Drive Bay	2 x 2.5" Drive Bay (SATA III, Max. up to 15mm Height Storage), RAID 0/1 supported
---------------	---

Front I/O

USB	2 x USB 2.0
-----	-------------

Power Button	1 x Push Button for Power on/off w/ LED(Blue)
--------------	---

Reset Button	1 x Push Button for Reset in hiding
--------------	-------------------------------------

COM Port	1 x RS232/422/485(Jumper + DIP switch), support auto-flow
----------	---

LED Indicator	1 x LED indicators for Storage (Yellow) - M.2 M-key PCIe Storage 1 x LED indicators for LTE (Green) - M.2 B-key 1 x LED indicators for Wi-Fi (Green) - M.2 E-key
---------------	--

SIM Slot	2 x SIM Card Slot (External Accessible w/Dust Protection Cover)
----------	---

Digital I/O	1 x 10-bits GPIO (5 x DI (9~60V) and 5 x DO (30V/200mA)), SW control
-------------	---

Rear I/O

USB	2 x USB 3.2 Gen.2
-----	-------------------

COM Port	2 x RS232/422/485(Jumper + DIP switch), support auto-flow (COM2/3 via Cable)
----------	--

LAN Port	4 x RJ-45 (4 x PoE Available for BOM option)
----------	--

Audio	1 x Line-Out 1 x Mic-In
-------	----------------------------

DP	2 x DP++ 1.4
----	--------------

HDMI	2 x HDMI 2.0
------	--------------

Antenna	2 x Antenna Mounting w/Dust Protection Cover
---------	--

Right I/O

Antenna	3 x Antenna Mounting w/Dust Protection Cover
---------	--

Left I/O

Antenna	3 x Antenna Mounting w/Dust Protection Cover
---------	--

GPS

Chipset	u-blox NEO-M9N GNSS LCC module with Untethered Dead Reckoning and onboard sensors.
---------	--

Protocol BeiDou, Galileo, GLONASS, GPS / QZSS

Display

Graphic Chipset Intel® Iris® Xe Graphics (i7-1265UL/ i5-1245UL)
Intel® UHD Graphics (i3-1215UL/Celeron® 7305L)

Resolution HDMI 2.0: Max. resolution 4096 x 2304 @ 60Hz
DP++ 1.4a: 4096x2304 @ 60Hz (DP to HDMI cable can't support 4K @ 60Hz, Max. up to 1920x1080 (60Hz))

Audio

Audio Codec Realtek ALC888S co-lay ALC897 (Default: ALC888S)

Ethernet

LAN Chipset 4 x Intel® I226IT 2.5 Gigabit Ethernet

Specification 4 x 10/100/1000/2.5G Base-Tx GbE compatible

Power Requirement

Voltage Input Spec. Typical 12/24/48 Vdc (+9 ~ 60Vdc)

Voltage Input Connector 1 x 3-Pin Terminal Block for DC Power Input

ACPI Single Power ATX Support S0, S3, S4, S5
ACPI 5.0 Compliant

Power Mode Vehicle Power Mode (Default Setting)/Industrial PC Power Mode
AT / ATX mode Switchable Through Jumper

Software Support

OS Win 10/Win 11/Linux

Certification

Certification Information CE, FCC Class A, E24 Mark, ISO 7637-2, IP50

Mechanical & Environmental

Operating Temp. Standard System: -40°C ~ 70°C (-40°F ~ 158°F) with 0.5m/S air flow, extended temperature peripherals (Factory option)
System with PoE: -40°C ~ 60°C (-40°F ~ 140°F) with 0.5m/S air flow, extended temperature peripherals (Factory option)

Storage Temp. -30°C ~ 70°C (-22°F ~ 185°F)

Operating Humidity 5% ~ 90% Relative Humidity, Non-condensing

Dimension (W x L x H) 239.4 x 160 x 55 mm (TBD)

Weight 3kg (TBD)

Vibration Test	Operating with SSD : MIL-STD-810G, Method 514.6, Category 4, common carrier US highway truck vibration exposure Storage with SSD : MIL-STD-810G, Method 514.6, Category 24, minimum integrity test
Shock Test	Operating with SSD : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G Non-Operating with SSD : MIL-STD-810G, Method 516.6, Procedure V, crash hazard shock test=75G
Drop Test	Package drop test Reference ISTA 2A, Method : IEC-60068-2-32 Test : Ed Test phase : One corner, three edges, six faces
IP Rating	IP50
Mounting Kit	Wall mount kit (Standard)

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660