

# OF17W5D

Open Frame, 17" 1440x900, LED Backlight 400nits

## Specification



### Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Available with auto-brightness sensor offers application in day and night
- Optional build-in touch screen for interactive application
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |   |  |   |
|---------------------|---|--|---|
| Panel               | Cell Type / Glass Surface   | TFT LCD / Black Anti-Glare, low reflection coating                         |   |
|                     | Aspect Ratio / Size   | Wide / 17" viewable diagonal area  |   |
|                     | Active Area / Pixel Pitch   | 367.2(H) x 229.5(V) mm / 0.255(H) x 0.255(V) mm                            |   |
|                     | Native Resolution / Colors  | 1440(H) x 900(V) / 262 K   |   |
|                     | Brightness / Contrast   | 400 cd/m <sup>2</sup> (typ) / 800 : 1                                      |   |
|                     | Response Time   | ≤ 8 ms   |   |
|                     | Viewing Angle (typical)   | H. 130° (- 65° ~ + 65°) , V. 100°(- 50° ~ + 50°)                           |   |
|                     | Light Source  | LED Backlight, Long life, 35,000 hrs (typ)                                 |   |
| Input Sources       | PC System   | Signal   | Analog RGB (0.7/1.0 V <sub>p-p</sub> , 75 ohms)         |
|                     |   | Sync   | Separate Sync, Composite Sync, Sync On Green            |
|                     |   | Frequency  | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System  | 2W Amplifier   |   |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Inlet |  |   |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)          |  |   |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)                            |  |   |
| Power               | Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz      |  |   |
| Power Consumption   | Operation / Power Saving  | 11 watt , < 2 watt (Support DPMS)  |   |
| Operating Condition | Temperature / Humidity  | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)                    |   |
| Storage Condition   | Temperature / Humidity  | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)                |   |
| Certification       | FCC , CE  |  |   |
| Dimensions          | Physical  | With Flanges(W x H x D) : 410.0 x 283.0(Center screw-to-screw) x 53.8 (mm) |   |
|                     |   | Without Flanges(W x H x D) : 410.0 x 271.0 x 53.8 (mm)                     |   |
|                     | Carton  | W x H x D = TBD  |   |
| Weight              | N.W. / G.W.   | 4.2 Kgs / 5.2 Kgs  |   |
| Container Loaded    | 20ft / 40ft / 40ft HQ   | TBD (Sets , By pallet)   |   |

|         |                  |                      |                          |                              |
|---------|------------------|----------------------|--------------------------|------------------------------|
| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |

**Winsonic**<sup>®</sup>

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com  
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C

Online Download

[www.ewinsonic.com](http://www.ewinsonic.com)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660