

P1197E-500


19" SXGA TFT Expandable Industrial Touch Panel Computer with 7th/6th Gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® Processor, PCI/PCIe Slot

Features

- 19" SXGA TFT LCD display
- LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processor
- Intel® H110 chipset
- Less screw design for easy installation
- 4 USB 3.0, 2 USB 2.0 and 4 COM
- One PCle x4 or one PCle expansion slots
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust aluminum with IP65 compliant front bezel design







- 1. AC plug 2. Audio (Mic-in/Line-out)
- 3. 1 x RS-232/422/485
- 4. 2 x LAN
- 5. VGA
- 6. PCIe x4 or PCI 7 1 x RS-232
- 8. 4 x USB 3.0
- 9. 1 x DisplayPort 10. 1 x HDMI
- 11. 1 x RS-232 12. 1 x RS-232
- 13. Power switch
- 14. Rack mount hole







Introduction

The P1197E-500 is a multimedia 19" touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the P1197E-500 is powered by a high performance LGA1151 socket 7th/6th generation Intel® Core™ processor with the Intel® H110 chipset. It features four COM ports, two Gigabit Ethernet and up to 32GB memory of dual-channel DDR4-2133 that delivers high computing capability for high performance-demanding applications. The industrial touch panel PC is most suitable for kiosk, factory and automation.

Expandable for 1 PCle or 1 PCl

The P1197E-500 has one PCle x4 or one PCl slot for expansion purpose. User can easily plug in standard half-size PCl or PCle card based on any application needs.

Speaker and WLAN Antenna Supported

The P1197E-500 is equipped with built-in speakers for multimedia applications. It also supports WLAN module antenna (optional) for wireless network connectivity.

Friendly Less Screw Design

The P1197E-500 is designed with ease of maintenance in mind. There are only three screws on the back chassis, so that technicians can quickly remove the system's back cover with minimum effort.

Specifications

| Front Bezel | Aluminum w/ IP65/ | Aluminum w/ IP65/NEMA 4 rugged protection | |
|-------------|-------------------|---|--|
| LCD Panel | Display Type | 19" SXGA TFT LCD | |
| | Brightness | 250 nits | |
| | Resolution | 1280 x 1024 pixels | |
| | Viewing Angle | 170°/160° | |
| Main System | CPU | LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processor | |
| | Chipset | Intel® H110 | |
| | System Memory | 2 x 288-pin DDR4-2133 Long-DIMM, up to 32GB | |
| | BIOS | AMI UEFI BIOS | |
| | Storage | 1 x 3.5" or 1 x SATA HDD (9.5 mm height) | |
| | Drive | 1 x Built-in slim DVD-RW (optional) | |
| | Watchdog Timer | 255 levels, 1 to 255 sec. | |

Specifications

| IO Connector | 3 x RS-232 | |
|-----------------------|---|--|
| | 1 x RS-232/422/485 | |
| | 1 x HDMI | |
| | 1 x VGA | |
| | 1 x DisplayPort | |
| | 4 x USB 3.0 | |
| | 2 x USB 2.0 | |
| | 2 x 10/100/1000 Mbps Ethernet (Intel® i219-LM/i211-AT) | |
| TO: 4 | 1 x Audio (Mic-in & Line-out) | |
| TPM | N/A | |
| Expansion Interface | 1 x PCle x4 or 1 x PCl | |
| Touchscreen | 5-wire resistive type | |
| | Light transmission 79% | |
| | 1 million activations (typical) at a single point | |
| Power Supply | 100 to 240 VAC, 200W | |
| Power Consumption | 157W | |
| Dimensions | 482 mm (18.98") (W) x 94.7 mm (3.73") (D) x 380.8 mm (14.99") (H) | |
| Packing Dimensions | 615 mm (24.21") (W) x 250 mm (9.84") (D) x 585 mm (23.03") (H) | |
| Weight(net/gross) | 8 kg (17.64 lb)/10.4 kg (22.93 lb) | |
| Operating temperature | 0°C to +45°C (+32°F to +113°F) | |
| Relative humidity | 10% to 90% @ +40°C, non-considering | |
| Operating vibration | 1.0G, 5 - 500 Hz, random | |
| Certifications | CE | |

Packing list

- 1 x P1197E-500 1 x Driver CD
- 1 x Panel mount kit 1 x US power cord

Ordering Information

| P1197E-500 with PCle | 19° SXGA expandable industrial touch panel computer with LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen, PCle x4 slot and 100 to 240 VAC |
|----------------------|---|
| P1197E-500 with PCI | 19" SXGA expandable industrial touch panel computer with LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen, PCI slot and 100 to 240 VAC |

^{*}Specifications and certifications may vary based on different requirements.

Optional Accessories

| Wi-Fi kit | |
|--------------|-----------------------------|
| 82211970070E | VESA & wall mount kit |
| E981604011 | ATC10 (VESA arm clamp type) |
| E981604012 | ATW10 (VESA arm wall mount) |
| E221177116 | PPC HA741L black stand (L) |

Optional EOS Installation


Windows® 10 IoT Enterprise

Optional OS Installation

Windows® 10



Dimensions



^{*} All specifications and photos are subject to change without notice. www.axiomtek.com

© 2020 Axiomtek Co., Ltd. All rights reserved.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660