



NUC-APL-Slim

Intel® Apollo Lake Fanless NUC Slim System

- > Onboard Intel® Celeron® Processor J3455/N3350
- > Single DRAM Socket, Max. Up to 8GB DDR3 1866MHz
- > Rich I/O, 1 x COM, 2 x HDMI, 2 x LAN, 4 x USB3.0, 1 x Audio, 2 x Antenna Mounting
- > Expansion Slot, M.2 Key-B, M.2 Key-E
- > Fanless Operating from 0°C ~ 50°C
- > DC Power Input +12V
- > Compact Size, 115mm x 111mm x 45mm
- > Supports VESA/Din-Rail Kit
- > TPM 2.0 (Factory Option)

+ Spec

-System Information-	
Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz) Intel® Celeron® Processor N3350 (2M Cache, up to 2.4 GHz)
System Memory	1 x 204-pin SO-DIMM Socket, Max. Up to 8GB DDR3L 1866MHz
BIOS Information	AMI BIOS, 128Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU Temperature, Voltage with Auto Throttling Control
SBC	NCM-APL
Expansion	
Expansion	1 x M.2 (Key-B, 2242/3042, PCIe, SATA, USB 3.0, USB 2.0) 1 x M.2 (Key-E, 2230, PCIe, USB2.0)
Storage	
Storage	1 x M.2 (Key-B, 2242, SATA)
I/O	
USB Port	4 x USB 3.0 (5Gbps)
COM Port	1 x RS-232/422/485 (BIOS&Cable)
Antenna	2 x Antenna Mounting with Dust Cover
System Control	
LED Indicator	1 x Power on/off LED & Storage Access LED on front side
Display	
Graphic Chipset	Intel® HD Graphics 500
Spec. & Resolution	2 x HDMI 1.4b: Max. Resolution 3840x2160@30Hz *1 x DP/DV-HVGA (Factory Option): Max. Resolution 1920 x 1080@60Hz *DP/DV-HVGA is an option which will replace the location of COM.
Multiple Display	Dual Display
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	1 x Audio Jack (Mic-in + Line-Out Combo)
Certifications	
Certification Information	CE, FCC Class A, UKCA
Ethernet	
LAN Chipset	Realtek RTL8111E Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx Gigabit Ethernet Compatible
LAN Port	2 x RJ45
Power Requirement	
DC Input	+12V
DC Input Connector	Lockable DC Jack
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant
Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 12V/5A AC-DC 60W Adapter
Mechanical & Environmental	
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F) with 0.2m/s air flow -10°C ~ 50°C (14°F ~ 122°F) with 0.5m/s air flow
Storage Temperature	-30~70°C (-22°F ~ 158°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	115mm x 111mm x 45mm (4.53" x 4.37" x 1.77")
Weight	0.72KG (1.59lbs)

www.avalue.com.tw



Vibration Test	With SSD: 5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis
Shock Test	With SDD : 55G, IEC 60068-2-27, Half Sine, 11ms, Z Axis
Mounting Kit	VESA/Din Rail Kit
Drop	ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces
Construction	Aluminum + Metal
Software Support	
OS Information	Win 10, Linux
Ordering Information	
Ordering Information	NUC-APL-34-B1-2R Intel® Celeron® Processor J3455 Fanless NUC Slim System
	NUC-APL-33-B1-2R Intel® Celeron® Processor N3350 Fanless NUC Slim System
	E1702031831R Australia Power Cord
	E1702031833R USA Power Cord
	E1702031834R Japan Power Cord
	E170P060380R UK Power Cord
	E1702031000R EU Power Cord

www.avalu.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660