

AI Embedded Box PCs

## COMPACT AI Rugged Series

Computer Vision Edge Unit with NVIDIA Jetson TX2 NX

LTE / GNSS / Wi-Fi



2x USB 2.0  
microSD  
DisplayPort

Image similar



Power Supply  
9 ... 45VDC

CAN

2x Gbit LAN

USB 3.1

HDMI

Rugged AI Computer

## RPC/COMPACT A2N

This fanless COMPACT A2N generation is based on the NVIDIA Jetson TX2 NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- IP67 protection
- Product lifecycle management
- Long term availability with fixed BOM



**NVIDIA.** Linux for Tegra (L4T)

### Product Highlights

Ultra rugged  
Sealed housing, protection class IP67  
Maintenance free  
Power Ignition controller  
No moving parts / passively cooled  
Pressure equalization membrane  
Resistance to chemicals  
Long term availability (fixed BOM)

### Product Features

256-core NVIDIA Pascal™ GPU Dual-Core  
NVIDIA Denver 2 64-Bit CPU Quad-Core  
ARM® Cortex®-A57 MPCore  
4GB 128-bit LPDDR4x RAM soldered on board  
M.2 NVMe slot for storage expansion up to 2TB  
Ethernet, USB, active / passive CAN  
Optional LTE & WiFi extensions  
Aluminum housing

### Markets / Applications

Autonomous Mobile Robots (AMRs)  
Agriculture  
Construction  
Transportation  
Off-Highway Vehicles  
Heavy Industry  
Outdoor applications



Order Code RPC/RSA2NH20-A102S<sup>1,5</sup>

Processor module / Performance		
NVIDIA Jetson TX2 NX   256-core NVIDIA Pascal™ GPU		•
6-Core ARM CPU (Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore)		•
AI Performance		1.33 TFLOPs
Memory / Storage		
Data Cache Size		2MB
128-bit LPDDR4 RAM soldered on board		4GB
eMMC 5.1 Flash Storage on board		16GB
M.2 2280 Key M socket (for NVMe SSD) <sup>5</sup>		1
microSD card socket <sup>2</sup>		1
Features		
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)		•
Hardware Watchdog & Temperature supervisor		•
Inertial measurement unit (IMU) <sup>1</sup> STMicroelectronics ISM330DHCXTR		on request
Buzzer		on request
Communication Interfaces		
Video output <small>behind the service cover</small>		DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small>	(micro USB Type AB )	1
USB version 2.0 <small>behind the service cover</small>	(Type A )	2
Video output		HDMI 2.0
USB version 3.1 (5 Gbit/s)	(Type A )	1
Ethernet 10/100/1000 BASE-T (1x native, 1x I210-IT)	(M12 female, x-coded)	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated	(M12 female, a-coded)	1
Mini PCIe socket <sup>2</sup>		2
I2C bus <sup>2</sup>		1
Serial RS232 <sup>1</sup>	(M12 female, a-coded)	on request
USB version 2.0 <sup>1</sup>	(M12 female, a-coded)	on request
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>		on request
Wireless Connectivity		
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS		none
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth		none
High precision GNSS module <sup>1</sup> u-blox ZED-F9R / F9P		none
Technical Data		
Dimensions [mm] (housing, incl. mounting)		w245 x h66 x d165
Net weight [gram]		~2300
Non isolated Input voltage, with Ignition controller, reverse polarity protected	(M12 male, a-coded)	9 ... 45VDC
Idle power consumption typ. in Watt @ 24V without Add-Ins		~8.5
Environmental Conditions		
Operating temperature <sup>3</sup>		-25°C ... +70°C
Storage temperature		-25°C ... +85°C
Ingress protection standard according to EN60529		IP67
Conformal coating <sup>4</sup>		on request
Shock (designed to meet)		EN60068-2-27
Vibration (designed to meet)		EN60068-2-64
EMI-Conformity (designed to meet)		EN55032 / EN55035
Safety (designed to meet)		EN62368-1
Radio and Telecommunication (designed to meet)		n/a
estimated MTBF @ 25°C ambient <small>excluding battery</small>		~550 000h

<sup>1</sup>Please contact factory for minimum order quantities

<sup>2</sup>Internal connector

<sup>3</sup>Depending on installation situation and interface connection. Derating of max. operating temp. is possible when using the cellular LTE module. Please see user documentation.

<sup>4</sup>On all possible components (excl. TX2 NX module, connectors and wireless devices)

<sup>5</sup>It is possible to equip the products with an Industrial grade Apacer PV210 NVMe SSD. Retrofitting an SSD is not possible by the user without complete disassembly. Use these part codes:

RPC/RSA2NH20-[A/B]102S-01 = 120GB | RPC/RSA2NH20-[A/B]102S-02 = 240GB | RPC/RSA2NH20-[A/B]102S-05 = 480GB | RPC/RSA2NH20-[A/B]102S-10 = 960GB

<sup>6</sup>On products version 2.0 and up, these LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL.

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogic Datentechnik AG  
All rights reserved

Syslogic Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:

info@syslogic.com  
support@syslogic.com  
www.syslogic.com

+41 56 200 90 40  
+49 7741 9671-420

Switzerland (Headquarters)  
Germany and Austria

 **syslogic**  
industrial computing

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660