

# M700DM8-4E, 7-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

M700DM8 is a compact rugged tablet PC with robust set of features designed to withstand industrial use while providing high tech solutions that increase productivity, improve safety, and reduce operational costs.

The processing power comes from Arm<sup>®</sup> Cortex<sup>®</sup>-A53 Octa Core processor that supports Android 7.0 OS. The tablet features a brilliant, in-plane switching with projected capacitive touch screen and offers 1280 x 720 pixel resolution. Weighing at just 1.2 pounds (approx. 550 grams) the M700DM8 delivers lightweight mobility in a pocket-sized rugged tablet.



#### Highlights

- Arm<sup>®</sup> Cortex<sup>®</sup>-A53 Octa Core Processor
- 7" 1280 x 720 TFT Panel with direct optical bonding
- Supports Android 7.0 OS
- Hot-swappable battery design
- IP65 waterproof and dustproof
- Rated for extreme temperature use
- Optional integrated 2D barcode reader

# Order Information 4G 2D Barcode Reader M700DM8-4E 4G/LTE for for EU and Asia Optional M700DM8-4EBM 4G/LTE for for EU and Asia Default

#### NFC Tag Support

Support Card Type (13.56 MHz)		
NFC Forum Platform	Type 1, Type 2, Type 3, Type 4	
ISO 15693	TI HF-I Plus, TI HF-I Pro, NXPI-Code SLI	
ISO 14443-A	NXP Mifare_One(S50_4byte), NXP Mifare_One(S50_7byte), NXP Mifare_One(S70_4byte), NXP Mifare_UltraLight, NXP Mifare_UltraLight C NXP Mifare_EV1 NXP Mifare_Plus \$/X	
ISO 14443-B	Ifineon JTOP	
ISO 18092(R/W)	SONY Felica Lite s, SONY Felica Lite	

# Winmate



# M700DM8-4E, 7-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

Disp	av :	Spec	ifica	tion
Diopi		opou		

n
7-inch
1280 x 720 650 nit
With direct optical bonding for sunlight readable
Multi-touch projected capacitive
800:1
80/80/80
<ul> <li>Ambient light sensor, g-sensor</li> </ul>
Automatic screen rotation
n
Arm® Cortex®-A53 Octa-core 1.3 GHz
2GB RAM <sup>1</sup>
16GB eMMC
Additional storage available with optional Storage Card
SD (up to 2 GB), SDHC (up to 64 GB)
Android 7.0
ation
802.11 a/b/g/n
Bluetooth 4.0
Support BLE mode + wide-band speech
GPS / AGPS / GLONASS
4G/ LTE or 3G.
1 x docking connector
1 x Micro USB OTG
1 x Power Jack
1 x Micro SD Card Slot
1 x SIM Card Slot
10-point multi touch,
support Hand / Gloves and Rain Mode
On-screen QWERTY keyboard
Button 1 x Volume +/- , 1 x Power Button,
1 x Home Button, 1 x Menu Button,
1 x Return Button, 1 x Trigger Button
2 x LED indicators (Power, Battery)
2 x Built-in Mic
1 x 1.2 W speaker
1 x 1.2 W speaker
1 x 1.2 W speaker
1 x 1.2 W speaker 1 x Earphone
1 x 1.2 W speaker 1 x Earphone 2MP Camera
1 x 1.2 W speaker 1 x Earphone 2MP Camera
1 x 1.2 W speaker 1 x Earphone 2MP Camera 8MP Camera with LED auxilliary light (auto focus)
1 x 1.2 W speaker 1 x Earphone 2MP Camera 8MP Camera with LED auxilliary light (auto focus)

#### **Mechanical and Environment**

Dimension (W $\times$ L $\times$ H)	212.4 x 132.8 x 19 mm (8.36 x 5.23 x 0.75 inches) <sup>3</sup>
Weight	550g
Operating Temperature	-20°C to 60°C (AC mode), -10°C to 50°C (Battery mode)
Storage Temperature	-30°C to 70°C (-22°F to 158°F)
Humidity	5% to 95% RH, non-condensing
IP Proof	IP65 Certified, waterproof and dustproof
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
Drop	MIL-STD-810G Method 516.6, 5 ft to concrete <sup>4</sup>

#### **Power Management**


Power Input	5V DC	
Battery	3.7V 5300mAh Li-Poly	
Battery Operating Time	20Hr 5	
Adapter	100-240V/ 5V 3A Adapter	

#### Accessories

#### **Standard Accessories**

Universal Adapter	9226015W05V1				
Battery	98K007SP002P				
Optional Accessories <sup>6</sup>					
Battery Charging Dock	98TA00Z00003				
Vehicle Dock (Charging + Connectors)	98TA07Z00004				
Vehicle Dock (Charging Only)	98TA07Z00003				
Desk Dock	98TA07Z00005				
Hand Strap	98K000A0004R				
Carry Bag	9B00000000X				
Micro SD Card	76G004300000				
Capacitive Touch Stylus	9B00000001D				

### Vehicle Adapter



98TZ00ZZ0006



Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example) Do not expose bare skin to this product when handling this unit in extreme

Caution hot or cold environments

1. Total usable memory will be less depending upon actual system configuration

- 2. SOTI are available upon request 3. Length measurements do not include protrusions.
- 4. The drop test with high-capacity battery must come with hand strap Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- A coessories and Integrated Options may vary depending on your configuration.
   This is a simplified drawing and some components are not marked in detail.





## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660