




www.transcend-info.com



Embedded Solutions

DRAM Modules DDR3



Transcend's DDR3 DRAM modules operate at a nominal voltage of 1.5V or 1.35V, offering exceptional clock speeds to cater to the demands of the embedded industry. The modules are available in multiple form factors and technologies, such as ECC and wide-temperature support. All components are of the highest quality, having been sourced directly from the world's first-tier supplier of DRAM chips and stringently tested for unparalleled compatibility, reliability, and performance.

Features

- JEDEC standard 1.5V $\pm$ 0.075V power supply
- Low Voltage models: JEDEC standard 1.35V (1.28V~1.45V) power supply
- 8 bit pre-fetch
- Burst Length: 4, 8
- Internal calibration through ZQ pin
- On-die termination with ODT pin
- Serial presence detect with EEPROM
- 100% tested for stability, compatibility and performance

Advanced Technologies



Anti-Sulfur
Technology



Corner Bond &
Underfill



Conformal
Coating



Wide
Temperature



30μm
Gold Finger

DDR3 Unbuffered DIMMs

Module Type	DDR3	
	Long-DIMM	SO-DIMM
Product Image		
Standard	JEDEC	
Speed	1866/1600/1333 Mbps	
Capacity	1GB~8GB	
Voltage	Standard voltage: 1.5V Low voltage: 1.35V	
Pin Count	Long-DIMM: 240 pin	SO-DIMM: 204 pin
PCB Height*	1.18 inches	
Operating Temperature	Standard Temperature: 0°C~ 85°C Wide Temperature: -40°C~ 85°C	

Ordering Information

DDR3-1866 Long-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
4GB	(512Mx8)x8	1Rx8	-	-	TS512MLK64W8H	-

DDR3-1866 SO-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
2GB	(256Mx8)x8	1Rx8	TS256MSK64V8N	-	TS256MSK64W8N	-
4GB	(512Mx8)x8	1Rx8	-	-	TS512MSK64W8H	TS512MSK64W8H-I
8GB	(512Mx8)x16	2Rx8	-	-	TS1GSK64W8H	TS1GSK64W8H-I

* DDR3 Long-DIMM VLP modules (0.74 inches) are also available.

DDR3-1600 Long-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
1GB	(128Mx8)x8	1Rx8	TS128MLK64V6U	TS128MLK64V6U-I	TS128MLK64W6U	TS128MLK64W6U-I
2GB	(128Mx8)x16	2Rx8	TS256MLK64V6U	TS256MLK64V6U-I	TS256MLK64W6U	TS256MLK64W6U-I
2GB	(256Mx8)x8	1Rx8	TS256MLK64V6N	TS256MLK64V6N-I	TS256MLK64W6N	TS256MLK64W6N-I
4GB	(256Mx8)x16	2Rx8	TS512MLK64V6N	TS512MLK64V6N-I	TS512MLK64W6N	TS512MLK64W6N-I
4GB	(512Mx8)x8	1Rx8	TS512MLK64V6H	TS512MLK64V6H-I	TS512MLK64W6H	TS512MLK64W6H-I
8GB	(512Mx8)x16	2Rx8	TS1GLK64V6H	TS1GLK64V6H-I	TS1GLK64W6H	TS1GLK64W6H-I

DDR3-1600 SO-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
1GB	(128Mx8)x8	1Rx8	TS128MSK64V6U	TS128MSK64V6U-I	TS128MSK64W6U	-
2GB	(128Mx8)x16	2Rx8	TS256MSK64V6U	TS256MSK64V6U-I	TS256MSK64W6U	TS256MSK64W6U-I
2GB	(256Mx8)x8	1Rx8	TS256MSK64V6N	TS256MSK64V6N-I	TS256MSK64W6N	TS256MSK64W6N-I
4GB	(256Mx8)x16	2Rx8	TS512MSK64V6N	TS512MSK64V6N-I	TS512MSK64W6N	TS512MSK64W6N-I
4GB	(512Mx8)x8	1Rx8	TS512MSK64V6H	TS512MSK64V6H-I	TS512MSK64W6H	TS512MSK64W6H-I
4GB	(512Mx8)x8	1Rx8	-	-	-	TS512MSK64W6H3-I
8GB	(512Mx8)x16	2Rx8	TS1GSK64V6H	TS1GSK64V6H-I	TS1GSK64W6H	TS1GSK64W6H-I
8GB	(512Mx8)x16	2Rx8	-	-	TS1GSK64W6H-G	-

DDR3-1333 Long-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
1GB	(128Mx8)x8	1Rx8	TS128MLK64V3U	-	-	-
2GB	(256Mx8)x8	1Rx8	TS256MLK64V3N	-	-	-
4GB	(256Mx8)x16	2Rx8	TS512MLK64V3N	-	-	-
4GB	(512Mx8)x8	1Rx8	TS512MLK64V3H	-	-	-
8GB	(512Mx8)x16	2Rx8	TS1GLK64V3H	-	-	-

DDR3-1333 SO-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
1GB	(128Mx8)x8	1Rx8	TS128MSK64V3U	TS128MSK64V3U-I	TS128MSK64W3W	-
2GB	(256Mx8)x8	1Rx8	TS256MSK64V3N	TS256MSK64V3N-I	TS256MSK64W3N	-
4GB	(256Mx8)x16	2Rx8	TS512MSK64V3N	TS512MSK64V3N-I	TS512MSK64W3N	-
4GB	(512Mx8)x8	1Rx8	TS512MSK64V3H	-	-	-
8GB	(512Mx8)x16	2Rx8	TS1GSK64V3H	-	-	-

* DDR3 Long-DIMM VLP modules (0.74 inches) are also available.

DDR3 ECC DIMMs

Module Type	DDR3	
	ECC Long-DIMM	ECC SO-DIMM
Product Image		
Standard	JEDEC	
Speed	1600/1333 Mbps	
Capacity	2GB~8GB	
Voltage	Standard voltage: 1.5V Low voltage: 1.35V	
Pin Count	Long-DIMM: 240 pin	SO-DIMM: 204 pin
PCB Height*	Standard: 1.18 inches Very Low Profile: 0.74 inches	
PCB Gold Finger Thickness	30μ"	
Anti-Sulfuration	Default	
Operating Temperature	Standard Temperature: 0°C~ 85°C Wide Temperature: -40°C~ 85°C	

Ordering Information

DDR3-1600 ECC Long-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
2GB	(128Mx8)x18	2Rx8	TS256MLK72V6U	TS256MLK72V6U-I	TS256MLK72W6U	TS256MLK72W6U-I
2GB	(256Mx8)x9	1Rx8	TS256MLK72V6N	TS256MLK72V6N-I	TS256MLK72W6N	TS256MLK72W6N-I
4GB	(256Mx8)x18	2Rx8	TS512MLK72V6N	TS512MLK72V6N-I	TS512MLK72W6N	TS512MLK72W6N-I
4GB	(512Mx8)x9	1Rx8	TS512MLK72V6H	TS512MLK72V6H-I	TS512MLK72W6H	TS512MLK72W6H-I
8GB	(512Mx8)x18	2Rx8	TS1GLK72V6H	TS1GLK72V6H-I	TS1GLK72W6H	TS1GLK72W6H-I

DDR3-1600 ECC Long-DIMM

Capacity	Component Composition	Rank x Org.	Very Low Profile (VLP)
4GB	(512Mx8)x9	1Rx8	TS512MLK72W6HL
8GB	(512Mx8)x18	2Rx8	TS1GLK72W6HL

* DDR3 ECC Long-DIMM VLP modules (0.74 inches) are also available.

DDR3-1600 ECC SO-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
2GB	(256Mx8)x9	1Rx8	TS256MSK72V6N	TS256MSK72V6N-I	TS256MSK72W6N	TS256MSK72W6N-I
4GB	(256Mx8)x18	2Rx8	TS512MSK72V6N	TS512MSK72V6N-I	-	TS512MSK72W6N-I
4GB	(512Mx8)x9	1Rx8	TS512MSK72V6H	TS512MSK72V6H-I	TS512MSK72W6H	TS512MSK72W6H-I
8GB	(512Mx8)x18	2Rx8	TS1GSK72V6H	TS1GSK72V6H-I	TS1GSK72W6H	TS1GSK72W6H-I

DDR3-1333 ECC Long-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
2GB	(128Mx8)x18	2Rx8	TS256MLK72V3U	-	-	-
2GB	(256Mx8)x9	1Rx8	TS256MLK72V3N	-	-	-
4GB	(256Mx8)x18	2Rx8	TS512MLK72V3N	-	-	-
8GB	(512Mx8)x18	2Rx8	TS1GLK72V3H	-	-	-

DDR3-1333 ECC SO-DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Wide Temp. (-40°C~ 85°C)	Low Voltage (1.35V)	Low Voltage + Wide Temp.
2GB	(256Mx8)x9	1Rx9	TS256MSK72V3N	TS256MSK72V3N-I	TS256MSK72W3N	-
4GB	(256Mx8)x18	2Rx8	TS512MSK72V3N	TS512MSK72V3N-I	-	-
4GB	(512Mx8)x9	1Rx8	-	-	TS512MSK72W3H	-
8GB	(512Mx8)x18	2Rx8	-	TS1GSK72V3H-I	TS1GSK72W3H	-

* DDR3 ECC Long-DIMM VLP modules (0.74 inches) are also available.

DDR3 Registered DIMMs

Module Type	DDR3
	Registered DIMM
Product Image	
Standard	JEDEC
Speed	1600/1333 Mbps
Capacity	2GB~16GB
Voltage	Standard voltage: 1.5V Low voltage: 1.35V
Pin Count	R-DIMM: 240 pin
PCB Height	Standard: 1.18 inches Very Low Profile: 0.74 inches
PCB Gold Finger Thickness	30μ"
Anti-Sulfuration	Default
Operating Temperature	Standard Temperature: 0°C~ 85°C

Ordering Information

DDR3-1600 Registered DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Low Voltage (1.35V)	Very Low Profile (VLP)
2GB	(256Mx8)x9	1Rx8	TS256MKR72V6N	TS256MKR72W6N	-
4GB	(256Mx8)x18	2Rx8	TS512MKR72V6N	TS512MKR72W6N	TS512MKR72V6NHL
4GB	(512Mx8)x9	1Rx8	TS512MKR72V6H	TS512MKR72W6H	TS512MKR72V6HHL
8GB	(512Mx8)x18	2Rx8	TS1GKR72V6H	TS1GKR72W6H	TS1GKR72V6HHL
16GB	(1Gx4)x36	2Rx4	TS2GKR72V6Z	-	-



www.transcend-info.com

DDR3-1333 Registered DIMM

Capacity	Component Composition	Rank x Org.	Standard (1.5V)	Low Voltage (1.35V)	Very Low Profile (VLP)
2GB	(256Mx8)x9	1Rx8	TS256MKR72V3N	-	TS256MKR72V3NL
8GB	(256Mx8)x36	4Rx8	TS1GKR72V3N	-	-
8GB	(512Mx4)x36	2Rx4	TS1GKR72V3Y	-	-
16GB	(512Mx8)x36	4Rx8	TS2GKR72V3H	-	-

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Due to the complexity and variety of industrial applications, Transcend cannot guarantee 100% compatibility with all platforms and under all scenarios. For special applications and environments, it is strongly suggested that you contact Transcend beforehand for clarification.



Please feel free to contact us with any special requests you might have.
Tel: +886-2-2792-8000 www.transcend-info.com



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660