



SPC-2133

21.5" Apollo Lake SoC Mobile Processor Fanless
Stainless Steel Chassis Touch Panel PC with Full
IP-65 & IP-X9K

- > Onboard Intel® Apollo Lake SoC with Integrated Chipset
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB
- > Rich I/O 3 x USB, 1 x COM(DB9), 1 x LAN
- > Metal Waterproof Connectors
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Optional WiFi/ High brightness solution
- > Full System IP65 & IPX9K
- > Fanless Operation

Spec

-System Information-	
Processor	Onboard Intel® Apollo Lake Mobile Processor
Platform Controller Hub	Intel Apollo Lake SoC integrated
System Memory	1 x 204-pin DDR3L 1600MTs SO-DIMM
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
SBC	EBM-APL
Expansion	
Expansion	1 x Mini PCIe
Storage	
Storage	1 x 2.5" Drive Bay
Panel	
LCD Size	21.5"
Display Type	WSXGA
Resolution	1920x1080
Pixel pitch	248.25um(H) x 248.25um(V)
Luminance	250 cd/m²
Contrast ratio	3000
Viewing angle	89 (U), 89 (D), 89 (L), 89 (R)
Response time	18 ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	89%
Touch Controller	Onboard USB touch (EETI)
I/O	
USB Port	3 x Waterproof USB 3.0
COM Port	1 x Waterproof COM(DB9, RS-232/422/485)
SATA	1 x SATA III
Other	1 x WiFi (Optional)
Display	
Graphic Chipset	Intel® Apollo Lake SoC integrated Graphics Supports dual display
Spec. & Resolution	HDMI: Max. resolution 3840x2160 @ 30Hz LVDS: Max. resolution 1920x1080 @ 60Hz eDP: Max. resolution 4096x2160 @ 60Hz
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	Line-Out
Speaker Output	2 x 5W
Certifications	
Certification Information	CE FCC Class A
Ethernet	
LAN Chipset	2 x Intel® I211AT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x Waterproof RJ-45
Power Requirement	

www.avalu.com.tw

DC Input Connector	Lockable Waterproof DC Jack
--------------------	-----------------------------

Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 60°C (14°F ~ 140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	9 Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
Mounting Kit	Wall / Stand / VESA 100mm x 100mm
Dimensions(W x L x D)	595 x 386 x 58mm
Power Requirement	+12V ~ +26V
Power Mode	AT/ATX (ATX is default setting)
System Fan	Fanless
Construction - Front	Stainless Steel
Construction - Rear	Stainless Steel
Software Support	
OS Information	Win10 Linux
Ordering Information	
Ordering Information	SPC-2133-335-A2R 21.5" 1920 x 1080 Full IP-65 Stainless Steel Panel PC w/PCAP Touch/IP-69K Intel Celeron N3350 (F1-CPU)/4GR/32GSSD/LAN/3USB/COM(DB9)/Speakers ACC-ARM-D1R VESA STAND, 75mm & 100 mm ACC-ARM-D23R VESA STAND, 75mm & 100 mm ACC-SPC-WIFI-1R Wifi Kits for SPC-15/17/22 802.11b/g/n MPCle/2Antenna/Cable E1702031833R USA Power Cord E1702031000R EU Power Cord E1702031834R Japan Power Cord E1702031830R UK Power Cord E1702031831R Australia Power Cord

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660