

## ARCDIS-121AP/R/G(H)


21.5" Front Panel IP66 Aluminum Die-casting Display

Industrial Panel PC

HMI Controller

Industrial  
Display Monitor

Box PC



### Features

- Industrial Display
- Flat front panel touch screen
- Fanless design
- Wide range DC 9~36V power input
- IP66 compliant front panel
- VGA/DVI-D/HDMI/DP input
- System power LED light
- High Brightness LCD and Auto Dimming for option
- Support protective AR glass for option (non-touch version)

### Specifications

| I/O Port             |                                                                                                       |
|----------------------|-------------------------------------------------------------------------------------------------------|
| VGA                  | 1 x VGA                                                                                               |
| DVI                  | 1 x DVI-D (share with HDMI)                                                                           |
| DP                   | 1 x DP                                                                                                |
| HDMI                 | 1 x HDMI (share with DVI-D)                                                                           |
| Audio                | 1 x Audio line-in phone jack                                                                          |
| OSD Control Membrane | OSD at rear side                                                                                      |
| Power                | 1 x 3-pin terminal block for DC 9~36V power input                                                     |
| Others               | 1 x USB type B for touch control<br>Optional I/O:<br>1 x Speaker<br>1 x RS-232 DB-9 for touch control |


| Display                        | Standard        | High Brightness Optional |
|--------------------------------|-----------------|--------------------------|
| Display Type                   | 21.5" TFT-LCD   | 21.5" TFT-LCD            |
| Max. Resolution                | 1920x 1080      | 1920 x 1080              |
| Max. Color                     | 16.7M           | 16.7M                    |
| Luminance (cd/m <sup>2</sup> ) | 250             | 1000                     |
| View Angle                     | 178(H) / 178(V) | 178(H) / 178(V)          |
| Contrast                       | 3000:1          | 3000:1                   |
| Backlight Lifetime             | 30,000 hrs      | 50,000 hrs               |

| Touch Screen          |                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------|
| Type                  | Resistive Touch (for AR Model)<br>Projected Capacitive Touch (for AP Model)<br>Glass (for AG model) |
| Interface             | USB default (Resistive / Projected Capacitive Touch)<br>RS-232 Option (Resistive Touch)             |
| Light Transmission(%) | Resistive Touch : over 80%<br>Projected Capacitive Touch : over 90%                                 |

| Power             |                         |
|-------------------|-------------------------|
| Power Input       | DC 9~36V                |
| Power Consumption | ARCDIS-121AP: 18W (MAX) |

| Mechanical         |                                    |
|--------------------|------------------------------------|
| Construction       | Aluminum Die-casting Chassis       |
| Mounting           | Panel Mount / VESA Mount 100 x 100 |
| IP Rating          | IP66 Compliant Front Panel         |
| Dimensions (WxHxD) | 557.3 x 362.3 x 64.8 mm            |
| Net Weight         | 7.5 kg                             |

### Dimensions



| Environmental         |                                  |
|-----------------------|----------------------------------|
| Operating Temperature | 0~50°C                           |
| Storage Temperature   | -30~70°C                         |
| Humidity              | 10 to 95% @ 40°C, non-condensing |
| Certificate           | CE/FCC, Class A                  |

| Ordering Information |                                                                                                                                                                                       |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARCDIS-121AR         | 21.5" FHD FPD Industrial display, Resistive touch window, VGA, DVI-D, HDMI, and DP input, 5 keys Rear OSD, DC 9~36V power input with adapter, Aluminum Die-casting Chassis            |
| ARCDIS-121AP         | 21.5" FHD FPD Industrial display, Projected Capacitive touch screen, VGA, DVI-D, HDMI, and DP input, 5 keys Rear OSD, DC 9~36V power input with adapter, Aluminum Die-casting Chassis |

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660