

iEP-5010G Series Industrial IoT Controller



Basic SKU

 PoE SKU
5LAN-WIFI SKU
5LAN-5G SKU

KEY FEATURES

- Latest and Powerful Intel® Atom® x6000RE Processor (Elkhart Lake)
- Fan-less and Rugged Design
- -40°C to 70°C Wide Operating Temp. for Basic SKU
- -40°C to 50°C Wide Operating Temp. for PoE SKU
- 6-36VDC Wide Range Power Inputs for Basic/5LAN/5G SKU
- 19-36VDC Wide Range Power Inputs for PoE SKU
- Most Flexible IOs and Expansion for Industrial Applications
- Intel® TCC and TSN Support for Real-Time Computing
- DIN Rail or Wall Mount Options
- 4 x Intel 1G LAN (2 Support IEEE 802.3AF PoE Ports)
- 1 x Intel 2.5G LAN
- Support Intel® IN-Band ECC

SPECIFICATIONS

System Core

Processor	Intel® Atom® x6000RE Processor (Elkhart Lake Platform) - iEP-5010G: Intel Atom® x6425RE, 4C, 1.9GHz, 12W - iEP-5011G: Intel Atom® x6214RE, 2C, 1.4GHz, 6W
Video	1 x HDMI 2.0b, 1 x VGA
Memory	2 x DDR4 3200MHz SO-DIMM, up to 32GB (In-Band ECC)

I/O Interface

Ethernet	2 x Intel® I210-IT (RJ45 8P8C) 1 x Intel® I226-IT, Support TSN (RJ45 8P8C) 2 x Intel® I210-AT for PoE SKU/5LAN SKU (RJ45 8P8C)
Ethernet/PoE (Option)	2 x Intel® I210-AT (RJ45 8P8C), PoE output max.15.4W/port, each port supports IEEE 802.3AF PoE. (For PoE SKU)
Serial Port	3 x RS-232/422/485 (9-pin D-sub connector)
USB	2 x USB 3.2 Gen1x1 2 x USB 2.0
Digital I/O	4DI/4DOs (9-pin D-sub connector)
Audio	1 x Mic in 1 x Line out

Expansion

SIM	1 x Nano SIM Card slot
RF Antenna (Option)	M.2 Wi-Fi 6E module supports IEEE 802.11 a/b/g/n/ac/ax + BT 5.2 - 3 x 4G LTE antenna and 2 x Wi-Fi antenna - 4 x 5G antenna and 2 x Wi-Fi antenna
M.2 Socket	1 x M.2 3042/3052 Key B (PCIe Gen3x1 / USB3.2 Gen1x1 mode) - Support 4G LTE/5G module 1 x M.2 2230 Key E (PCIe Gen3x1 / USB2.0 mode) - Support Wifi/BT module

Manageability / Security

Manageability	WDT, Intel® In-Band Manageability
Security	TPM2.0

Power Supply

DC Input	1 x 3-pin pluggable terminal block (Phoenix type) for 6 to 36V DC input (For Basic/5LAN SKU) 1 x 3-pin pluggable terminal block (Phoenix type) for 19 to 36V DC input (For PoE SKU) - OVP, UVP, OCP, plus 80V surge protection
AC to DC Adaptor (Option)	AC input 100-240Vac, 1.5A 50-60Hz, DC output 19V, 3.42A, 65W Adaptor (For Basic/5LAN SKU) AC input 100-240Vac, 1.8A 50-60Hz, DC output 19V, 6.32A, 120W Adaptor (For PoE SKU)

Storage Device

SD Slot	1 x Micro SD card slot (SD Card specification version 3.01)
SATA (Option)	1 x 2.5" 9.5mm SATA3 SSD (For Basic SKU only)
M.2 Socket	1 x M.2 2280 Key M (PCIe Gen3 / SATA3 mode)

Mechanical

Dimensions	58mm (W) x 125mm (D) x 157mm (H)
Indicator	1 x SATA / NVMe Storage LED, 1 x Wi-Fi / BT LED
Function	Power on Button with LED, Clear CMOS Button
Net Weight	Basic SKU: 1.43kg PoE SKU: 1.75kg 5LAN SKU: 1.65kg
Mounting (Option)	DIN-Rail or Wall mounting

Environmental

Operating Temperature	For Basic/5LAN SKU: -40°C ~ 70°C (-40°F ~ 158°F) (w/ airflow 0.5-0.8m/s) For PoE SKU: -40°C ~ 50°C (-40°F ~ 122°F) (w/ airflow 0.5-0.8m/s)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Humidity	~95% @ 40°C (non-condensing)
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes with SSD
ESD	Contact +/-8 KV, Air +/-15 KV
Shock	Operating 100G, half sine 11 ms duration with SSD
EMC	CE and FCC Class A (EN61000-6-4/-2)
Safety	LVD

Add-on Feature / OS Support

Real-Time Enablement	TSN, TCC support under Ubuntu (only LAN1)
OS Support	Windows 10, Ubuntu 22.04 LTS

Order Information	SKU	Processor	2.5 Storage	WiFi*	4G LTE/5G*	LAN	PoE
iEP-5010G-010	Basic SKU	X6425RE	Support by additional kits	Support	Support	3	Not Support
iEP-5011G-010		X6214RE					
iEP-5010G-011	PoE SKU	X6425RE	Not Support	Support	Not Support	5	Support
iEP-5011G-011		X6214RE					
iEP-5010G-012	5LAN-WIFI	X6425RE	Not Support	Support	Not Support	5	Not Support
iEP-5011G-012		X6214RE					
iEP-5010G-013	5LAN-5G	X6425RE	Not Support	Not Support	Support	5	Not Support
iEP-5011G-013		X6214RE					

*The Wi-Fi, 4G LTE and 5G module kits are purchased separately

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660