

Hisense

55L35B5U





Create a powerful visual experience with pixel perfect clarity with our latest video wall solutions. With an extra narrow bezel, Hisense video walls seamlessly recreate your desired content across almost any configuration style.

Highlights



Ultra-narrow bezel

An ultra-narrow 3.5mm bezel-to-bezel width creates a seamless and more perfect picture.



Round-the-clock operation

The Hisense L35B5U series can be used as reliable display 24 hours a day, 7 days a week.



178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view L35B5U displays from diverse angles while passing by.



500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



1200:1 Ultra high contrast

1200:1 ultra high contrast display, providing eye-catching vivid visuals any time of the day or night, with outstanding colour performance.



Specifications are subject to change without further notice

commercial-display.hisense.com



Hisense


55L35B5U


Specifications

• •	
Panel size	55"
Brightness	500nits
Resolution	1920 x 1080
Contrast Ratio	1200:1(typ.)
Back-Light	D-LED
Color	16.7M(8bit)
Viewing Angle	178°/178°
Refresh Ratio	8 ms
Surface Treatment	The surface of the LCD has an Anti-glare coating to minimize reflec- tion and a coating to Reduce scratching Haze 25%,3H,(Front Polarizer)
Usage time	24x7
MTBF	30000hours
Orientation	Landscape & Portrait
Physical	
Splice Pitch	3.5mm
VESA	400x400mm, M6
Set Dimension	1213.6 x 684.3 x 94.4mm
Packed Dimension	
רמנתכט ביווופווסוטוו	1360 x 240 x 840mm
Net Weight	1360 x 240 x 840mm 28.1
Net Weight	28.1
Net Weight Packed Weight	28.1 38
Net Weight Packed Weight 20GP container capacity (pcs)	28.1 38 74

Speaker	
Built-in Speaker	No
Power	
Voltage	100-240V 50/60Hz
Power Consumption	240W
Software	
os	Yes
Language	Chinese/English
Environment	
Operation Temperature	10-40°
Operation Humidity	10%-80%RH
Media Player compatibility	
OPS Type Compatible	No
Accessories	
Basic	Remote Controller, power cord, Ethernet cable, User Manual, RS232 connector,Infrared reception
Optional	Optional Wall Mount, Control Software, Process System
Certification	
Standard Certification CB, CE, ERP	CB C€

Display Dimensions





HISENSE COMMERCIAL DISPLAY



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660