

ViPAC-917P/R/G(H)

17" Intel 6th/7th Core i3/i5/i7 Panel PC

Industrial Panel PC

HMI Cotroller

Industrial Display Monitor

Box PC



Features /

- 17" TFT LCD Panel PC
- Intel 6th/7th Core i3/i5/i7 Socket type Processor
- Modular concept and with Fan Design
- Support PCT/RTW/AR Glass
- Front Bezel IP66
- Option WiFi/BT/Speaker
- Support 2 x Expansion slot
- DC 9~36V Power input, option AC power input



Specifications /

| CPU | Intel 6th/7th Gen Core i3/i5/i7 processor |
|----------------|--|
| System Chipset | Intel H170 |
| Memoni | 2 v 260 pin SO DIMM up to 32GB DDD4 2133 MHz SDDAM |

| IO Port | |
|--------------------|---|
| Rear side I/O port | 4 x USB3.0 type A 2 x R.445 GbE LAN 1 x DB9 RS-232/422/485 default RS-232 1 x DB9 RS-232 1 x DB9 RS-232 1 x DB9 RS-422/485 default RS-485 1 x DB15 VGA 1 x HDMI with Cover 1 x Line-out/Mic-in 1 x Zpin Terminal block for external power switch 2 x LED indication for HDD/System 1 x System LED indication at front 1 x 3pin TB Power connector 1 x Power Switch on/off |
| Option I/O | 2 x 2W speaker at rear side 4 x USB 2.0 Type A via TB-546 2 x DB9 COM port 1 x 8-bit GPIO (3 in/out/VCC/GND) |

| Storage Space | |
|---------------|--|
| HDD | 2x2.5" SATA HDD space, support RAID 0, 1, 5 (Easily Accessible storage design) |
| | |

| Expansion | | |
|----------------|---|---|
| Expansion Slot | 1 x Full-size Mini PCle on board(I 1 x Half-size Mini PCle on board 1 x SIM slot for option(Option wifi 1 x PCle x1 and 1 x PCle x16 slo | (PCIe/USB, PCIe by default) /BT/4G and antenna at rear sid |
| Display | Standard | High Brightness Optional |


| Display | Standard | High Brightness Optional |
|--------------------|-----------------|--------------------------|
| Display Type | 17" TFT-LCD | 17" TFT-LCD |
| Max. Resolution | 1280 x1024 | 1280 x1024 |
| Max. Color | 16.7M | 16.7M |
| Luminance (cd/m²) | 350 | 1000 |
| View Angle | 160(H) / 140(V) | 170(H) / 160(V) |
| Contrast | 800:1 | 1000:1 |
| Backlight Lifetime | 50,000 hrs | 50,000 hrs |
| Option | Auto Dimming | Auto Dimming |
| | | |

| Touch Screen | Resistive Touch | Projected Capacitive Touch |
|-----------------------|-----------------|----------------------------|
| Interface | USB | USB |
| Light Transmission(%) | Over 80% | Over 90% |


| Fower | |
|-------------|---|
| Power Input | DC 9~36V Power input, option AC power input |

All specifications and photos are subject to change without notice











E Mounting Hole Size

| UNIT: | mm |
|-------|----------|
| Toler | nnce:+05 |

| Mechanical | |
|---------------------------------|--|
| Construction | Aluminum die-casting front bezel and steel chssis Stainless front bezel (option) |
| Mounting | Panel Mount |
| IP Rating | Front Panel IP66 |
| Dimensions | 439 x 348 x 95 mm |
| Net Weight | 7.6 kg |
| Environmental | |
| Operating Tempe | rature 0~50°C |
| Storage Tempera | ature -30~70°C |
| Humidity | 10 to 95% @ 40°C, non- condensing |
| Certificate | CE / FCC Class A |
| Operating Syste | m Support |
| Windows embed | ded 7 |
| Windows embed Windows 10 IoT | 404 0.1 |
| TTINGOTTO OTTIDOG | Enterprise |
| Windows 10 IoT | Enterprise |

V 1.4

Industrial Panel PC

All specifications and photos are subject to change without notice

Industrial Panel PC



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660