

## Hisense

86" Air Conditioned Display

DO NOT MISS YOUR WORLD VACATIONS



# **86SOA25PT**

## 86" AIR CONDITIONED - ALL WEATHER DISPLAY

Hisense All Weather Digital Signage Display's are ideal for any retail and business environments. Our 2500nit high-bright screen provides clear content ensuring maximum engagement in any lighting conditions. The IP65 Air Conditioned cooled enclosure protects components in any conditions all year round with no filter maintainance required.

### Highlights



#### IP Rated All Weather Displays

The IP65 rating provide full protection against dust and water projection. Built in intelligent heating and cooling, together with a smart automatic air circulation system. Anti vandal glass for protection from extreme environmental conditions and impacts to the display.



#### Safety Lock and Invisible Screws and Hinges

With Professional three-point anti-theft lock design, internal locking of bolts, no exposed high-strength steel doors, Hisense Outdoor Display can prevent criminals from picking locks and doing malicious damage.



#### **Smart Brightness Sensor**

Adjusts the brightness of the monitor automatically according to the surrounding lighting conditions. This feature considerably reduces power consumption and increases the monitor's lifetime.



#### **Visible With Polarized Sunglasses**

2,500 nits LCD to give you a clear image, even in direct sunlight. Enables clear visibility even when the viewer is wearing polarized sunglasses.



### **Easy Maintenance**

Telecom-class routing design ensures the cabinet sealing performance. Front door access with lock for both wall mount monitor and kiosk models for easy operation and maintenance.



### **Efficient Heat Dissapation Management**

Professional software for thermal simulation for cooling system design, which cools down the heat generated from every part of the product with high performance, preventing outside air from entering.









www.hisense-b2b.com




# **Hisense**

86" Air Conditioned Display

## Specifications

| General                  |  |
|--------------------------|--|
| Screen Size              | 86"  |
| Screen Active Area (mm)  | 1895 × 1066  |
| Resolution               | UHD (3840 x 2160)  |
| Aspect Ratio             | 16:9   |
| Brightness (nit)         | 2500nits   |
| Contrast Ratio           | 1200:1   |
| Viewing Angle (H/V)      | 178°/178°  |
| Backlight Life Cycle     | 50,000 Hrs   |
| Operation Hours          | 24/7   |
| Response Time            | 8ms  |
| Screen Orientation       | Portrait   |
| Touchscreen (Option)     |  |
| Touch Type               | Touch foil   |
| Touch Point              | 10-points  |
| Response Time            | ≤10ms  |
| System                   |  |
| os                       | Android 7.1  |
| CPU                      | Amlogic Quad-core Cortex-A53,1.5GHz                        |
| GPU                      | Mali-450   |
| DDR                      | 2G DDR4  |
| ROM                      | 16G EMMC (support expanded memory card up to 128G)         |
| Language                 | Chinese/English  |
| Connectivity             |  |
| Input                    | x2 HDMI IN/ x1 USB2.0/ x1 LAN x1 TF<br>card slot/ x1 RS232 |
| Output                   | x1 HDMI OUT/ x1 AV OUT                                     |
| Network connection       |  |
| Wifi or LAN              | Yes  |
| 3G/4G Connection         | Optional   |
| Speaker                  |  |
| Build in Speaker         | Yes  |
| Thermal management       |  |
| Build in air conditioner | Air conditioner  |
| Overheating Dretestion   | v.   |

| Physical                               |   |
|--|---|
| IP Rating                              | IP65                                    |
| Glass                                  | 6.8 mm (AR, Tempered & Laminated Glass) |
| Metal                                  | Galvanized steel with powder coated     |
| Standard Color                         | Black                                   |
| Dimensions                             | 2852(H) x 1310(W) x 300(D) mm           |
| Net Weight                             | 325kg                                   |
| Packing Dimensions                     | 3000(L) x 1510(H) x 580(D) mm           |
| Operation                              |   |
| Working Environment                    | Full outdoor                            |
| Auto Brightness Control                | Light sensor                            |
| Operation Temperature (ambient temp.)  | -40°C to 55°C                           |
| Operation Humidity                     | 5% to 95%                               |
| Power                                  |   |
| Power Supply                           | AC 110 /220V,50/60Hz                    |
| Power Type                             | Built-In Power                          |
| Power Consumption                      | 2500W(Max.)                             |
| Dimensions                             |   |
| <b>86"</b>   2852 x 1310 x 300mm 450kg |   |



HISENSE B2B EUROPE Beechavenue 139, 1119 RB Schiphol-Rijk, Netherlands

Overheating Protection Yes

www.hisense-b2b.com sales@hisense-b2b.com



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660