

APPC 1950T

19" TFT SXGA 4:3 Flush Panel PC with Intel® Celeron® J3455 1.50GHz, Touch Screen, 4GB DDR3L, 4 x USB, 3 x COM





- 4:3 19" SXGA fanless LED panel computer
- Intel[®] Celeron[®] J3455 processors , low consumption CPU
- Flush panel by 5-wire touch screen
- 2 X DDR4 2933MHz memory, up to 64GB (non-ECC)
- Dual Intel[®] GbE LAN ports/DP/Dual USB 3.0 & USB 2.0
- 1 x mini-PCle sockets, 1 x M.2, 1 x RS232/422/485
- DDR3L 4GB/2.5" HDD bracket
- IP66 compliant front panel
- Mounting support: panel/wall/stand/VESA 100mm x 100mm
- DC power input 24VDC

Product Overview

The 19" SXGA fanless panel PC APPC 1950T incorporating an industrial motherboard is intended for versatile industrial applications. APPC 1950T supports 1280 x 1024 (SXGA) resolution and 350-nit brightness. The front panel which adopts flush design and complies with IP65 standard makes it the perfect fit in industrial applications.

APPC 1950T supports LTE, WLAN communications via dual Gigabit Ethernet connectors and mini-PCIe slot . Several options are on storage devices like M.2 and 2.5" SSD. With support for DC power input of 24VDC, APPC 1950T can gain a strong foothold in industrial field and machine devices. In addition, APPC 1950T can hook 2nd display via a DP for dual independent display, with the 3 x COM ports option, will makes it a real intelligent system for various solutions.

Specifications

Panel

- LCD size: 19", 4:3
- Resolution: SXGA 1280 x 1024
- Luminance: 350cd/m²
- Contrast ratio: 1000
- LCD color: 16.7M
- Viewing angle: 80 (U), 80 (D), 85 (L), 85 (R) Backlight: LED

Touch Screen

- 5-wire resistive (flush panel type)
- Light transmission: 81%
- Interface: USB

System

- CPU: onboard Intel[®] Celeron[®] Quad Core processor J3455, 1.50GHz
- BIOS: AMI BIOS
- System memory: 1 x 204-pin DDR3L SO-DIMM socket, 4GB DDR3L (default), support up to 8GB DDR3L-1066/1333, non-ECC and un-buffered Storage device
- 1 x Internal M 2 2242
- 1 x Hard drive bay: optional 1 x 2.5" SATA HDD or 1 x SATA DOM
- Watchdog timer: Watchdog timeout can be programmable by

software from 1 second to 255 seconds and from 1 minute to 255 minutes (tolerance 15% under room temperature 25°C)

- Expansion : 1 x mini-PCIe sockets (support optional Wi-Fi module)
- Front LED indicator to show operating status

Rear I/O

• Ethernet: 2 x RJ45

- Display : 2 x DP1.2
- USB: 2 x USB 2.0, 2 x USB 3.0
- LED indicator : power/HDD/GPIO programmable LED
- Power button
- COM #3: RS232/422/485
- COM #1&2: RS232

Ethernet

- LAN chip: dual Intel® I210-AT Gigabit LAN
- Ethernet interface: 10/100/1000 Base-Tx Ethernet compatible

Mechanical & Environment

- Color: Pantone black\RAL 15 00 front bezel w/ Pantone 400C\RAL
- 090 80 10 metal style membrane and black silver PC box IP protection: IP65 front
- Mounting: panel/wall/stand/VESA 100mm x 100mm

Applied Panel PC & Monitor


Copyright © 2021 NexAloT Co., Ltd. All Rights Reserved.

NEXIOT

N (O 1



www.nexaiot.com



- Power
 - Power input: 24VDC
 - Power adapter: optional AC to DC power adapter (+24V, 60W)
- Vibration
 - IEC 68 2-64 (w/ HDD)
 - 1Grms @ sine, 5~500Hz, 1hr/axis (HDD operating)
 - 2Grms @ sine, 5~500Hz, 1hr/axis (M.2/SSD operating)
- 2.2Grms @ random condition, 5~500Hz, 0.5hr/axis (non operating)
 Shock
 - IEC 68 2-27
 - HDD: 20G @ wall mount, half sine, 11ms
- Temperature
 - Operating temperature: 0°C~50°C
 - Storage temperature: -20°C~75°C
- Operating humidity: 10%~90% relative humidity, non-condensing (limits to be at 90% RH at max 50°C)
- Dimension: 457.64 x 379.24 x 80.25mm
- Weight: 6.2kg

Certifications

- CE approval
- FCC Class A

OS Support Lists

Windows 10 64 bit

Ordering Information

Barebone

- APPC1950T (10IA0195000X0)
 - 19" SXGA LED backlight touch panel PC, Intel® Celeron® Quad Core processor J3455, 1.50GHz, touch screen, 4GB DDR3L, 1 x RS232/422/485

Options

 24V, 60W AC/DC power adapter w/o power cord (P/N: 7400060054X00)

NÈ∿IOT

Applied Panel PC & Monitor

We reserve the right to change specifications and product descriptions at any time without prior notice. Last update: 05/07/2021



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660