



MEG5000 **robustOS**

Modular Edge Gateway for IoT
Control Card + Expansion Card 1+ Expansion Card 2



INTRODUCTION

MEG5000, Robustel Modular Edge Gateway for Internet of Things (IoT), is a most configurable and manageable cellular gateway. The MEG5000 features three scalable cards supporting various interfaces to meet changing demands for industrial IoT applications. It is developed to provide application of calculation, and performs real-time data analysis and intelligent processing at the edge of sensor, which is more effective and secure. With quick-to-deploy and easy-to-customize, the MEG5000 gateway can be tailored to your industrial needs.

MEG5000 is a powerful gateway developed from **RobustOS**, a Robustel self-developed and Linux-based operating system which is designed to be used in Robustel devices. The RobustOS includes basic networking features and protocols providing customers with a very good user experience. Meanwhile, Robustel offers a **Software Development Kit (SDK)** for partners and customers to allow additional customization by using C, Python or Java. It also provides rich **Apps** to meet fragmented IoT market demands.

Robustel is a leading global industrial IoT/M2M hardware and solution provider. Since its establishment in 2010 in Guangzhou, China, Robustel has been focusing on designing and manufacturing industrial cellular routers, gateways, modems, cloud platforms and E2E solutions. In order to support global business in more than 100+ countries and regions, Robustel has set up local offices in Germany, Australia, the Netherlands, the UK, Japan and Hong Kong.

KEY FEATURES

- > Flexible interfaces supporting numerous industrial applications
- > High performance, high reliability and high throughput for data processing
- > Quick customization meeting rapid market promotion
- > Custom development based on integrated Linux environment, and providing edge computing power
- > Embedded mSATA SSD providing data logging
- > Real-time running temperature
- > RobustOS + SDK + App
- > IPsec/OpenVPN/GRE/L2TP/PPTP/DMVPN
- > The option *Backup Mode* supporting cold, warm and load balancing
- > Event/Alarm management with notification (SMS, e-mail, DI/DO, SNMP trap or RobustLink)
- > Robust industrial design (12 to 60V DC, desktop or wall mounting or DIN rail mounting)

PLUG-IN CARDS



Control Card

- 2 x cellular SMA antenna
- 4 x WiFi antenna
- 6 x LED indicator
- 2 x SIM slot
- 1 x Gigabit WAN port/ Gigabit Fiber
- 1 x 3-pin power interface



Expansion Card 1

- 8 x Megabyte LAN Ethernet
- 1 x mSATA SSD



Expansion Card 2

- 1 x RUN LED indicator for card running status
- 1 x GPS antenna
- 2 x RS-232
- 2 x Digital Input
- 2 x Digital Output
- 1 x CAN
- 1 x RS-485

SPECIFICATIONS

Cellular Interface

Number of antennas	2 (MAIN + AUX)
Connector	SMA, female
SIM slot	2 (3 V & 1.8 V)
Standards	GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+/TD-SCDMA/CDMA (CDMA 1X/EVDO)/FDD LTE/TDD LTE

Ethernet Interface

Number of ports	1 x 10/100/1000 Mbps WAN (ETH0) + 8 x 10/100 Mbps LAN (ETH1~ETH8)
Magnet isolation protection	1.5 KV

WiFi Interface

Number of antennas	Support up to 4 antennas (WiFi1 + WiFi2 + WiFi3 + WiFi4)
Connector	RP-SMA, male
Standards	802.11a/b/g/n/ac, supporting AP and Client modes
Frequency bands	2.4 GHz 5 GHz
Security	Open, WPA, WPA2, WEP
Encryption	AES, TKIP, WEP64, WEP128
Data speed	Up to 1300 Mbps

Device Interface

GPS/GLONASS	1 x GPS/GLONASS, SMA, female(Optional)
Serial port	2 x RS-232 + 1 x RS-485 + 1 x CAN
DI/DO	2 x Digital Input + 2 x Digital Output

Others

Reset button	1 x RST
LED indicators	1 x RUN(Main control card),1 x RUN(Expansion Card 2);, 1 x MODEM, 1 x USR, 3 x RSSI 1 x Link indicator + 1 x Speed indicator for each Ethernet port

Software (Basic features of RobustOS)

Network protocols	PPP, PPPoE, TCP, UDP, DHCP, ICMP, NAT, HTTP, HTTPs, DNS, ARP, NTP, SMTP, Telnet, VLAN, SSH2, DDNS, etc
VPN tunnel	IPsec, OpenVPN, GRE
Firewall	DMZ, anti-DoS, Filtering (IP/Domain name/MAC address), Port Mapping, Access Control
Management	Web, CLI, SMS
Serial port	Transparent, TCP Client/Server, UDP, Modbus RTU Gateway

App Center (Available Apps for RobustOS)

Apps	L2TP, PPTP, DMVPN, RobustVPN, VRRP, QoS, SNMP, Language, RobustLink
------	---

**Request on demand. For more Apps please visit www.robustel.com.*

Power Supply and Consumption

Connector	3.5 mm terminal block with lock
Input voltage	12 to 60V DC
Input current	12V@3A, 24V@1.5A

Physical Characteristics

Ingress protection	IP30
Housing & Weight	Metal, 1600 g
Dimensions	157 x 145 x 89 mm
Installations	Desktop, wall mounting and 35 mm DIN rail mounting

Approvals

Environmental	RoHS, WEEE
---------------	------------

ORDERING INFORMATION

Model	MEG5000-4L	MEG5000-NU
Gateway Type	LTE gateway	--
Antenna Number	2	--
Air Interface	GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+/TD-SCDMA/CDMA (CDMA 1X/EVDO)/FDD LTE/TDD LTE	--
Frequency Bands	AU: B1/B2/B3/B4/B5/B7/B8/B28, B40 EU: B1/B3/B7/B8/B20/B28/B31, B38/B40 US: B2/B4/B5/B13/B17/B25, B41 JP: B1/B3/B8/B9/B18/B19/B21/B28, B41 CN: B1/B3, B38/B39/B40/B41	--
4G		
3G	WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+: B1/B2/B5/B6/B8/B9/B19 TD-SCDMA: B34/B39 CDMA (CDMA 1X/EVDO): R0/A BC0/BC1/BC10	--
2G	850/900/1800/1900 MHz	--
Operating Environment	-40 to +65 °C/-10 to +65 °C(with Wifi)/5 to 95% RH	-40 to +65 °C/-10 to +65 °C(with Wifi)/5 to 95% RH

**For more information about 4G frequency bands in different countries, please contact your Robustel sales representative.*



Email: info@robustel.com | Website: www.robustel.com

©2019 Guangzhou Robustel LTD

All rights reserved. Subject to change without notice.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660