



SPC-1209

12.1" Intel® Atom™ SoC Processor E3845 Fanless
Stainless Steel Chassis Touch Panel PC with Full
IP-65

- > Fanless Onboard Intel® Atom Quad-Core E3845 1.91GHz with Integrated Chipset
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1333 SDRAM
- > 1 LAN, 1 COM, 3 USB
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Full System IP65

+ Spec

-System Information-	
Processor	Intel® Atom™ E3845 4-Core 1.91GHz processor/ Intel® Celeron® J1900 2.00GHz processor
System Memory	1 x 204-Pin DDR3L 1333MHz SO-DIMMup to 8 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
SBC	EBM-BYT
Expansion	
Expansion	1 x Mini PCIe Support mSATA 1 x Mini PCIe Supports SIM Card
Storage	
Storage	1 x CompactFlash Type I/II Socket 1 x 2.5" Drive Bay
Panel	
LCD Size	12.1", 4:3
Display Type	XGA
Resolution	1024x768
Pixel pitch	0.240mm(H) x 0.240mm(V)
Luminance	600 cd/m2
Contrast ratio	700
Viewing angle	70 (U), 70 (D), 80 (L), 80 (R)
Response time	16 ms
Backlight	LED
Touch Type	5 Wires resistive
Touch Light Transmission	80 %
Touch Controller	Onboard USB touch (EETI)
I/O	
USB Port	3 x USB 2.0 (2 from rear I/O, 1 through 3-in-1 waterproof external cable)
COM Port	1 x DB9 (Through 3-in-1 Waterproof External Cable)
SATA	1 x SATA II
Wireless Communication	
WLAN	Optional WIFI Module 802.11 ac/a/b/g/n/
Display	
Graphic Chipset	Intel® Valleyview SoC integrated Graphics Supports dual display
Spec. & Resolution	HDMI:Max. resolution 1920x1200@ 60Hz
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	Line-Out
Speaker Output	2 x 5W
Certifications	
Certification Information	CE / FCC Class A
Ethernet	
LAN Chipset	2 x Intel® I211AT Gigabit Ethernet Controller
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	1 x RJ-45 (Through 3-in-1 external waterproof cable)
Power Requirement	
DC Input	+12V ~ +26V
DC Input Connector	Lockable DC Jack



Power Mode	AT/ATX (ATX is default setting)
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (24V @ 2.5A Adapter)
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 80% Relative Humidity, Non-condensing
Dimension (W x L x H)	311 x 272 x 58mm
Weight	4.23Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Construction - Front	Front & Rear Silver Stainless
Construction - Rear	Black
Software Support	
OS Information	Win 7 Win 8 Win 10 Linux
Ordering Information	
Ordering Information	SPC-1209-190-A4R Intel Celeron SoC J1900 2.0GHz D1-CPU/4G DDR3L/32G SSD/1GLAN/2USB/12~26V input/24V Adapter SPC-1209-384-A4R Intel E3845 CPU/4G DDR3L/32G SSD/1GLAN/1COM/3USB/12~26V input/24V Adapter ACC-ARM-D1R VESA STAND, 75mm & 100 mm ACC-ARM-D23R VESA STAND, 75mm & 100 mm ACC-SPC-WIFI-1R Wifi Kits for SPC-15/17/22 802.11b/g/n MPCle/2Antenna/Cable E1702031833R USA Power Cord E1702031000R EU Power Cord E1702031834R Japan Power Cord E1702031830R UK Power Cord E1702031831R Australia Power Cord

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660