

## Aplex Technology ViTAM-916BR Get Quote

VITAM-916BPR(H)	15.6" IP66 / IP69K Stainless Steel Panel P	С	Industrial Panel PC	HMI Controller	Industrial Display Monitor Box F	
	Features / 💭	Dimen	sions / 🔎			
	<ul> <li>15.6" New Generation Stainless Steel Panel PC</li> </ul>					
	<ul> <li>B.5. New Generation stainless Steel Parlet PC</li> <li>Bth Gen. Intel Core i3/15 BGA type Processor</li> <li>True Flat Front Bezel Design and Grade 304 Stainless S (Grade 316 for Option)</li> <li>IP66/IP69K Rated with M12 Connectors</li> <li>Support Resistive Touch, Projected Capacitive Touch</li> <li>Touch on/off Button on the Side Edge for Hygienic Clean</li> <li>Support Ergonomic Versatile Mounting: Yoke Mounting / Space-saving VESA 75 x 75 mm Mounting</li> </ul>	ing				
	Specifications / 🔎	•		• <u>****</u>		
	System	132 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		22		
	Core i5-8365UE(Quad Core, 6 MB cache				• • •	
	Core i3-8145UE(Dual Core, 4 MB cache, System Chipset SoC	, 2.2GHZ)				
	Memory         2 x 260-pin SO-DIMM up to 64GB DDR4           TPM         Firmware TPM (TPM 2.0 compliance)	2400MHz				
	IO Port				UNIT: mm	
	USB         1 x M12 8-pin for USB 2.0 with waterprod           Serial / Parallel         1 x M12 8-pin COM1, RS-232/422/485, d				Tolerance: ±0.5	
	waterproof cover and chain					
	LAN 1 x M12 8-pin for LAN with waterproof co Others 1 x Touch on/off button at the side	ver and chain				
	1 x M12 2 pip for DC power with waterpr	oof cover and chain				
	1 x Power switch on the rear	Power				
	2 x optional blank M12 connector with wa for selecting two from the following option 2 x USB 2.0		DC 9~36V Imption ViTAM-916BP: 39W			
	Option 1 x USB 3.2 Gen.1 1 x LAN	Mechanical	004.01.11			
	1 x COM 1 x CAN	Construction	304 Stainless steel chassi chassis(optional)	s(default), 316 Stainless steel		
	Storage Space	Mounting	VESA mount 75 x 75, Yok	e mount for optional		
	HDD 1 x 2.5" SATA3 HDD (for option)	IP Rating Dimensions	Total IP66/IP69K 440 x 290 x 55 mm			
	M.2 1 x B-key 2280 (SATA as default, PCI-e s		7 kg			
	Expansion	Environmen	tal			
	1 x Full size mSATA/mPCle (mSATA as defa Expansion slot 1 x NANO-SIM					
	1 x M.2 E-key 2230 (PCle+USB) for optional	al WIFI/BT module Storage Tem Humidity	perature -30~70°C 10 to 95% @ 40°C, non-ce	ondensing		
	RFID module RFID module design on the front side (for	r option) Certificate	CE/FCC Class A	ondensing		
		Brightness Optional	ystem Support			
		15.6 IFI-LCD	IoT ENT LTSB, Windows 11			
	Max. Color 16.7M / 16.2M	16.7M / 16.2M				
	Luminance (cd/m²)         400/450           170(H)/160(V)         170(H)/160(V)	1000	15.6" WXGA IP66/IP69K stainless steel	I panel pc, Intel 8th Gen. Core i Processor,		
	View Angle (H/V) 170(H)/170(V)	170(H)/170(V)	2 x SO-DIMM DDR4 slots, 128GB TLC DC power input with Adapter	SSD, projected capacitive touch, 9~36V		
	Contrast 500:1 / 800:1 Backlight Lifetime 50,000 hrs	800:1 50,000 hrs	15.6" WXGA IP66/IP69K stainless steel	I panel pc, Intel 8th Gen. Core i Processor,		
	Backlight Lifetime 50,000 hrs	50,000 hrs ViTAM-916B	R 2 x SO-DIMM DDR4 slots, 128GB TLC DC power input with Adapter	SSD, 5 wire resistive touch window, 9~36V		
	Type Resistive Touch (for BR model) Projected Capacitive (for BP model)	VITAM-916B	15.6" WXGA IP66/IP69K stainless steel PH 2 x SO-DIMM DDR4 slots, 128GB TLC DC power input with Adapter, 1000 nits	l panel pc, Intel 8th Gen. Core i Processor, SSD, projected capacitive touch, 9~36V		
	Interface USB		15.6" WXGA IP66/IP69K stainless steel	panel pc, Intel 8th Gen. Core i Processor,		
	Light Transmission(%) Resistive Touch : 80% Projected Capacitive : 90%	VITAM-916B	RH 2 x SO-DIMM DDR4 slots, 128GB TLC DC power input with Adapter, 1000 nits	SSD, 5 wire resistive touch window, 9~36V		
	,					



## **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

## US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

## **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660