

M101PR, 10.1-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

M101PR is a rugged tablet PC with robust set of features designed to operate in heavy duty environments while providing high tech solutions that increase productivity, improve safety, and reduce operational costs. The processing power comes from Intel's Pentium N4200 Apollo Lake processor paired with genuine Intel graphics for high performance. The tablet features a brilliant, in-plane switching with direct optical bonding, 4-wire resistive touchscreen, which is outdoor viewable and offers 1920 x 1200 pixel resolution. Weighing at just 2.65 pounds (approx. 1200 grams) the M101PR delivers lightweight mobility in a rugged tablet.









Highlights

- Intel[®] Pentium[®] N4200 Apollo Lake Processor
- 10.1" 1920 x 1200 IPS LED Panel with direct optical bonding
- Optional 1D/2D Barcode Reader and HF RFID for data collection
- Hot-swappable battery design with optional high capacity battery pack
- IP65 waterproof and dustproof
- · Rated for extreme temperature use
- Optional Expansion port for USB / RS232 connection
- 4-wire resistive touch

^{*}Accessories and Integrated Options may vary depending on your configuration. Visit Winmate website for more accessories and details.



^{*}Please consult your reseller or Winmate representative before purchasing.



M101PR, 10.1-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

Display Specification

10.1-inch IPS display with LED Backlight 1920 x 1200 WUXGA

Resolution

Panel Brightness

With direct optical bonding for sunlight readable Touch 4-wire resistive

Contrast Ratio Viewing Angle 85/85/85/85

Technology · Ambient light sensor, e-compass, gyro, acceleration

sensors

Intel HD Graphics (built-in CPU) video controller

System Specification

Intel Pentium N4200 Processor

1.10 GHz, up to 2.50 GHz with turbo boost technology

4GB SODIMM DDR3L-1600 (up to 8GB) System Memory

128GB solid state drive (SSD) Storage

Optional up to 512GB, up to 128GB additional storage

with microSDXC card slot

Operating System Windows 10 IoT Enterprise (64 bit)

Wireless Communication

802.11 a/b/g/n/ac Bluetooth Bluetooth 5.0 GNSS GPS, GLONASS WWAN Optional 4G LTE

Interface

Docking Connector 1 x 19-pin docking connector HDMI 1 x Micro HDMI

USB 1 x USB3.0 (Type A), 1 x USB3.0 (Type C) 2

Power Input 1 x Power Jack Micro SD 1 x Micro SD Slot

Audio Connector 1 x Audio Combo connector (Mic in or Line Out)

1 x Expansion Connector for USB 2.0 /

Full RS232 (Optional)

Keyboard and Input

Expansion Port

Touch · Single touch.

supports finger, stylus, glove touch input

On-screen QWERTY keyboard Button 1 x power, 1 x Home, 2 x volume key,

2 x function key (Programmable

function key configured by Hottab Utility)

Power, Battery, HDD, RF

Audio

LED Indicators

Microphone Built-in dual Digital Mic with Noise Cancellation

Speaker

Cameras

2MP webcam Web Camera

8MP rear camera with autofocus and LED light

Data Capture

Barcode Optional 1D/2D Barcode Reader Optional HF RFID reader 13.56 MHz HF RFID

Security Function

• Password security for user and hard disk lock

• Trusted Platform Module (TPM) 2.0

Kensington Lock

Mobile Device Mamt. SOTI Mobicontrol compatible

Standards and Certification

CE, FCC

Mechanical and Environment

 $271.8 \times 197.2 \times 19 \text{ mm} (10.7 \times 7.76 \times 0.75 \text{ inches})^{-1} (1.2 \text{ kg} (2.65 \text{ lbs}) \text{ with standard battery,}$ Dimension (W x L x H)

1.4 kg (3.1 lbs) with optional high capacity battery

MIL-STD-810G Method 516.6, 4 ft to concrete

-20°C to 60°C (AC mode), -10°C to 50°C (Battery mode) -30°C to 70°C (-22°F to 158°F) Operating Temperature Storage Temperature Humidity 10% to 90% RH, non-condensing IP Proof IP65 certified, Dustproof and waterproof Shock MIL-STD-810G Method 516.6 Procedure I Vibration MIL-STD-810G Method 514.6 Procedure I

Power Management

Power Input 12-19V DC

Battery 7.4V, typ. 5140 mAh Li-Polymer Battery (2S1P)

7.4V, typ. 10280 mAh Li-Polymer Battery (2S2P, optional)

Battery Operating Time Std. Battery: 8 hours

High Capacity Battery: 16 hours

100-240V, 50-60Hz / 19V DC

Accessories


Standard Accessories

922D065W19V1
9B0000000415
98K000A0003T

Optional Accessories

8DT00A0000E
98K000A0003L
8KT00A0000F
98K000A0003U
8K000A0003S
8K000A0003J
8K000A0004J
8KT00A0001H
8K000A0003Q
B00000003J
491191190K1
226065W19V0
AN00000000I
AN0000000L
AN0000000J

Drawing





Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in

Do not expose bare skin to this product when handling this unit in extreme hot or

- 1. Total usable memory will be less depending upon actual system configuration.
- 2. The USB Type-C connector follows USB 3.0 standard, which does not support
- Alternate Mode (ALT) or USB Power Delivery (USB-PD).
- TPM 2.0 available upon request SOTI is available upon request.
- 5. Length measurements do not include protrusions. Weight varies with options and active pen.
- 6. The drop test with high-capacity battery must come with hand strap.
- 7. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- 8. Accessories and Integrated Options may vary depending on your configuration.
- 9. This is a simplified drawing and some components are not marked in detail





Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660