



EMX-C246P

Intel® 8th Generation Core™ Processor Mini ITX Motherboard With Intel® C246 Chipset

- > Intel® 8th Generation Core™ Processor (Max. TDP at 95W)
- > Intel® C246 Chipset
- > 2 x 260-pin DDR4 2400/2666MHz DIMM socket, supports up to 32GB (ECC memory supported by CPU)
- > 1 x Intel® I219LM Gigabit Ethernet PHY
- > 3 x Intel® I211AT PCI-e Gigabit Ethernet
- > 2 x HDMI, VGA, Dual-CH LDVS co-lay eDP(By BOM option)
- > 4 x SATA III
- > 1 x M.2 (2242/2260/2280) M-Key, support Intel RST, PCI-e x4 mode SSD
- > 1 x M.2 (2230) E-Key, support WiFi module
- > 1 x PCI-e x 16
- > 6 x USB3.1 Gen1, 2 x USB3.0 at I/O, 1 x 2 x 10pin for 2 x USB3.0, 3 x USB2.0 by pin header
- > 4 x RS232 2 x RS232/422/485

Spec

System	
Processor	Intel® LGA1151 Socket Supports 8th Generation Core™ i7/ i5/ i3 & / Intel® Xeon®Process(Workstation) / Pentium®/Celeron® Processors (Max. TDP at 95W)
System Chipset	Intel® C246 Chipset
System Memory	2 x 260-pin DDR4 2400/2666MHz DIMM supports up to 32GB (ECC memory supported by CPU)
I/O Chip	Nuvoton® NCT6106D
BIOS	AMI uEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 5~255 seconds/5~255 minutes
H/W Status Monitor	CPU temperature monitoring, Voltages monitoring, CPU fan speed control
TPM	Onboard Infineon SLB9665 supports TPM 2.0
Board	Mini ITX Board
Expansion	
Expansion	1 x PCI-e x 16 1 x M.2 (2242/2260/2280) M-Key, supports Intel RST, PCI-e x4 mode SSD 1 x M.2 (2230) E-Key, supports WiFi module
I/O	
USB	2 x USB 3.0 6 x USB 3.1 Gen1
SATA	4 x SATA III
COM Port	4 x RS232 2 x RS232/422/485
DIO	1 x 16-bit GPIO
Display	
Chipset	Intel® 8th Generation CPU integrated
Resolution	VGA: 2048 x 1536 @ 60 Hz HDMI: 3840 x 2160 @ 30 Hz, 2560 x 1600@ 30 Hz Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS)- By BOM option
LVDS	Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS)- By BOM option
Multiple Display	Triple Display
Audio	
Chipset	Realtek ALC662
Audio Amplifier	3W Amplifier
Ethernet	
Chipset	1 x Intel® I219LM Gigabit Ethernet PHY 3 x Intel® I211AT PCI-e Gigabit Ethernet
LAN Port	4 x RJ-45
Mechanical & Environmental	
Power Requirement	+12V/+5V/5VSB/+3.3V/-12V
ACPI	Single power ATX Support S0, S3, S4, S5
Power Type	AT/ATX
Operating Temp	0~60°C (32~140°F)
Storage Temp	-40 ~ 75°C
Operating Humidity	0%~90% relative humidity, non-condensing
Dimension (L x W)	6.7" x 6.7" (170mm x 170mm)
Weight	0.4 kg

Ordering

EMX-C246P-A1R
Intel® 8th Generation Core™ Processor Mini ITX Motherboard With Intel® C246 Chipset

www.avalue.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660