

M116K, 11.6-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

The M116 platform is a next-generation Windows rugged tablet series designed to boost efficiency in a mobile, versatile form factor. The large 11.6-inch sunlight readable full HD display allows for a premium viewing experience no matter where work takes place. The M116K allows for powerful performance with the Intel Core i5 processor for all day use with a hot-swappable battery design. Multiple wireless connectivity options and data capture modules allows users to complete their tasks reliably; from warehouses, to vehicle mounted, to field service external use. All these tools suited for productivity encased in an IP65 water and dust proof rugged housing with MIL-STD 810G specs ensures that the M116K is the ultimate rugged tablet designed with mobile productivity in mind.



Highlights

- Intel[®] Core[™] i5-7200U Kaby Lake 2.5GHz (Turbo up to 3.1GHz)
 Optional Intel[®] Core[™] i5-7300U Kaby Lake 2.60GHz (Turbo up to 3.5GHz)
- 11.6" 1920 x 1080 LED panel with direct optical bonding
- IP65 water and dust proof with MIL-STD-810G rugged housing
- Optional Integrated 1D/2D Barcode Reader and HF RFID for data collection
- Removable battery with hot-swap function for all day productivity
- 802.11ac WiFi, BT 5.0, 4G LTE, GPS Wireless Connectivity
- Optional GigaLAN Port





M116K, 11.6-inch Rugged Tablet PC

A Rugged Tablet that Can Survive Any Environment and Get Real Work Done

Display Specification		Power Management	
Size Resolution Contrast Ratio Panel Brightness Viewing Angle Touch	11.6-inch display with LED Backlight 1920 x 1080 Full HD 1000:1 850 nits with direct optical bonding for sunlight readabili 89/88/89/89 Projected capacitive multi-touch	AC Adapter 10 Battery Ho	W DC 0-240V, 50-60Hz (19V DC) ot-swappable 7.7V typ. 5900 mAh Li-Polymer Battery (2S' ptional 7.4V typ. 10280 mAh Li-Polymer Battery (2S2P) d. Battery: 8 hours ⁶
Technology	 Anti-glare technology (Default) Automatic screen rotation 	Mechanical	
System Specification		· · · · ·	00.67 x 201.97 x 22.5 mm ⁷ 4 kg
CPU	Intel® Core™ i5-7200U Kaby Lake 2.5GHz	C C	- Ng
System Memory	(Turbo up to 3.1GHz) Optional Intel [®] Core™ i5-7300U Kaby Lake 2.60GHz (Turbo up to 3.5GHz) 4GB DDR4 SDRAM 1 (up to 16GB)	Storage Temperature -30	0°C to 60°C (AC mode), -10°C to 50°C (Battery mode) 0°C to 70°C
Graphics	128GB SSD (options up to 512GB) Additional storage available with micro SDXC card slot Intel® HD Graphics 620	Shock MI Vibration MI	1% to 90% RH, non-condensing IL-STD-810G Method 516.6 Procedure I IL-STD-810G Method 514.6 Procedure I IL-STD-810G Method 516.6, 4 ft to concrete
Operating System Sensors	Windows 10 IoT Enterprise (64 bit) Light sensor/ g-sensor / Gyro / E-compass		65 certified, dustproof and waterproof
Wireless Commu		Accessories	
WLAN	802.11 a/b/g/n/ac WiFi	Standard Accessories	
Bluetooth GNSS WWAN	Bluetooth 5.0 GPS, GLONASS Optional 4G LTE	Adapter and Power Cord Capacitive Stylus Standard Battery	922D065W19V1 9B0000000415 98K000A000D6
Interface		Optional Accessories	
Docking Connector HDMI USB Power Input Micro SD Audio LAN Expansion Port Micro SIM mini PCle	1 x 19-pin docking connector 1 x micro HDMI 1 x USB 3.0 (Type A), 1 x USB 3.0 (Type C) ² 1 x Power Jack 1 x Micro SDXC slot 1 x Audio combo connector (Mic in or Line Out) 1 x RJ45-10/100/1000 GigaLAN port (Optional) 1 x Expansion connector for USB 2.0/ Full RS232 (Option 1 x Micro SIM card slot 1 x Mini PCIe for WWAN Module	Desk Dock Vehicle Dock Vehicle Charger Battery Charger Smart Card Reader UHF RFID Reader High Capacity Battery al) Hand Strap VESA Mount Kit Shoulder Strap Carry Bag	98DT00A0001G 98DT00A0001H 9226065W19V0 98K000A000DK 98K000A0003U 98K000A0004J 98K000A0000C 98K000A000DC 98K000A000DD 98K000A000DJ
Input		Micro HDMI Cable	9491191190K7
Physical Buttons Touch	1 x Power; 3 x function keys 10-point multi-touch, supports Rain / Glove / Stylus Modes	USB-C to Ethernet Adapter USB-C to RS232 Adapter USB-C to USB-A Hub	9AN000000001 9AN000000000L 9AN00000000J
Status Indicator	S	Drawing ⁸	
LED Indicators	Power, Battery, HDD, RF		UNIT:mm
Audio		300.67	
Microphone Speaker	Built-in dual digital mic with noise cancellation 2 x 1 watt front-facing speakers		
Cameras			
Front Camera Rear Camera	2MP front camera 8MP rear camera with autofocus and LED light	Į L	
Data Capture			*Expansion port is an optional function.
Integrated Add-on Module ³	Optional 1D/2D Barcode Reader Optional HF RFID reader 13.56 MHz Optional add-on UHF RFID Reader or Smart Card Reade		Battery Pack to Excessive Heat, or Extreme Heat (Near aht for example)
			e skin to this product when handling this unit in extreme
Security Function		1. Total usable memory will be	less depending upon actual system configuration.
Security Mobile Device Manag	Trusted Platform Module (TPM) 2.0 ⁴ Kensington Lock gement SOTI Mobicontrol compatible ⁵	Alternate Mode (ALT) or USB	ollows USB 3.0 standard, which does not support 3 Power Delivery (USB-PD). expansion port option to be usable.
		4. TPM 2.0 available upon reque	est.
Standards and C	Certification CE, FCC	when an external device is at	orightness. Varies depending on the usage conditions, or



8. This is a simplified drawing and some components are not marked in detail.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28 Business Registration Number: 07699660