

ViPAC-917P/R/G(H)

17" Intel 6th/7th Core i3/i5/i7 Panel PC

Industrial Panel PC

HMI Controller

Industrial Display Monitor

Box PC




Features

- 17" TFT LCD Panel PC
- Intel 6th/7th Core i3/i5/i7 Socket type Processor
- Modular concept and with Fan Design
- Support PCT/RTW/AR Glass
- Front Bezel IP66
- Option WiFi/BT/Speaker
- Support 2 x Expansion slot
- DC 9~36V Power input, option AC power input

Specifications

System		
CPU	Intel 6th/7th Gen Core i3/i5/i7 processor	
System Chipset	Intel H170	
Memory	2 x 260-pin SO-DIMM up to 32GB DDR4 2133 MHz SDRAM	
IO Port		
Rear side I/O port	4 x USB3.0 type A	
	2 x RJ45 GbE LAN	
	1 x DB9 RS-232/422/485 default RS-232	
	1 x DB9 RS-232	
	1 x DB9 RS-422/485 default RS-485	
	1 x DB15 VGA	
	1 x HDMI with Cover	
	1 x Line-out/Mic-in	
	1 x 2pin Terminal block for external power switch	
	2 x LED indication for HDD/System	
	1 x System LED indication at front	
Option I/O	1 x 3pin TB Power connector	
	1 x Power Switch on/off	
	2 x 2W speaker at rear side	
	4 x USB 2.0 Type A via TB-546	
	2 x DB9 COM port	
1 x 8-bit GPIO (3 in/out/VCC/GND)		
Storage Space		
HDD	2 x 2.5" SATA HDD space, support RAID 0, 1, 5 (Easily Accessible storage design)	
Expansion		
Expansion Slot	1 x Full-size Mini PCIe on board (PCIe/USB/SATA, SATA by default)	
	1 x Half-size Mini PCIe on board (PCIe/USB, PCIe by default)	
	1 x SIM slot for option (Option wifi/BT/4G and antenna at rear side)	
	1 x PCIe x1 and 1 x PCIe x16 slot via TB-560E11E161 (default)	
Display	Standard	High Brightness Optional
Display Type	17" TFT-LCD	17" TFT-LCD
Max. Resolution	1280 x 1024	1280 x 1024
Max. Color	16.7M	16.7M
Luminance (cd/m ²)	350	1000
View Angle	160(H) / 140(V)	170(H) / 160(V)
Contrast	800:1	1000:1
Backlight Lifetime	50,000 hrs	50,000 hrs
Option	Auto Dimming	Auto Dimming
Touch Screen	Resistive Touch	Projected Capacitive Touch
Interface	USB	USB
Light Transmission(%)	Over 80%	Over 90%
Power		
Power Input	DC 9~36V Power input, option AC power input	

Dimensions



Mechanical	
Construction	Aluminum die-casting front bezel and steel chssis Stainless front bezel (option)
Mounting	Panel Mount
IP Rating	Front Panel IP66
Dimensions	439 x 348 x 95 mm
Net Weight	7.6 kg
Environmental	
Operating Temperature	0~50°C
Storage Temperature	-30~70°C
Humidity	10 to 95% @ 40°C, non- condensing
Certificate	CE / FCC Class A
Operating System Support	
Windows embedded 7	
Windows embedded 8.1	
Windows 10 IoT Enterprise	
Ordering Information	
ViPAC-917R	17" SXGA Intel Core 6th Core i processor with H170 chipset, with Fan design panel PC, 2 x 260pin DDR4 SO-DIMM slot, 2 x 2.5" HDD/SSD space, 1 x PCIe x1 and 1 x PCIe x16 slot, resistive touch window, 9~36VDC power input with adaptor, Alu.die-casting front bezel.
ViPAC-917P	17" SXGA Intel Core 6th Core i processor with H170 chipset, with Fan design panel PC, 2 x 260pin DDR4 SO-DIMM slot, 2 x 2.5" HDD/SSD space, 1 x PCIe x1 and 1 x PCIe x16 slot, projected capacitive touch, 9~36VDC power input with adaptor, Alu.die-casting front bezel.

V 1.4

Industrial Panel PC

All specifications and photos are subject to change without notice.

All specifications and photos are subject to change without notice.

Industrial Panel PC

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660