

# **entaira**

## LNX-C500 Series

Compact 5-Port Industrial Unmanged Ethernet Switches, w/5\*10/100Tx, 12~48VDC Power Input








#### **Features**


- ► Compact Industrial Grade Design
- ► Supports 5-Port 10/100Tx RJ45 Fast Ethernet
- ► Supports Auto MDI/MDI-X Function
- ► Store-and-Forward Switching Architecture
- ► Surge Protection: 2,000 VDC Support
- ► ESD Protection: 6,000 VDC Support
- ► Redundant Power Input Design: 12~48VDC
- Power Polarity Reserve Protect
- Overload Current Protection
- ▶ IP30 Rugged Metal Case Design
- ► DIN-Rail and Wall Mount Support
- Operating Temperature Range: STD:-10° to 70°C, EOT:-40° to 75°C
- 5-Year Warranty


#### INTRODUCTION



The LNX-C500 series supports high EFT & ESD protection through the redundant power inputs that support reverse polarity and overload current protection. This product series supports DIN-rail as well as wall mountable orientations and provides operating temperature range models in STD: -10°C to 70°C and EOT: -40°C to 75°C. This is an industrial grade unit applicable for networking applications in factory automation, ITS, power/utility, water wastewater treatment plants, or any application that needs a compact solution.

#### **DIMENSIONS**





26.00

www.antaira.com

Toll-Free:1 (844) 268-2472

T: 1 (714) 671-9000

F: 1 (714) 671-9944



# **a**ntaira<sup>®</sup>

# SPECIFICATIONS



Technology		N
Standards	IEEE 802.3 10Tx Ethernet IEEE 802.3u 100Tx Fast Ethernet	L
Switch Properties	3	_[
Protocol	CSMA/CD	_\
Data Process	Store and forward	
Transfer Rate	14,880pps for 10Base-T Ethernet port 148,8800pps for 100Base-T Fast Ethernet port	F
Packet Buffer	448 Kbits	F
MAC Table	8K	F
Flow Control	IEEE 802.3x for full duplex mode, back pressure for half duplex mode	E
Port Interface		_
Ethernet RJ45 Port	5*10/100BaseTx auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	- 5
Protection		
Overload Current	Present	E
Power Reverse Polarity	Present (the unit will not be on, if power reverse)	E
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable; 100Base-TX: 2-pair UTP/STP Cat. 5 cable.	5

<b>Mechanical Characteris</b>	stics
LED Indicator	Per Unit: Power 1 & 2
Housing	Metal IP30 rated
Dimensions	26 x 95 x 75 mm
Weight	Unit: 1.0 lbs; Shipping: 1.5 lbs
Mounting	DIN-Rail; Wall-mount (optional)
Power Requirement	
Input Voltage	12~48VDC Redundant Input
Power Connection	1 removable 4-contact terminal block
Power Consumption	1.2 Watts
Environmental Limits	
Operating Temperature	STD: -10° to 70° C EOT: -40° to 75° C
Storage Temperature	-40°C ~ 85°C
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Class A
EMS	EN61000-4-2,3,4,5,6,8
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE, UL 61010-1, UL 61010-2-201
Compliance	NEMA TS1/TS2
Warranty	5 Years

### **ORDERING INFO**



LNX-C500	Compact 5-Port Industrial Ethernet Switch with 5*10/100Tx	
LNX-C500-T	Compact 5-Port Industrial Ethernet Switch with 5*10/100Tx; EOT -40° to 75°C	
Optional Accessories		
DR-15-12	15W Industrial DIN-Rail Power Supply, 12VDC	
MDR-20-24	20W Industrial DIN-Rail Power Supply, 24VDC	
MDR-40-48	40W Industrial DIN-Rail Power Supply, 48VDC	
MDR-60-48	60W Industrial DIN-Rail Power Supply, 48VDC	
DR-75-48	75W Industrial DIN-Rail Power Supply, 48VDC	



# **Assured Systems**

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

#### **EMEA**

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660