

# UTC-315x

## 15.6" Ubiquitous Touch Computer UTC-315D with Intel® BayTrail J1900

Preliminary



### Features

- Low Power & Fanless design
- Built in Intel BayTrail J1900 (UTC-315D)
- Providing Natural Viewing Experience with 16:9 15.6" Display
- Front panel complies with IP65 protection standard
- Landscape & Portrait screen mode support by different applications
- VESA 75 mm standard mounting holes for varied mounting demands
- Attachable frame design , flexible for panel mount applications




### Introduction

UTC-315x is the multi-purpose all-in-one computing system which equipped with wide format, touch based LCD panel. It is easy to integrate key peripherals and display systems for diversified self-service and interactive signage deploy in different application areas. With the removable frame , the system also could fulfill industries or control system applications with panel mounting design. UTC series touch panel computers are the best investments to enhance user satisfaction, further brand equity, and maximize business profits.

### Specifications

Processor System	CPU	Intel® BayTrail J1900	
	Basic Frequency	2.0 GHz (Quad-Core)	
	L2 Cache	2MB	
	Memory	1 x SO-DIMM DDR3L 1333 MHz up to 8 GB	
	HDD	1 x 2.5 internal SATA HDD bay	
	Network	2 x Gigabit Ethernet ports (RJ-45)	
	I/O ports	1 x RS-232 COM , 1 x RS-232 / 422 / 485	
		5 x USB 2.0 / 1 x USB 3.0	
		2 x Gigabit Ethernet (RJ-45)	
		1 x HDMI	
	Audio Line-out x 1, Mic-in x 1		
	RJ-11 (option)		
	Stereo Speaker	1W x 2	
	BUS expansion	Full-size MiniPCIe/mSATA	
	Mounting	VESA 75 x 75	
	Dimension(WxHxD)	402 x 260 x 39.7 mm	
	Weight	< 4 kg (8.8 lb)	
OS support	Windows Embedded Standard 7		
	Windows Embedded Standard 8		
	Embedded Linux 3.0		
Environmental Specifications	Operating Temperature	0 ~ 40° C (32 ~ 104° F)	
	Relative Humidity	10 ~ 95% @ 40° C non-condensing	
	Vibration	0.5G	
	Shock	10 G peak acceleration (11 msec. duration)	
	EMC/ Safety	CE, FCC, UL, CCC CB, BSMI	
	Front Panel Protection	IP65/ NEMA4 Compliant	
Power Supply	Input Rating	12 V/7 A (84W ITE Adapter)	
	Power consumption	Typical 32W Max. 70W	
LCD Display	Size	15.6" TFT LCD	
	Max Resolution	1366 x 768	
	Max Color	262K	
	Pixel Pitch (um)	252 (H) x 252 (V)	
	Brightness (cd/m2)	200 (Typical)	
	View Angle	90°/60°	
Touch Screen	Type	Analog Resistive 5-wires (Res. Flat Glass) / Projected Capacitive Touch Panel (Pcap. Flat Glass)	
	Light Transmission	Res. Touch : 80% ± 5% / P-Cap Touch : 90% ± 2%	
	Controller	COM interface / USB interface	

**UTC-315D**



**Ordering Information**

Part No.	Description
UTC-315D-RE	15.6" Intel® Celeron J1900 Based fanless UTC with Resi.T/S, 4 GB RAM
UTC-315D-PE	15.6" Intel® Celeron J1900 Based fanless UTC with PCT.T/S, 4 GB RAM


**Peripherals for UTC-300 series**

Part No.	Description
UTC-300P-C01E	5M Camera Module for UTC-3XX
UTC-300P-M01E	Magnet Strip Reader for UTC-3XX
UTC-300P-R01E	RFID Reader for UTC-3XX
UTC-300P-S01E	Smart Card Reader for UTC-3XX
UTC-300P-B01E	1D Barcode Reader for UTC-3XX
UTC-300P-B02E	2D Barcode Reader for UTC-3XX

**Installation Accessory**

Part No.	Description
UTC-300P-D01E	Desk Stand for UTC-3xx
UTC-WALL-MOUNT1E	Wall Mount kit for UTC-515/520
UTC-WALL-MOUNT3E	Wall Mount Kit for UTC-515/520
UTC-T01-STANDE	Triangle shape floor stand
UTC-H01-STANDE	H-shaped floor stand

**Fully- Integrated I/O**



- A. Com1
- B. Com2
- C. Line-out
- D. Mic in
- E. LAN ports x 2
- F. HDMI
- G. USB 2.0 x 5 / USB 3.0 x 1
- H. Power button
- I. DC input (12 V<sub>DC</sub>)

## Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

### US

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +1 347 719 4508  
Support: +1 347 719 4508

1309 Coffeen Ave  
Ste 1200  
Sheridan  
WY 82801  
USA

### EMEA

[sales@assured-systems.com](mailto:sales@assured-systems.com)

Sales: +44 (0)1785 879 050  
Support: +44 (0)1785 879 050

Unit A5 Douglas Park  
Stone Business Park  
Stone  
ST15 0YJ  
United Kingdom

VAT Number: 120 9546 28  
Business Registration Number: 07699660