

LMP-0501-XX-24-V2 Series

5-Port Industrial PoE+ Managed Ethernet Switches
w/4*10/100Tx (30W/Port) and 1*100Fx Multi-Mode/Single
Mode, 12~55VDC Power Input; Version 2 Hardware



Features


- ▶ Supports 4*10/100Tx IEEE 802.3at/af Compliant with 30W/Port and 1*100Fx Fiber Port
- ▶ Network Redundancy: RSTP/MSTP and TG.8032 ERPS (Recovery Time <50ms)
- ▶ Supports IGMP v1/v2/v3, up to 1024 Groups
- ▶ Supports QoS (IEEE802.1p) and CoS/ToS
- ▶ Supports IEEE802.1Q VLAN, SNMP v1/v2c/v3
- ▶ PoE Ping Alarm Function for PoE Ports Power Recycle
- ▶ Redundant Power Input: 12~55VDC (Voltage Booster)
- ▶ Reverse Polarity Protection
- ▶ IP30 Protection
- ▶ DIN-Rail or Wall Mountable
- ▶ Operating Temperature Range
 - STD: -10° to 70°C, EOT: -40° to 75°C
- ▶ 5-Year Warranty

INTRODUCTION

Antaira Technologies' LMP-0501-XX-24-V2 series is a 5-port industrial PoE+ managed Ethernet switch embedded with 4*10/100Tx Ethernet ports that support IEEE802.3at/af for a maximum of 30W/port and 1*100Fx fiber connection. The LMP-0501-XX-24-V2 is a fully manageable Layer 2 Ethernet switch that is pre-loaded with a user-friendly web management console design. It supports the ring network redundancy function using the market's open standard ITU-T G.8032 Ethernet Ring Protection Switch (ERPS) protocol that has a <50ms network recovery time. The advanced network filtering and security functions, such as IGMP, VLAN, QoS, SNMP, RMON, Modbus TCP, and 802.1X/HTTPS/SSH/SSL increase determinism and improve network management for remote SCADA systems or control networks.

The LMP-0501-XX-24-V2 series is IP30 rated and DIN-rail mountable. There are also two wide operating temperature models for either a standard temperature range (STD: -10°C to 70°C) or an extended temperature range (EOT: -40°C to 75°C). It also provides high EFT and ESD protection for industrial networking applications, such as power/utility, water wastewater, oil/gas/mining, factory automation, security surveillance, ITS and any other outdoor or harsh environment.

DIMENSIONS



SPECIFICATIONS

Technology	
L2 Switching	Port/MAC/Protocol/IP Subnet-based VLAN, VLAN trunking, GARP/GVRP, Loop Guard, Link Aggregation static/LACP, BPDU guard, Error disable recovery, IGMPv2/v3 snooping, MLD snooping, IGMP filtering, IPMC throttling / filtering leave proxy, DHCP snooping, ARP, MEP, G.8032 v1/v2, NAT, DHCP per port, SMTP, Quick ERPS, TLS
L3 Switching	DHCP option82, static routes
QoS	802.1p Queueing, Input priority mapping, Storm control for Unicast/Multicast/Broadcast, Port/Queue/ACL policer, Port egress shaper, Queue egress shaper, DiffServ (DSCP), Tag remarking, Scheduler mode
Power Saving	ActiPHY, PerfectReach, IEEE 802.3az EEE power management
Network Redundancy	STP/RSTP/MSTP, port trunk with LACP, ERPS v1/v2 (<50ms)
Configuration System / Diagnostics	Http, Https, Telnet, SSH, CLI, TFTP, SNMP v3
Switch Properties	Dual Image Protection, PING, PING6
Switch Architecture	Back-Plane (Switching Fabric): 1Gbps
Priority Queues	8
Processing Type	Store and Forward
Flow Control	IEEE 802.3x flow control, back pressure flow control
Transfer Rate	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port
Memory Buffer	4Mbits
Jumbo Frame	9.6Kbytes
MAC Table Size	8K
VLAN Group	4095
IGMP Group	1024
Port Interface	
Ethernet Port	4*10/100Base-TX, auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Fiber Port	1*100Base-FX SC/ST type connector
RS232 Serial Console	1*RS232 in RJ45
Configuration Backup	1*USB 2.0
LED Indicators	System: Power 1, Power 2, Master, Ring, Fault Ethernet Ports: Speed/Link/Active Fixed Fiber: Link/Active

Protection	
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)
Mechanical Characteristics	
Housing	Metal, IP30 protection
Dimensions	54 x 142 x 99 mm (W x H x D)
Weight	Unit: 1.9 lbs Shipping: 2.7 lbs
Mounting	DIN-Rail, Wall-mount (Optional)
Power Requirement	
Input Voltage	12~55VDC Redundant Input
Power Connection	1 removable 6-contact terminal block
Relay Contact	24VDC, 1A resistive
Overload Current Protection	Present
Reverse Polarity Protection	Present
PoE Pin Assignment	V+, V+, V-, V-, for pin 1, 2, 3, 6 (Endspan, Mode A)
PoE Power Budget	90W@12VDC 120W@24-55VDC
System Power Consumption	7.5W
Environmental Limits	
Operating Temperature	STD: -10°C to 70°C EOT: -40°C to 75°C
Storage Temperature	-40°C to 85°C
Ambient Relative Humidity	5% to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
EMS	CE EN55035/EN61000-6-2, IEC61000-4-2,3,4,5,6,8
Free Fall / Shock / Vibration	IEC60068-2-32 / IEC60068-2-27 / IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE
Warranty	5 Years

ORDERING INFO

LMP-0501-M-24-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Multi-Mode 2Km, 12~55VDC Power Input; Version 2 Hardware
LMP-0501-M-24-T-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Multi-Mode 2Km, 12~55VDC Power Input; Version 2 Hardware; EOT: -40°C to 75°C
LMP-0501-S3-24-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Single-Mode 30Km, 12~55VDC Power Input; Version 2 Hardware
LMP-0501-S3-24-T-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Single-Mode 30Km, 12~55VDC Power Input; Version 2 Hardware; EOT: -40°C to 75°C
LMP-0501-ST-M-24-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Multi-Mode 2Km, 12~55VDC Power Input; Version 2 Hardware
LMP-0501-ST-M-24-T-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Multi-Mode 2Km, 12~55VDC Power Input; Version 2 Hardware; EOT: -40°C to 75°C
LMP-0501-ST-S3-24-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Single-Mode 30Km, 12~55VDC Power Input; Version 2 Hardware
LMP-0501-ST-S3-24-T-V2	5-Port Industrial PoE+ Managed Ethernet Switches w/4*10/100Tx (30W/Port) and 1*100Fx Single-Mode 30Km, 12~55VDC Power Input; Version 2 Hardware; EOT: -40°C to 75°C

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave

Ste 1200

Sheridan

WY 82801

USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park

Stone Business Park

Stone

ST15 0YJ

United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660