



RSC-IMX8M

3.5" NXP IMX8M SBC

- > NXP® i.MX8M Quad ARM Cortex A53 Quad Core Up to 1.5GHz; Cortex-M4 core processor(Default)
- > 16GB eMMC
- > 2GB Onboard LPDDR4 Memory (expandable up to 4GB Max)- industry(Default)
- > Display (HDMI / LVDS / MIPI DSI)
- > Dual GLAN
- > JTAG
- > OTG USB 3.0 Type C (Data only)
- USB 3.0 Type A
- USB 3.0 Pin Header
- > MIC in
- Line out
- Speaker out
- Hand Phone out
- > Watch dog / I2C / MIPI CSI 1/2 function
- > M.2 Key E Socket (For WiFi/BT)
- > M.2 Key B Socket + SIM Socket (For LTE)
- > DC IN 12~24V
- > Industry Operating temperature: -40~85 Degree (Default)
- Consumer Operating temperature: 0~85 Degree
- > OS Support Linux Yocto 2.5 (First) & Android 10 (coming soon)

+ Spec

-System Information-	
Processor	NXP® i.MX8M Quad ARM Cortex A53 Quad Core Up to 1.5GHz; Cortex-M4 core processor
System Memory	2GB RAM
Storage	
Storage	eMMC 16GB
I/O	
USB Port	OTG USB 3.0 Type C (Data only) USB 3.0 Type A USB 3.0 Pin Header
COM Port	Extend Board (4 x RS232/485 , 1 x GPIO)(Default)
External I/O Connector	1 x USB 3.0 Type A (Vertical type) 2x RJ45 connector with indicate LED Industry Version: 2pcs(Default) , Consumer Version: 1pcs 1 x HDMI connector (Vertical type) 1 x USB 3.0 Type C 1 x Micro SD socket 1 x Hand Phone 1 x Reset 1 x Power LED (Green)
Internal I/O Connector	1 x Front Panel connector 2 x MIPI CSI connector 1 x DC connector with lock Header 1 x TAG connector 1 x MIPI DSI connector 1 x LVDS connector 1 x Back Light connector 1 x I2C connector 1 x USB connector 1 x 2230 M.2 for WiFi/BT (PCIe& USB Channel) 1 x 3042 M.2 for 3G/4G Module (USB Only) 1 x SIM Socket connector 1 x 2x20P Header connector 1 x 1x2P Header (R) connector 1 x 1x2P Header (L) connector 1 x Line-Out Header with 12V out 1 x Mic-In Header connector
Display	
Multiple Display	Display (HDMI / LVDS / MIPI DSI)
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	LAN 1: Intel I210 LAN 2: AR8033
Ethernet Interface	2 x RJ45 Connectors for Dual Gigabit LAN Industry Version: 2pcs(Default) Consumer Version: 1pcs
Mechanical & Environmental	
Operating Temperature	Industry Operating temperature: -40~85 Degree (Default) Consumer Operating temperature: 0~85 Degree
Storage Temperature	-40°C ~ 85°C



Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	0.16kg
Power Requirement	DC 12 ~ 24V Power Input
Power Mode	DC Jack
Dimension (L x W)	(146.05mm x 101.6mm)
Software Support	
OS Information	Linux Yocto Version 3.0 Android Version 10
Ordering Information	
Ordering Information	RSC-IMX8M-XXX

www.avalu.com.tw

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508

Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050

Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660