R17L100-RKA1ML

17" Rack Mount Protective Glass Defense Display

KEY FEATURES

- Compliant MIL-STD 810G/ MIL-STD 461E glass defense
- Rack mount mechanical design, supports VESA mount
- High image quality, 1280 x 1024 pixels resolution Rack Mount Protective Glass Defense Display
- AR protection glass, Rack Mount Protective Glass Defense Display
- Defence-grade power connector (MIL-DTL-38999/1)
- AC 100~240V, Universal, ±10%; DC 9~36V, ±10% (Optional)
- Build-in Light Sensor for Auto Brightness Control
- Resistive Touch (Optional)
- Glass defense

CE FC COMPLIANT MIL-STD 461F COMPLIANT MIL-STD 810G

SPECIFICATIONS

Display

Resolution	1280x1024	**Size**	17 inches
Contrast Ratio	1000:1	**Panel Brightness**	350 nits
Display Color	16.7M Colors	**View Angles**	85,85,80,80
Active Area	337.920x270.336 mm	**Touch / Glass**	AR Protection Glass EMI ITO Glass (Optional) 5-wire Resistive Touch (Optional) 5-wire Resistive Touch with EMI Mesh Filter (Optional)

Environment

Operating Humidity	10% to 95% RH	**Operating Temperature**	-20°C~60°C
Storage Temperature	-30°C~70°C		

Compliance

MIL-STD 461E/F	RE101 / RE102 CE101 / CE102 with EMI Glass / Touch(Optional) RS101 / RS 103 CS101 / CS 106 / CS 109 / CS 114 / CS 115 / CS 116	**MIL-STD 810F/G**	Vibartion Method 514.5 Humidity Method 507.4 Transit Drop Method516.5

Certification

Certification	CE, FCC

IO Ports

Video	1 x 15 Pin D-Sub 5 x BNC 1 x DVI-D

Mechanical

Dimension	482.6 x 399.3 x 69.6 mm	**Mounting**	Rack Mount/ VESA Mount
Enclosure	Metal Housing with Aluminum Bezel	**Cooling System**	Fanless Design

Power

| Power Rating	AC 100~240V, Universal, ±10% DC 9~36V, ±10% (Optional)
Accessory	
Accessory	1 x User Manual(Hardcopy) 1 x Power Cord MIL-DTL-38999/1 1 x VGA Cable 1 x DVI Cable 1 x VGA to 5 BNC Shielding Cable
Control	
Button	7 key: Power Decrease Increase Exit/ Auto Menu Day/ Night Lock/ Unlock

DIMENSIONS UNIT:MM

- ❶ OSD Control Panel
- ❷ Power Input
- ❸ RGBHV
- ❹ VGA
- ❺ DVI

NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. If you require an external test report, Winmate will charge an NRE fee.
3. Please contact our sales representative if you need further product information.
4. All specifications are subject to change without prior notice.
5. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.

Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508
Support: +1 347 719 4508

1309 Coffeen Ave
Ste 1200
Sheridan
WY 82801
USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050
Support: +44 (0)1785 879 050

Unit A5 Douglas Park
Stone Business Park
Stone
ST15 0YJ
United Kingdom

VAT Number: 120 9546 28
Business Registration Number: 07699660