

AIR6NO-C-MB NX I/O

YUAN

Card Size AI Edge with Multi AIoT Expansion

Features

- · Powered by NVIDIA® Jetson Orin™ NX Super up to 157 / 117 TOPS
- · Business Card Size
- · 3×M.2, 8×MIPI CSI-2 Lanes and RS232 / RS485 / GPIO
- · 2×USB3.2 Gen2
- · 1×Mini DisplayPort



Specifications

SOM 1 CPU 8 6 6 GPU 1 Al Performance 1 System Memory 1 Interface 5 Storage 1 Display Interface 1 Ethernet 1	1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	NVIDIA Jetson Orin™ NX 8GB Super 6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3 ture GPU with 32 Tensor Cores 117 TOPS 8GB 128-bit LPDDR5 102.4GB/s	NVIDIA Jetson Orin™ Nano 8GB Super 6-Core Arm® Cortex®-A78AE v8. 1024-core NVIDIA Ampere Architecture GPU with 32 Tensor Cores 67 TOPS 8GB 128-bit LPDDR5 102 GB/s	NVIDIA Jetson Orin™ Nano 4GB Super 2 64-Bit CPU 1.5MB L2 + 4MB L3 512-core NVIDIA Ampere Architecture GPU with 16 Tensor Cores 34 TOPS 4GB 64-bit LPDDR5 51 GB/s					
1	16GB Super 8-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 2MB L2 + 4MB L3 1024-Core NVIDIA Ampere Architect 157 TOPS 16GB 128-bit LPDDR5 102.4GB/s Supports External NVMe 1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	8GB Super 6-Core Arm* Cortex*-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3 ture GPU with 32 Tensor Cores 117 TOPS 8GB 128-bit LPDDR5	8GB Super 6-Core Arm® Cortex®-A78AE v8. 1024-core NVIDIA Ampere Architecture GPU with 32 Tensor Cores 67 TOPS 8GB 128-bit LPDDR5	4GB Super 2 64-Bit CPU 1.5MB L2 + 4MB L3 512-core NVIDIA Ampere Architecture GPU with 16 Tensor Cores 34 TOPS 4GB 64-bit LPDDR5					
GPU 1 Al Performance 1 System Memory 1 Interface 5 Storage 1 Display Interface 1 Ethernet 1	64-Bit CPU 2MB L2 + 4MB L3 1024-Core NVIDIA Ampere Architect 157 TOPS 16GB 128-bit LPDDR5 102.4GB/s Supports External NVMe 1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	64-Bit CPU 1.5MB L2 + 4MB L3 ture GPU with 32 Tensor Cores 117 TOPS 8GB 128-bit LPDDR5	1024-core NVIDIA Ampere Architecture GPU with 32 Tensor Cores 67 TOPS 8GB 128-bit LPDDR5	512-core NVIDIA Ampere Architecture GPU with 16 Tensor Cores 34 TOPS 4GB 64-bit LPDDR5					
Al Performance 1 System Memory 1 Interface Storage S Display Interface 1 Ethernet 1	157 TOPS 16GB 128-bit LPDDR5 102.4GB/s Supports External NVMe 1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	117 TOPS 8GB 128-bit LPDDR5	Architecture GPU with 32 Tensor Cores 67 TOPS 8GB 128-bit LPDDR5	Architecture GPU with 16 Tensor Cores 34 TOPS 4GB 64-bit LPDDR5					
1 1 1 1 1 1 1 1 1 1	16GB 128-bit LPDDR5 102.4GB/s Supports External NVMe 1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	8GB 128-bit LPDDR5	67 TOPS 8GB 128-bit LPDDR5	34 TOPS 4GB 64-bit LPDDR5					
1 1 1 1 1 1 1 1 1 1	16GB 128-bit LPDDR5 102.4GB/s Supports External NVMe 1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo	8GB 128-bit LPDDR5	8GB 128-bit LPDDR5	4GB 64-bit LPDDR5					
Storage	1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo								
1 Display Interface	1×Micro SD Card Slot 1×Mini DP1.4 1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCIe Gen4×4 Slo								
Ethernet 1	1×RJ45 for 10/100/1000Mbps Ether 1×M.2 2280 M Key PCle Gen4×4 Slo			Supports External NVMe 1×Micro SD Card Slot					
1	1×M.2 2280 M Key PCIe Gen4×4 Slo		1×Mini DP1.4						
		1×RJ45 for 10/100/1000Mbps Ethernet (DHCP Client)							
	1×M.2 2280 M Key PCIe Gen4×4 Slot 1×M.2 2230 M Key PCIe Gen4×2 Slot (Nano: Gen3×2) 1×M.2 2230 E Key PCIe Gen4×1 Slot (Nano: Gen3×1)								
USB 1	1×USB3.2 Gen2 (Type-C) 1×USB3.2 Gen1 (Type-A)								
	8 MIPI CSI-2 Lanes (D-PHY 2.1, Support MIPI Camera, Capture Card)								
Peripheral Communication 8 1 1 1 1 2 1	10 Pin Header 1×USB2.0 4×GPIO 1×12C 6 Pin Wafer 1×UART (*) 4 Pin Header 5V / 3A 8 Pin Phoenix Connector (CON2) 1×GPIO 2×12C 8 Pin Phoenix Connector (CON3) 1×RS232(*) 1×RS485 1×GPIO 2 Pin Header (CON4) 1×GPIO 2 Pin Header (CON5) 1×GPIO								
	* Diagram India 141 DC0000 C0001	* Please select either RS232 of 8 Pin Phoenix Connector or UART of 6 Pin Wafer to use Firmware Upgradable							



Development Environment				
JetPack	6.2 or Higher			
Environment				
Power Supply	DC input : 12~36V			
Power Consumption	ТВА			
Operating Temperature	0°60°C with Airflow			
Storage Temperature	-20~80 °C			
Certification	CE, FCC			

SDK / Software

Video Feature						
SOM	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano		
JUIVI	16GB Super	8GB Super	8GB Super	4GB Super		
	AV1 (UHP)					
	1×4K60 3×4K30 6×1080p60 12×1080p30		_			
Video Encode	H.265 (UHP)		1080p30 supported by 1-2 CPU o	1080p30 supported by 1-2 CPU cores		
	1×4K60 3×4K30 6×1080p60	12×1080p30				
	H.264 (UHP)					
	1×4K60 2×4K30 5×1080p60	11×1080p30		AM (AA : 2 51)		
Video Decode	AV1 (Main Profile)		AV1 (Main Profile)			
	1×8K30 2×4K60 4×4K30 10×1080p60 20×1080p30		1×4K60 2×4K30 5×1080p60 10×1080p30			
	H.265 (Main, Main10)		H.265 (Main, Main10) 1×4K60 2×4K30 5×1080p60 11×1080p30			
	1×8K30 2×4K60 4×4K30 9×1080p60 18×1080p30		H.264 (Baseline, Main, High)			
	H.264 (Baseline, Main, High) 1×4K60 2×4K30 5×1080p60	l 11x1080n30	1×4K30 3×1080p60 7×1080p30			
	VP9 (Profile 0, Profile 2)		VP9 (Profile 0, Profile 2)			
	1×4K60 3×4K30 7×1080p60 15×1080p30		1×4K60 2×4K30 5×1080p60 10×1080p30			
SDK	TV4KOO TV4KOO 1V1000hoo T0V1000hoo					
	Capture	<u> </u>				
	High Performance Renderer					
	Image Snapshot					
	De-interlace, Alpha Blending Engine					
	Auto Signal Detection					
	2D/3D Video, Audio and VANC Streams Capture					
	Record					
	Encrypt / Sync / Clone / Recording					
OCAR	Time-Shifting / Rewind / Pre-Event / Recording					
QCAP	Multi-Streams (3D) Recording Animation Transition Effect					
	Animation Transition Effect Video Cropping, Scaling and Alpha Blending Engine					
	Stream					
	Stream 2D/3D Universal Stream Client					
	2D/3D Multi-Stream Stream Server					
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)					
	Animation Transition Effect					
	Video Cropping, Scaling and Alpha Blending Engine					
	*Separate License Required					
	AI SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications					
	Face Recognition					
	Objects Detection					
QDEEP	Objects Segment Optical Character Recognition					
	Optical Character Recognition					
	License Plate Recognition Customizable Video AI Functions Upon Request					
Software (Optional)	Custoffizable video Al Fullction	is opon nequest				
Software (Optional)	Web Based User Interface		-			
			The management of the second o	The state of the s		
	Encode / Decode					
	AV1, H.26X Color Format Adjust					
	Color Format Adjust 444 / 422 / 420, 10Bit / 8Bit Select					
Xtreamer	444 / 422 / 420, 108it / 88it Select Record					
	MP4, TS					
	Stream / Network		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the s		
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)					
	*Separate License Required					

Mechanical

· Dimension: 90mm × 55mm

 \cdot Weight: 165g (With SOM and Fan)



- * All registered trademarks are the property of their owners. The photo is for reference only.
- * Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.

Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.



Assured Systems

Assured Systems is a leading technology company with over 1,500 regular clients in 80 countries, deploying over 85,000 systems to a diverse customer base in 12 years of business. We offer high-quality and innovative rugged computing, display, networking and data collection solutions to the embedded, industrial, and digital-out-of-home market sectors.

US

sales@assured-systems.com

Sales: +1 347 719 4508 Support: +1 347 719 4508

1309 Coffeen Ave Ste 1200 Sheridan WY 82801 USA

EMEA

sales@assured-systems.com

Sales: +44 (0)1785 879 050 Support: +44 (0)1785 879 050

Unit A5 Douglas Park Stone Business Park Stone ST15 0YJ United Kingdom

VAT Number: 120 9546 28

Business Registration Number: 07699660